

Door Solutions Catalogue 2021/22

ASSA ABLOY

Experience a safer and more open world

Door openings made easy.

Download and get started in programs such as Autodesk® Revit®.





ASSA ABLOY Openings Studio® revolutionizes the way you create and visualize 3D doors, frames and hardware in your building projects. Our Building Information Modeling (BIM) software tools offer complete door opening information to help architects, contractors and building owners design, construct and maintain products in their buildings.



- Fully integrated door opening solutions save you time and effort
- Compliant with building regulations and project requirements for peace of mind
- Robust version control streamlines information sharing and specification
- Real-time 3D visualisation, to enhance users' understanding and experience

To download ASSA ABLOY Openings Studio or contact us, visit ASSA ABLOY on the link www.assaabloyopeningsolutions.co.za/en/specification-bim/

Or simply scan the QR code



Table of Contents

Introduction:	Conditions of Sale	
	Branches & Offices	iv
	Environmental Policy	V
	Product Maintenance	vi
	Handing Explanation	vii
	Glossary of Terms	viii
Catalogue:	Yale Residential Solutions	1
	Digital Access Solutions	35
	Aperio	36
	SMARTair	40
	eCLIQ	45
	Black Series	64
	Door Furniture	70
	Valli & Valli	71
	Lever Handles	78
	Pull Handles	89
	Door Hardware	97
	Cylinders	115
	Door Closers	124
	Panic Escape Devices	138
	Sliding & Folding Door Gear	149
	Locksets	159
	Mortice Locks	164
	Nightlatches & Rimlocks	176
	Glass Solutions	180
	Padlocks	187

Conditions of Sale

ASSA ABLOY

Definitions:

- 1. Company, also referred to as ASSA ABLOY, shall mean ASSA ABLOY (SA) (Pty) Limited.
- 2. Buyer shall mean the party to whom the order acknowledgment, Invoice and Statement is addressed. In particular, the Buyer's attention is drawn to clauses which have been highlighted, where the Buyer's risk may be limited, risk or liability assumed or an indemnity given by the Buyer.

Payment:

- 1. Terms of payment are 30 days from date of monthly statement for which a 2.5% settlement discount may be taken.
- 2. Should payment not be received within the 30 day period, the settlement discount is automatically disallowed and the account is deemed overdue and immediately payable.
- 3. Interest at prime will be charged on all overdue accounts.
- 4. If payment is not received within five (5) working days of the due date, credit facilities may be suspended immediately and no further goods will be supplied until payment of any overdue portions of the account are received.
- 5. We reserve the right to totally withdraw credit facilities without notice when an account regularly exceeds the credit facilities granted.
- 6. For the sake of clarity, an account is deemed to have been honoured either by payment of cash at ASSA ABLOY's official place of business or by cleared funds having been received at ASSA ABLOY's bank.
- 7. Payment through ASSA ABLOY's Electronic Banking Facilities is an approved and preferred method of payment provided a faxed copy of the deposit slip is sent to ASSA ABLOY immediately after the deposit is made.
- 8. ASSA ABLOY shall have retention of title to all goods for which payment has not been received in full by ASSA ABLOY.
- 9. No refund will made for goods manufactured to Buyer's specific requirements, where these are different to the standard product. This includes Master Keyed suites.

Delivery:

1. All deliveries are standard 3 -5 days. Should an overnight delivery be required, an additional fee of R350.00 will be charged.

Carriage and Place of Delivery:

- **1. Republic of South Africa** In all cases delivery will be on a carriage and insurance paid basis, ex Johannesburg, by ASSA ABLOY designated and approved road transport, to any destination in the Republic of South Africa It is the responsibility of the Buyer to indicate clearly on the order, the address to which the goods should be consigned and no subsequent costs will be borne by ASSA ABLOY in the event of the Buyer's error.
- **2. Over-Border Freight & Documentation Fee** All goods dispatched for Namibia, Lesotho, Swaziland & Botswana will be charged a R150.00 Over-Border Freight Fee and a R50.00 Over-Border Documentation Fee
- 3. Export All goods dispatched for Export will be Carriage Forward and are F.O.B. Johannesburg.
- **4. Non-returnable Containers** Standard containers for standard bulk packing will be supplied free of charge, but any special packing, including non-returnable wooden export cases, will be charged at extra cost. This will be quoted based on delivery requirements.
- **5. Damage** Non-receipt of goods or goods delivered in a damaged condition shall be notified to ASSA ABLOY within ten (10) business days. The receipt of ASSA ABLOY's invoice shall be the notification of dispatch upon which the Buyer shall make a non delivery claim.
- **6. Weight** The goods to be dispatched to the customer shall be packed and weighed by ASSA ABLOY at the place of dispatch. The packed weight shall be marked on the packaging. The Buyer should check that the goods conform to their description and weight as soon as possible after they are received. Should goods be short delivered, the Buyer has 48 hours in which to submit a claim and notify ASSA ABLOY. No claims for short delivery will be entertained unless the Buyer can prove that the goods delivered are not of the weight declared on the packaging, and this was done within 48 hours of delivery.

Minimum Invoice Value and Pack Quantities:

1. All orders with a value of less than R 3,000.00 excluding VAT shall have a R 100.00 minimum order surcharge (MOS) applied.

i

2. Stock will only be sold in multiples of standard pack quantities as shown in the price list. Non-conforming quantities, will be subject to a R 10.00 Break Bulk fee (per box) on the price indicated.

Conditions of Sale

ASSA ABLOY

Return of Goods:

- 1. Unless specifically stated in writing, ASSA ABLOY does not supply goods on a "Sale or Return" basis.
- 2. The Buyer may only return goods to ASSA ABLOY after receipt of a Return Material Authorisation (RMA), which shall be issued through the ASSA ABLOY sales department after authorization by the appropriate manager.
- 3. In order for a RMA to be issued, full particulars of the ASSA ABLOY invoice and dispatch note number, together with quantities, item numbers and description of goods and the reason for return, must be provided by the Buyer.
- 4. Goods being surplus to requirements or wrongly ordered by the Buyer do not constitute a reason for requesting an RMA
- 5. No goods should be returned to ASSA ABLOY without an RMA. Goods will still be charged to the Buyer's account, with payment expected on the relevant due date.9. ASSA ABLOY undertakes to only issue a credit note for any agreed RMA circumstances to refunded for reasons of unsuitability.
- 6. The costs of shipping returned goods will be for the account of the Buyer and no carriage will be payable by ASSA ABLOY.
- 7. Any goods that ASSA ABLOY accepts back for credit due to no fault of ASSA ABLOY shall be subject to a 15% handling charge, provided the goods are in the same condition as when they left ASSA ABLOY.
- 8. Should restoration be required to returned goods, the further cost of such restoration will be deducted from the credit allowed. unless the goods are returned in terms of the provisions of Section 56 of the Consumer Protection Act 68 of 2009.
- 9. ASSA ABLOY undertakes to only issue a credit note for any agreed RMA if the goods are returned in terms of the provisions of Section 56 of the Consumer Protection Act 68 of 2009.
- 10. No refund will made for goods manufactured to Buyer's specific requirements, where these are different to the standard product. This includes Master Keyed suites.

Credit Notes:

- 1. ASSA ABLOY will issue the Buyer with a Company credit note under the following conditions providing a RMA is issued in accordance with the procedures in paragraph 4 above if the goods are returned.
 - 1.1 The goods supplied are proven to be faulty or not reasonably suitable for the purpose for which they are generally intended (subject to ASSA ABLOY's quality control inspection and report). Section 55(2) CPA
 - 1.1.1 Are not of good quality, in good working order and free of any defects
 - 1.1.2 Not usable and durable for a reasonable period of time, having regard to the use to which they would normally be put and to all the surrounding circumstances of their supply; and
 - 1.1.3 Don't comply with any applicable standards set under the Standards Act, 1993 (Act No. 29 of 1993), or any other public regulation]
 - 1.2 The goods delivered did not conform to the goods that were ordered.
 - 1.3 The goods were short delivered.
 - 1.4 The goods were incorrectly priced or discounted.
 - 1.5 As set out in 4.9 above.

Warranty:

- 1. In addition to the statutory warranties in terms of section 56 of the Consumer Protection Act 68 of 2009 all products manufactured or distributed by ASSA ABLOY carry a warranty of 1 year from date of purchase against manufacturing defects in materials or workmanship. This warranty is subject to appropriate application and correct installation .
- 2. ASSA ABLOY will not accept any claim for any consequential losses arising out of a warranty claim.
- 3. Warranty claims will not be credited or taken back for cash refund.
- 4. The warranty does not cover error of fitment.
- 5. The warranty is invalidated if the ASSA ABLOY supplied product is used in combination with non-approved products from a third party.
- 6. Should ASSA ABLOY be required to do a site visit for Warranty checks and it is found that the fault is not that of an ASSA ABLOY product, a fee of R350.00 per half day will be charged. This excludes, travel, accommodation and meals.

For more detailed information on ASSA ABLOY's warranties and guarantees go to: https://www.assaabloyopeningsolutions.co.za/en/about-us/warranties-and-guarantees/

Conditions of Sale



Prices:

- 1. Prices will always be those ruling at date of dispatch unless a specific fixed price quotation has been agreed by ASSA ABLOY when submitting a written quotation.
- 2. ASSA ABLOY will always endeavour to give as much notice as possible of any price increases but due to fluctuating costs of materials linked to local inflation and monetary foreign exchange rate fluctuations, prices may be subject to change without notice.
- 3. The Buyer should check for any price increases due to foreign exchange fluctuation before placing a firm order for large quantities of these products. Any change in exchange rate of more than 5% may result in a price revision.
- 4. All prices quoted are exclusive of Value Added Tax.
- 6. A 5% packaging premium will be charged if it is requested that lock components be packed as a lockset. Stock orders will be rounded to the nearest case quantity.
- 7. A packaging premium on all Pack-By-Door requests will be charged at R 10.00 per door.

Delivery:

1. All delivery dates are given in good faith but any delay in delivery for any reason shall not constitute any breach of contract and no claims arising out of late delivery shall be considered. [Section 19(6) CPA]

Specification:

1. Unless otherwise stated, specifications generally will conform to that quoted in the Company's latest catalogue, but we reserve the right to alter such specification without notice. Supplementary catalogue pages as issued from time to time will be deemed to be part of the Company's latest catalogue.

General:

1. No responsibility is accepted for delay caused by war, force majeure, restraint or control by government, strikes, lockouts, disputes, accidents to works, plant or machinery or any other circumstances beyond control, which affect or interfere with the production or delivery of goods sold, and we reserve the right to cancel or suspend orders or deliveries on the occurrence of such eventualities.

Branches & Agent Offices

Head Office - ASSA ABLOY (SA) Pty Ltd, Roodepoort

176 Progress Road, Technikon, Tel: +27 11 761 5000 Roodepoort, Johannesburg, 1724

PO Box 146, Roodepoort, 1725

Fax: +27 11 766 3570

za.info@assaabloy.com

www.assaabloyopeningsolutions.

co.za

ABLOY za.abloy.info@assaabloy.com www.abloy.co.za

Architectural za.projects@assaabloy.com www.assaabloyopeningsolutions.

co.za

ASSA ABLOY Sales za.sales@assaabloy.com www.assaabloyopeningsolutions.

co.za

Customer Care za.care@assaabloy.com

9 Nickel Road, Technikon, Roodepoort

Electronic Door Solutions za.eds@assaabloy.com www.assaabloyopeningsolutions.

CO.Z

www.besam.co.za

www.mul-t-lock.co.za

Entrance Systems za.besam.marketing@assaabloy.com

Exports za.export@assaabloy.com

Henderson za.info@assaabloy.com www.henderson.co.za

Hospitality za.info@assaabloy.com www.assaabloyopeningsolutions.

co.za

Mul-T-Lock za.multilock.quote@assaabloy.com

Traka za.info@assaabloy.com www.traka.co.za
Yale Security za.yale.info@assaabloy.com www.yalelock.co.za

Yale Security Sales za.yale.orders@assaabloy.com

ASSA ABLOY (SA) Pty Ltd, Cape Town

Northgate Business Park, 10 Gold Street,

Northgate Estate, Brooklyn

Tel: +27 21 531 0770

Fax: +27 21 531 5366

PO Box 1111 za.wcape@assaabloy.com Cape Town, 8000

ASSA ABLOY (SA) Pty Ltd, Durban

Newton Park, 6055

91 Escom Road, New Germany, IDS Electronics Building

Tel: +27 31 312 5151

Durban, Kwa-Zulu Natal, 4001

Fax: +27 31 312 5151

za.kzn@assaabloy.com

ASSA ABLOY (SA) Pty Ltd, Port Elizabeth

60 5th Avenue, Newton Park
Port Elizabeth, 6055
Fax: +27 41 364 1565
Fax: +27 41 364 1431
Za.ecape@assaabloy.com

Environmental Policy

Commitment:

ASSA ABLOY is committed to meeting the climate change challenge. Our strategy is to reduce our carbon footprint step by step, beginning with our own manufacturing. Our objective is to achieve continuous improvement in energy consumption, with a focus on replacing the largest energy usage areas with supply from renewable energy sources. In parallel we will continue to explore and investigate our other carbon emissions aiming to reach measurable values. Our priorities are manufacturing, transport of goods and innovation.

ASSA ABLOY has established a roadmap relating to activities concerning transport and its impact on the environment. We are committed to:

- 1. Raising the environmental awareness in all transport activities
- 2. Investigating modes of transportation and regions where the environmental impact can measured in terms of emission or others, and related costs
- 3. Investigating possibilities to decrease the environmental impact, through increased co-ordination, lowering of emissions, choice of transportation modes, such as rail instead of road, ship instead of air, renewable energy etc.

The excellence of our suppliers in terms of quality, delivery time and cost is important to ASSA ABLOY and we rely on our suppliers to be committed to sustainable developments. Hence suppliers are evaluated on how well they manage to put business practices in place which promote long-term excellence in environmental, social and ethical performance.

ASSA ABLOY, through our well established process of our product development, will secure products with a sustainable profile. By reducing the use of chemicals, the energy used and the amount of material needed to fulfil the requirements for security, safety and convenience, we will not only implement our sustainability strategy but also lower our costs. To reuse and recycle the material from our products and our manufacturing has been as natural as it has been logical for many years.

ASSAABLOY SA is committed to continued sustainability and lead change, seeking ways to eliminate, reduce, recycle, reuse, control and conserve the use of energy and material resources and the disposal of waste, to minimize risks and take measures to prevent pollution. Through the design and planning of its operations and products as well as the use of technology, substitution and resource reduction of significant environmental aspects, we aim to minimize or eliminate their potential impacts.

Our Environmental Policy:

We meet our legal expectations

We continuously develop strategies to reduce consumption of resources, prevent pollution and improve the overall environmental impact from our operations and products along the value-chain.

We continually seek ways to improve our work environment and to reduce risks that can cause accidents and pollution We require management personnel to be responsible for implementing and upholding this policy in their business units and groups through awareness, training, measurement and reporting.

We encourage and foster openness and communication for our policy with our stakeholders.

We apply our policy in all business transactions and expect our employees, partners and suppliers to apply them as well. We will strive to implement certifiable environmental management systems at all local production units.

Management Systems:

ASSA ABLOY has a systemic approach to sustainability. We are of the opinion that systems are necessary and valuable if used correctly and effectively.

Systems build all elements of the sustainability strategy and approach together as one. However, systems need both qualitative and quantitative measures & objectives.

As a guiding principle we are committed to implement and maintain ISO 14001 for our environmental management system. We have also defined a set of floor requirements and more specific tools and programs that strive to define the actual performance level we want to achieve. Additionally we have a system for internal audits that cover some system elements, and more extensively the floor requirements and technical specifications of how we want our manufacturers to operate.

Product Maintenance

General Maintenance:

Atmospheric deposits of dust and grime are the major causes of premature deterioration of surface coatings because of the wide variety of chemical pollutants in the atmosphere. When such chemicals become damp, they often initiate local attack, generally in the form of pitting on the surface finish. Dampness can rarely be prevented but dust and grime can usually be removed by regular attention such as dusting with a dry cloth or by washing neglected surfaces with clean or soapy water. Little and often should be the rule, avoiding the use of even the mildest abrasive. The application of wax or silicone polishes can be beneficial because of the barrier layer created between surface finish and atmospheric deposits.

Locks and Latches:

The correct operation of a lock or latch, assuming correct fitting, is often affected by movement of the door or frame occurring, perhaps, due to distortion influenced by climatic conditions or wear on hinges or pivots inducing door drop.

The usual effect from these conditions is inability of the latch and dead bolts to easily engage the striking plate or keep, requiring an adjustment to their position on the frame, or an adjustment to the lip of the striking plate to provide a more favourable striking angle.

Freedom of operation of the latch action in conjunction with the striking plate or keep is particularly important when the door is fitted with a closing device and also, of course, on fire resisting doors.

It is also important that the holes in the frame behind striking plates are deep enough and free from foreign matter, to ensure unrestricted movement of the bolt or bolts.

Lubrication, when required in the context of free latching of a door, need only be applied to the sides and striking face of a latch bolt.

Pin tumbler and disc tumbler cylinders should be lubricated with a PTFE lubricant.

Door Closing Devices:

There is little routine maintenance to be carried out on door closing devices, lubrication generally being limited to the application of a little light oil on visible joints, such as those on the arms of overhead patterns.

The closer should be examined periodically to ensure that the door is closing correctly and that the appropriate valve adjustments have been made for the closing and latching speed of the door.

Exit Hardware:

Regular inspection and maintenance is necessary in the interests of public safety. Attention must be given to opening and closing with adjustments as necessary to compensate for any door or frame movement. Floor sockets should be cleaned out to prevent foreign matter impeding bolt movement. Lubrication will be limited to the application of a little light machine oil to the pivots of the top tripper mechanism of panic bolts, and to the head of panic latches.

Pull Handles & Furniture:

Pull handles and lever knob furniture should be checked periodically for secure fixing. Problems occur where wood screws are incorrectly installed and where the material to which the products are fixed is unsuitable.

It is also important to check that knob and lever furniture fully withdraws the latch bolt, again for safety.

Coastal Maintenance:


Stainless Steel furniture in coastal regions should be regularly dusted. Occasionally wash with warm soapy water, dry and polish.

Handing Explanation

A hinged door opens in one of four ways shown on the diagrams below. The number of the opening or the hand of the lock should be stated except for those listed below which suit all ways of door opening:

- Cylinder and other rim locks
- Cylinder rim deadlocks
- Double hand rim locks
- Ordinary mortice locks and latches with plain forends
- Mortice locks with rebated forends
- Straight cupboard locks

Striking plates instead of staples are supplied for rim locks and latches if ordered for doors opening outwards as number 3 or 4.




Rim Lock Mortice Lock Lockset	- - -	Left Hand Left Hand Left Hand
Rim Lock Mortice Lock Lockset	- - -	Right Hand Right Hand Right Hand
Rim Lock Mortice Lock Lockset Cupboard Lock Wardrobe Lock Locker Lock	- - - - -	Right Hand / Reverse Bolt Right Hand / Reverse Bolt Right Hand / Reverse Bolt Right Hand Right Hand Right Hand
Rim Lock Mortice Lock Lockset Cupboard Lock Wardrobe Lock Locker Lock	- - - -	Left Hand / Reverse Bolt Left Hand / Reverse Bolt Left Hand / Reverse Bolt Left Hand Left Hand Left Hand

Hands of Rebated Locks:

Pairs of folding doors with rebated edges require rebated mortice locks or latches. The standard width of rebate (W) is 13mm unless otherwise ordered.

Mortice locks with reversible rebated forends and striking plates suit all ways of opening and rebate shown on diagrams 5-8 below. For other patterns and all locksets quote the number of the opening or the hand as given below.



Mortice Lock - Left Hand

Mortice Lock - Right Hand

Mortice Lock - Right Hand

Mortice Lock - Right Hand / Open Out
Lockset - Right Hand / Open Out
Lockset - Left Hand / Open Out

Left Hand / Open Out

Lockset

Glossary of Terms

ASSA ABLOY

Adjustable Closing Force

Inbuilt function of any door closing device that allows the closing moment of the device to be adjusted (see also EN 1154)

Adjustable Power

(see "adjustable closing force")

Alike Change

(see "keyed alike)

Anti-drill Plate

Steel plate with sufficient hardness to resist penetration by a HSS drill bit.

Anti-lift Device / Anti-lift Block

Device which prevents displacement movement in the plane of a door or window

Anti-thrust Action

Latch action in which the latch bolt, when fully thrown, resists being forced back by end pressure

Anti-thrust Bolt

Spring actuated bolt which cannot be pushed back once it has been fully thrown into a correctly positioned locking plate

Anti-thrust Slide / Snib Bolt

Component which contacts the locking plate to activate the anti-thrust bolt mechanism

Armoured Rose

Cylinder rose with features to protect it from physical attack

Automatic Bolt

Bolt which self-engages as the door is closed

Automatic Dead Latch

Dead latch with bolt that deadlocks automatically, as the door is closed

Automatic Lock

Lock comprising an automatic bolt

Backcheck

A 'cushioning' effect to prevent damage to door and adjoining structure if door is thrown or blown open.

Backplate

Separate component on back of product providing the fixing means, and (where applicable) the bearing(s) for rotating spindle(s) etc.

Backset

Distance from the outer face of the forend (or faceplate if fitted) to the centre-line of the keyhole and/or follower

Ball Locking

A method of locking used in high security padlocks. Hardened steel ball bearings are pushed outwards to engage with round indents on the shackle

Bathroom Lock

Privacy lock with latch bolt operated by lever handle or knob from both sides, and an additional deadbolt operated by thumb slide, thumb turn etc. from inside only

Blank (of key)

Key which has not been cut

Body

The main section of a product usually containing the working mechanism

Bolt (part of lock or latch)

Moving part of a lock or latch that provides engagement between leaf and frame

Bolt (complete product)

Device for securing, or helping to secure, an opening leaf in the closed position, where movement of the engaging member (shoot) is effected from one side only, either directly by hand (thumb slide, etc), or via a lever, knob or non-differ key mechanism

Bolt-through Fixing

Method of attachment whereby the fixing means pass right through the door, window etc.

Bottom Pin / Pin

Pin of a cylinder mechanism that is located in the plug and makes contact with the key

Bow (of key)

Enlarged portion of key at end remote from blade/bit

Burr

Plug which closes off the outer end of an individual pin chamber in a cylinder housing

Cabinet Lock

Generic term for a variety of locks fitted to items of furniture such as cupboards, drawers, chests, boxes etc.

Cam

Component attached to the end of a cylinder plug to transmit locking/unlocking movement

Cam Lock

Cylinder lock where the cam serves as the bolt

Case

(see "lock case")

Change (of key)

(see "differ")

Change Key

Alternative term for either "servant key" or "changing key"

Classroom Functionality

The classroom function in a thumb-turn cylinder makes it possible to rotate the thumb-turn in one direction only i.e.clockwise only or anti-clockwise only. This is usually used to ensure that someone inside a room cannot lock anybody out but can always escape in an emergency. The cylinder is also clutch release as standard so somebody in the room cannot prevent a key holder from entering

Glossary of Terms

ASSA ABLOY

Claw Bolt

Pivoting claw-shaped element of a deadbolt, which serves as an anti-separation point when locked, but which withdraws fully into the lockcase when unlocked

Claw Bolt Lock

Lock comprising at least two claw bolts moving in opposite directions

Close Shackle Padlock

Padlock with most of the shackle concealed within the body

Closing Device / Closer

Device that automatically returns a leaf to its closed position

Closing Speed

Speed at which a door leaf is allowed to close when under hydraulic control

Clutch Release Cylinder

A clutch release thumb-turn cylinder is designed to prevent somebody on the inside of the door from holding the turn and locking key holders out. Insertion of the key disengages the clutch, which allows the turn to rotate freely without engaging the cam

Construction Keying

A construction key cylinder is typically used on building sites, where employees need access to the building during construction, but should not have access when the home owner has moved in. The first operation of the home owner's key will permanently disable the builder's key

Cupboard Lock

Generic term for any lock used on a cupboard door

Cut Cupboard Lock / Cut Cabinet Lock

Cabinet lock designed for flush fitting which is cut into the edge/rear face of the door

Cylinder

Self-contained assembly comprising at least one c linder mechanism and the output drive element

Cylinder Housing

Main body of cylinder

Cylinder Key

Key for use in a cylinder lock

Cylinder Latch

Latch operated by a cylinder

Cylinder Lock

Lock comprising one or more cylinders

Cylinder Night Latch

Night latch operated by a cylinder (see also EN 12209)

Cylinder Pin Tumbler Lock

Cylinder lock with pin tumbler detaining elements

Cylinder Pull

Shaped plate for fitting under the flange of a rim cylinder to provide the means to pull the door leaf using fingers

Cylinder Rose / Cylinder Ring

Substantial circular ring which surrounds the outer end of a cylinder at the surface of the leaf for decorative and/or security purposes

Dead Latch

(see "deadlocking latch")

Deadbolt

Bolt of a lock that is moved in both locking and unlocking directions by means of a key or thumbturn

Deadlock

Lock with a deadbolt only

Deadlocked

Locked in such a way that movement of the bolt towards its unlocked position is positively prevented

Deadlocking

Capable of being deadlocked

Deadlocking Latch

Latch with a bolt that can be deadlocked

Differ

Variation between lock mechanisms of similar design due to differences in the lift and/or position of the detaining elements

Differ Bit

Intermediate element resulting from pin being split for the purpose of master keying

Differ Step

Step on the key bit of a lever lock that makes direct contact with, and lifts, a particular detaining element

Dogging

A device found on exit hardware. If an exit door permits unrestricted traffic flow, a dogging device is a means of holding back the latch bolts when required.

Door

Opening member and associated frame of sufficient height to provide access for pedestrians

Door Bolt

Bolt for use on a door

Door Chain

Chain link device that can be used to restrict the opening of entrance doors to dwellings, for safety purposes

Door Closer / Door Closing Device

Device that automatically returns a door leaf to its closed position

Door Closer Power Size

Classification level of closing moment exerted by a door closer

Door Control

Any device that controls the speed or timing of door leaf movement

Glossary of Terms

ASSA ABLOY

Door Furniture

Items of building hardware that are attached to a door, but excluding locks and hinges

Door Handle

Handle for use with a door leaf

Door Knob

Knob used to open or close a door by operating a latch and/or providing a means to pull on the door leaf by hand (see also EN 1906)

Door Knocker

Device comprising a hinged component that can be struck by hand against its mounting plate to create a sound for attracting attention

Door Lever Handle

Lever handle used to open or close a door by operating a latch and providing a means to pull on the door leaf by hand (see also EN 1906)

Double Throw Lock

Lock requiring two full turns of the key to fully throw the deadbolt

Draw Back Lock

Lock in which the spring bolt is withdrawn by a sliding handle

Drawer Lock / Till Lock

Lock for use on a drawer

Electromagnetic Hold Open

A closer with an integral electro magnet allows a fire door to be held open for convenience. The magnet is linked into the fire alarm system and automatically releases the door when the fire alarm is activated

Electromagnetic Swing Free

As electromagnetic hold open, but permits a fire door to be 'free swinging' for convenience. Not recommended for general traffic areas or doors which are subject to draughts

Emergency Exit Device

Door locking arrangement that allows keyless egress at all times, using one simple hand movement, although this may require prior knowledge of its operation (see also EN 179 and EN 1125)

Escape Lock

Lock that allows keyless egress at all times, using one simple hand movement, without the need for prior knowledge of its operation

Escutcheon

Component which surrounds the entrance to a keyhole at the surface of the leaf, for (mainly) decorative purposes (see also EN 1906)

Euro Profile Cylinder / DIN Cylinder

Profile cylinder for which the cross-section of the housing is to the standard European profile

Exit Device

Device that provides an emergency or panic exit function on an escape route

Faceplate / Face Plate / Outer Forend

Additional plate mounted over forend for decorative purposes

Flush Bolt

Lever action bolt which when mounted does not project above the surface of the leaf

Follower

Component that transmits rotational movement from a spindle (linked to the handle/knob) to the latch bolt, to withdraw it against spring force

Forend / Fore End / Inner Forend

Long narrow plate attached to, but extending beyond, the lockcase, for mounting purposes

Grand Master Key

Key that operates locks of all combinations in a suite, including those in lower level suites under separate submaster keys

Handed

Restricted to one particular closing direction only (either clockwise closing only or anti-clockwise closing only)

Handing

Property relating to the direction a leaf rotates to close

Handle

Item of furniture operated directly by hand

Hasp

A Hinged metal strap used in conjunction with a padlock to secure doors and gates

Hook Bolt

Swing bolt in the shape of a hook

Horizontal Lock

Mortice or rim lock with the follower at the same height as the keyhole but further away from the forend

Indicating Bolt / Indicator Bolt

Bolt with external means for visually indicating status

Keep / Staple

Alternative terms for "locking plate" or "striking plate" - but used, preferably, where there is no plate-like feature

Key

Instrument used to operate a lock, which can be removed and carried on the person

Key Blank

Key without steps

Key Bow

Part of the key that is held to operate it

Glossary of Terms

ASSA ABLOY

Key Registration

Control of key combinations to prevent unauthorised duplication of keys

Keyed Alike

Operable with the same key

Key-retaining

Allowing the key to be withdrawn only when the product is in the locked condition

Keys to Pass

(see "keyed alike")

Knob

Substantially circular form of handle

Knobset

Lockset or latchset in which the key mechanism is contained within the knob

Latch

Self-engaging fastener which secures the leaf of a door or window in the closed position, and which can be released by hand

Latch (Snap) Action

Accelerated closing during the final few degrees of closing to overcome latch bolt or seal resistance

Latch Bolt

Bolt which, by virtue of its shape and the forces acting on it, engages automatically with the locking plate as the door is closed

Left Hand Door

Door which opens in a clockwise direction when viewed from above

Lever Mechanism

Lock mechanism comprising one or more levers

Lock

Device for securing a door or window in the closed position, where unlocking movement of the bolt is by means of a differ key from at least one side

Lock Case

Cylinder mortice lock without the cylinder

Locking Plate

Generally accepted term for any component that engages the bolt or bolts of a lock (i.e. it includes striking plate, keep and staple)

Locking Snib

Hand operated device for preventing a bolt from being thrown or withdrawn, or to change the function of a lock or latch without dismantling

Master Key

Key that operates locks of all combinations within a particular suite

Master Keyed Suite

Set of locks and/or padlocks related by a common key, or keys

Mortice Cylinder

Cylinder for use with a mortice lock

Mortice deadlock

Deadlock adapted for flush fitting into a mortice

Mortice Latch

Latch adapted for flush fitting into a mortice

Mortice Lock

Lock adapted for flush fitting into a mortice

Mortice Night Latch

Night latch adapted for flush fitting into a mortice

Mushroom Roller / Mushroom Driver

Top pin with undercut groove which when under-lifted allows the plug to rotate a small amount thereby frustrating attempts to pick the cylinder

Narrow Stile Lock

Mortice lock with a case depth of less that 67mm

Night Latch

Lock with automatic bolt which is withdrawn from outside by key, and from inside by handle or knob

Non-handed

Not restricted to one particular closing direction only (either clockwise closing only or anti-clockwise closing only)

Open Shackle Padlock

Padlock in which a complete 180° hoop of shackle is exposed

Outside Access Device (OAD)

Mechanism for opening an exit device from outside (see also EN 179 & EN 1125)

Oval Profile Cylinder

Profile cylinder for which the cross-section of the housing is oval

Padlock

Detachable and portable locking device which uses a shackle to link itself to an object, or link objects together (see also EN 12320)

Panel Lock

Two-bolt upright lock for use on metal casement doors

Panic Bar

Horizontal bar of a panic exit device which is used to activate the mechanism

Panic Bolt(s)

(see "panic exit device")

Glossary of Terms

assa abloy

Panic Exit

Egress point on an escape route that is likely to encounter a panic situation

Panic Exit Device

Door locking arrangement that allows egress under all conditions in response to light pressure anywhere along a horizontal bar running the width of the door (see also EN 179 and EN 1125)

Panic Latch

Latch which is released by pressure anywhere along a horizontal bar running the width of the door

Pin / Pin Tumbler

Cylindrical-shaped detaining element of a cylinder mechanism that it is positioned by the key as it is inserted

Pin Tumbler Mechanism

Locking mechanism in which the principal detaining elements are a pins

Plug

Rotating part of a cylinder lock containing the pins, and into which the key is inserted

Postal Knocker

Combined letter plate and pivoted pull handle which also serves as a knocker

Privacy Lock

Lock that is lockable from the inside only

Profile Cylinder

Mortice cylinder with constant cross-section housing

Pull Handle

Fixed handle used to open or close a door by providing a means to pull on the door leaf by hand

Pullman Latch

Panic exit latch with curved bearing surfaces to facilitate engagement and release under side load

Push Pad

One of the accepted operating elements of an emergency exit device

Push-bar

Horizontal bar of a panic exit device

Rebate

Step in a frame (or adjacent leaf) which provides the stop for the leaf

Rebated Lock

Lock adapted to mount on the rebated edge of a leaf

Reversible Latch

Bolt for which the closing direction (clockwise or anticlockwise) can be altered without dismantling

Right Hand Door

Door which opens in an anti-clockwise direction when viewed from above

Rim Cylinder

Cylinder for use with a rim lock or latch, and which is adapted for flush (or near flush) mounting within a leaf

Rim Deadlock

Deadlock adapted for surface mounting on the face of a leaf

Rim Latch

Latch adapted for surface mounting on the face of a leaf

Rim Lock

Lock adapted for surface mounting on the face of a leaf

Rim Night Latch

Night latch adapted for surface mounting on the face of a door leaf

Roller Bolt

Latch bolt with rotating feature in the head to facilitate withdrawal of the bolt upon engagement with the striking plate

Sash Lock

Alternative term for an upright mortice lock

Scandinavian Oval

Mortice cylinder with oval cross-section housing, attached to the lockcase using bolt through fixings

Screwed Cylinder

Mortice cylinder with threaded housing

Security Cylinder

Cylinder with a high level of resistance to attack methods

Servant Key

Key that operates one particular lock in a master keyed suite

Shackle

The 'U' shaped metal bar on a padlock which forms the lockable link to another object (or other objects) (see also EN 12320)

Shear Line

Line representing the cylindrical surface of the plug in a pin tumbler cylinder

Side Bar

Element of a pin tumbler cylinder that only allows the plug to rotate when all the pin tumblers are correctly positioned

Single Action Door Closer

Door closer for use on doors which open in one direction only, and close against a fixed stop

Sliding Door

Door with one or more leaves which move horizontally in their own plane

Snaplock

Method of locking a padlock without the use of a key by pushing the shackle into the body

Glossary of Terms

ASSA ABLOY

Spindle

Bar (usually of square cross-section) that transmits the rotational movement of lever handles/knobs on either or both sides of a door leaf to the follower of a latch (see also EN 1906)

Split Follower / Divided Follower

Two-part follower that enables movement from handles/knobs on opposite side of a door leaf to be transmitted independently

Spring Bolt

Latch bolt operated by a spring

Spring Cassette

Component within door furniture that enables the door handle to return to the horizontal position automatically after use

Spring Shackle Padlock

Padlock with shackle that springs open when unlocked, and which closes without the use of a key

Straight Cabinet Lock/Straight Cupboard Lock

Lock adapted to lie flat on inside face of cabinet or cupboard door

Sprung

Hardware containing a spring mechanism which enables the door handle to return to the horizontal position after use

Striking Plate / Strike Plate / Striker

Component that engages and operates a latch bolt

Sub-grand Master Key

Key which will operate all locks in a one level down subsuite of a great grand master-keyed suite

Sub-master Key

Key which will operate all locks in a one level down subsuite of a grand master-keyed suite

Suited

Belonging to a master keyed suite

Thrower

Component of a lever lock mechanism that rotates with the key and engages with the bolt to move it

Thumb Turn

Small handle or knob for operation by thumb and forefinger (see also EN 1906)

Top Pin / Driver / Roller

Pin of a cylinder mechanism that is located in the cylinder body and is acted on by a spring

Touch-Bar

Horizontal bar of a panic exit device constrained to trigger release in response to a lateral force

Tubular Mortice Latch

Mortice latch with case shaped to fit into a cylindrical mortice

Tubular Mortice Lock

Mortice lock with case shaped to fit into a cylindrical mortice

Two-way Latch Action

Latch action in which the follower will turn in either direction

Unsprung

Hardware that does not containing a spring mechanism to automatically return the handle to the horizontal position after use

Yale



Rack & Pinion Closers

Door Closers





Hydraulic Door Closer

Yale 0-0001-00-60-01


Selectable size class 2,3 & 4
Max door weight: 80kg
Max door width: 1100mm
Independent swing and latch
valves to control speeds
3-hour fire rating - UL listed
Suitable for indoor or outdoor use

Finish

Powdercoated Grey

Mortice Locks





2 Lever Lock Only - Essential Galvanised


Yale 22955-76BP

SABS approved lock Durable for long life operation Fit for left or right hinged doors

Finish

Brass Forend





2 Lever Lock Only - Essential Galvanised


Yale 22955-76SS

SABS approved lock Durable for long life operation Fit for left or right hinged doors

Finish

Stainless Steel Forend





3 Lever Lock Only - Essential Galvanised


Yale 22525-76BP

SABS approved lock Durable for long life operation Fit for left or right hinged doors

Finish

Brass Forend





3 Lever Lock Only - Essential Galvanised

Yale 22525-76SS

SABS approved lock
Durable for long life operation
Fit for left or right hinged doors

Finish

Stainless Steel Forend

Mortice Locks





4 Lever Lock Only - Comm Galvanised


Yale 22615-76BP

SABS approved lock Durable for long life operation Fit for left or right hinged doors

Finish

Brass Forend





4 Lever Lock Only - Comm Galvanised

Yale 22615-76SS

SABS approved lock Durable for long life operation Fit for left or right hinged doors

Finish

Stainless Steel Forend

Locksets



Euro Profile Cylinder Lockset

Yale YDY69405315CH

Euro profile cylinder
SABS approved
Traditional handles
Pressed stainless steel backplate
Use on external doors, high level of security
Mortice Lock comes with stainless steel forend
Powder coated mortice lock case
Durable for long life operation
Fit left or right hinged doors

Finish

Stainless Steel



3 Lever Lockset

Yale YDY69424525CH

3 lever lockset
SABS approved
Traditional handles
Pressed stainless steel backplate
Powder coated lock body
Use on internal doors, medium
level of security
Mortice Lock comes with stainless
steel forend
Durable for long life operation
Fit left or right hinged doors

Finish

Stainless Steel

Locksets



4 Lever Lockset

Yale YDY69424615CH

4 lever lockset
SABS approved
Traditional handles
Pressed stainless steel Backplate
Powder coated lock body
Use on internal doors, high level of security
Mortice Lock comes with stainless
steel forend
Durable for long life operation
Fit left or right hinged doors

Finish

Stainless Steel



2 Lever Lockset

Yale YDY69424955CH

2 lever lockset
SABS approved
Traditional handles
Pressed stainless steel backplate
Powder coated lock body
Use on internal doors, low level of
security
Mortice Lock comes with stainless
steel forend
Durable for long life operation
Fit left or right hinged doors

Finish

Stainless Steel



3 Lever Lockset - Onda Handles

Yale 22-A082-3L-5701

180X43mm modern handles on steel back plates with high quality electroplated finish Salt spray - tested to 100 hours Galvanised 3-lever lock body with stainless steel forend Zinc dead and latch bolt Reversible latchbolt - fits left or right hinged doors Durable for long life operation Supplied with 2 keys

Finish

Satin Black Nickel

Locksets



3 Lever Lockset - Onda Handles

Finish

Yale 22-A082-3L-7501 Matte Coffee

180X43mm modern handles on steel back plates with high quality electroplated finish Salt spray - tested to 100 hours Galvanised 3-lever lock body with stainless steel forend Zinc dead and latch bolt Reversible latchbolt - fits left or right hinged doors Durable for long life operation Supplied with 2 keys

3 Lever Lockset - Dritta Handles

Finish

Yale 22-A083-3L-5701 Satin Black Nickel



3 Lever Lockset - Dritta Handles

Finish

Yale 22-A083-3L-7501 Matte Coffee



180X43mm modern handles on steel back plates with high quality electroplated finish Salt spray - tested to 100 hours Galvanised 3-lever lock body with stainless steel forend Zinc dead and latch bolt Reversible latchbolt - fits left or right hinged doors Durable for long life operation Supplied with 2 keys

Door Hardware



Profile Escutcheon (Pair)

Finish

Yale

35ZX-CE09-5001

Antique Brass

Euro profile cylinder escutcheons Type: Screw-on cover



Profile Escutcheon (Pair)

Finish

Yale 35ZX-CE22-5001 Satin Nickel

Euro profile cylinder escutcheons Type: Screw-on cover

Knobsets



Tulip Cylindrical Knobset

Finish

Yale 40CY3-5716-0201 **Polished Brass**

Tulip Cylindrical Knobset
Key / push button operation
Rosette 65mm wide
Brass cylinder with 3 keys
Adjustable latch 60/70mm backset
Suitable for door thickness of
35-45mm
Reversible for left and right hand
doors



Tulip Cylindrical Knobset

Finish

Yale 40CY3-5716-0901 **Antique Brass**

Tulip Cylindrical Knobset
Key / push button operation
Rosette 65mm wide
Brass cylinder with 3 keys
Adjustable latch 60/70mm backset
Suitable for door thickness of
35-45mm
Reversible for left and right hand
doors

Knobsets



Tulip Cylindrical Knobset

Yale 40CY3-5716-3101

Satin Silver

Finish

Tulip Cylindrical Knobset
Key / push button operation
Rosette 65mm wide
Brass cylinder with 3 keys
Adjustable latch 60/70mm backset
Suitable for door thickness of
35-45mm
Reversible for left and right hand
doors

Round Cylindrical Knobset

40CY3-5866-0201

Yale

Polished Brass

Finish

Round Cylindrical Knobset Key / push button operation Rosette 65mm wide Brass cylinder with 3 keys Adjustable latch 60/70mm backset Suitable for door thickness of 35-45mm Reversible for left and right hand doors

Round Cylindrical Knobset

and Cymranical Miobset

Finish

Yale 40CY3-5866-0901 **Antique Brass**



Round Cylindrical Knobset
Key / push button operation
Rosette 65mm wide
Brass cylinder with 3 keys
Adjustable latch 60/70mm backset
Suitable for door thickness of
35-45mm
Reversible for left and right hand
doors

Knobsets



Round Cylindrical Knobset

obset Finish

Yale 40CY3-5866-3101 Satin Silver

Round Cylindrical Knobset
Key / push button operation
Rosette 65mm wide
Brass cylinder with 3 keys
Adjustable latch 60/70mm backset
Suitable for door thickness of
35-45mm
Reversible for left and right hand
doors



Double Cylinder Deadbolt

Finish

Yale 40-D102-0201 **Polished Brass**

Double Cylinder deadbolt Key operation from both sides Adjustable bolt for 60/70mm backset Suitable for door thickness of 35-45mm



Double Cylinder Deadbolt

Finish

Yale 40-D102-0901 **Antique Brass**

Double Cylinder deadbolt Key operation from both sides Adjustable bolt for 60/70mm backset Suitable for door thickness of 35-45mm



Double Cylinder Deadbolt

Finish

Yale 40-D102-3101 Satin Silver

Double Cylinder deadbolt Key operation from both sides Adjustable bolt for 60/70mm backset Suitable for door thickness of 35-45mm

Cylinders



64mm Euro Profile Replacement Cylinder

Yale 2023232000201 Finish

Machined Brass

64mm Euro Profile Replacement Cylinder Supplied with 3 keys 5 pin cylinder provides 7000 key

differs for high security

Finish

Satin Nickel



64mm Euro Profile Replacement Cylinder

Yale 2023232002201

64mm Euro Profile Replacement Cylinder

Supplied with 3 keys 5 pin cylinder provides 7000 key differs for high security

64mm Euro Profile Replacement Cylinder - Thumb Turn

Yale 2033232CK0201 **Finish**

Machined Brass



64mm Euro Profile Replacement

Thumb Turn Cylinder
Supplied with 3 keys
5 pin cylinder provides 7000 key
differs for high security

64mm Euro Profile Replacement Cylinder - Thumb Turn

Yale 2033232CK2201 Finish

Satin Nickel



64mm Euro Profile Replacement Thumb Turn Cylinder Supplied with 3 keys 5 pin cylinder provides 7000 key differs for high security

Fire Safety




Smoke Detector

Yale E-SD2

Detects all types of smoke - photoelectric sensing technology Battery operated - 9V battery included 85 dB alarm alerts you of a potential fire Blinking power indicator Audible low battery warning indicator - coverage 75m³ (5m effective radius | placement height 7m max)

Narrow Stile Lever Handles




Narrow Stile Aluminium Handle

Yale 35A214852P3111

For use with 85mm CTC lockcases Powder-coated handles with Euro profile piercing Ergonomically designed handle with comfort contours Reversible for left or right hinged doors Bolt through fixings and spindle included

Finish

Powdercoated Silver



Narrow Stile Aluminium Handle

Yale 35A214852P5011


For use with 85mm CTC lockcases Powder-coated handles with Euro profile piercing Ergonomically designed handle with comfort contours Reversible for left or right hinged doors Bolt through fixings and spindle included

Finish

Powdercoated White

Narrow Stile Lever Handles






Narrow Stile Aluminium Handle

Yale 35A214852P5611 Powdercoated Black

Finish

For use with 85mm CTC lockcases Powder-coated handles with Euro profile piercing Ergonomically designed handle with comfort contours Reversible for left or right hinged doors Bolt through fixings and spindle included





Narrow Stile Aluminium Handle


Yale 35A214852P7511 Powdercoated Bronze

Finish

For use with 85mm CTC lockcases Powder-coated handles with Euro profile piercing Ergonomically designed handle with comfort contours Reversible for left or right hinged doors Bolt through fixings and spindle included

Narrow Stile Locks





25mm Latch And Deadlock

Yale 20-NSLT-2285-25


Reversible latch bolt with drawback functionality Stainless steel forend and strike plate 25mm backset

85mm centre-to-centre 22mm forend width

Finish

Stainless Steel Forend





35mm Latch And Deadlock

Yale 20-NSLT-2285-35 Stainless Steel Forend


Finish

Reversible latch bolt with drawback functionality Stainless steel forend and strike plate 35mm backset 85mm centre-to-centre 22mm forend width

10

Narrow Stile Locks





25mm Roller And Deadlock

Yale 20-NSRT-2285-25

Roller latch and deadbolt lock Stainless steel forend and strike plate

85mm centre-to-centre


22mm forend width

25mm backset

Finish

Stainless Steel Forend





35mm Roller And Deadlock


Yale 20-NSRT-2285-35

Roller latch and deadbolt lock Stainless steel forend and strike plate 35mm backset 85mm centre-to-centre

Finish

Stainless Steel Forend





25mm Hook Bolt Box

22mm forend width


Yale NSHA2200253111

Hook bolt suitable for stacking Stainless steel forend and strike plate 25mm backset 22mm forend width

Finish

Stainless Steel **Forend**





35mm Hook Bolt Box

Yale NSHA2200353111


Hook bolt suitable for stacking Stainless steel forend and strike plate 35mm backset 22mm forend width

Finish

Stainless Steel **Forend**

Narrow Stile Locks





35mm Latch & Hookbolt Box

Yale NSHA2285353111

Reversible latch with drawback functionality Hook bolt suitable for stacking doors Stainless steel forend and strike plate 35mm backset 85mm centre-to-centre

Finish

Stainless Steel Forend

Stainless Steel Lever Handles





SS201 Tubular Handles On Back Plate Cylinder - Straight

Yale P100-CH-31-01

22mm forend width

19mm diameter tubular handles on plate SS201 Stainless Steel Sprung handles Euro profile cylinder piercing Includes fixing screws

Finish

Stainless Steel





SS201 Tubular Handles On Back Plate Keyhole - Straight

Yale P100-KH-31-01

19mm diameter tubular handles on plate SS201 Stainless Steel Sprung handles Keyhole piercing Includes fixing screws

Finish

Stainless Steel





SS201 Tubular Handles On Back Plate Cylinder - Curve

raie P101-CH-31-01

19mm diameter tubular handles on plate SS201 Stainless Steel Sprung handles Euro profile cylinder piercing Includes fixing screws

Finish

Stainless Steel





SS201 Tubular Handles On Back Plate Keyhole - Curve

Yale P101-KH-31-01 **Finish**

Stainless Steel

19mm diameter tubular handles on plate SS201 Stainless Steel Sprung handles Keyhole piercing Includes fixing screws

Finish

Stainless Steel





SS201 Tubular Handles On Back Plate Cylinder- Wave-Ext.

Yale P102-CH-31-01

19mm diameter tubular handles on plate SS201 Stainless Steel Sprung handles Euro profile cylinder piercing Includes fixing screws

SS201 Tubular Handles On Back Plate Keyhole - Wave-Ext.

Yale P102-KH-31-01 Finish

Stainless Steel





19mm diameter tubular handles on plate

SS201 Stainless Steel Sprung handles Keyhole piercing Includes fixing screws

SS201 Tubular Handles On Back Plate Cylinder - Straight-Ext.

Yale P103-CH-31-01 **Finish**

Stainless Steel





19mm diameter tubular handles on plate SS201 Stainless Steel Sprung handles Euro profile cylinder piercing

Includes fixing screws





SS201 Tubular Handles On Back Plate Keyhole - Straight-Ext.

Yale

P103-KH-31-01

Finish

Stainless Steel

19mm diameter tubular handles on plate SS201 Stainless Steel Sprung handles Keyhole piercing Includes fixing screws

SS201 Handles Cylinder Straight

Box

Yale


P500-CH-31-11

Finish

Stainless Steel



1



SS201 Handles Keyhole Straight

- Box

Yale

P500-KH-31-11

Finish

Stainless Steel

150 x 40mm backplate 16mm diameter tubular handles SS201 Stainless Steel Sprung handles Keyhole piercing Includes fixing screws





SS201 Handles Cylinder Curve - Box


Yale

P501-CH-31-11

Finish

Stainless Steel

150 x 40mm backplate 16mm diameter tubular handles SS201 Stainless Steel Sprung handles Cylinder piercing Includes fixing screws



SS201 Handles Keyhole Curve - Box

Yale

P501-KH-31-11

Finish

Stainless Steel

150 x 40mm backplate 16mm diameter tubular handles SS201 Stainless Steel Sprung handles Keyhole piercing Includes fixing screws

Stainless Steel Tubular Handles On Rose - Straight

Yale

R100-KH-31-01

Finish

Stainless Steel

19mm diameter tubular handles SS201 Stainless Steel Sprung handles Includes escutcheons & fixing screws



Stainless Steel Tubular Handles On Rose - Curve

Yale

R101-KH-31-01

Finish

Stainless Steel

19mm diameter tubular handles SS201 Stainless Steel Sprung handles Includes escutcheons & fixing screws





Stainless Steel Tubular Handles On Rose - Wave-Ext.

Yale

R102-KH-31-01

Finish

Stainless Steel

19mm diameter tubular handles SS201 Stainless Steel Sprung handles Includes escutcheons & fixing

screws



On Rose - Straight-Ext. Yale

R103-KH-31-01

Finish

Stainless Steel





19mm diameter tubular handles SS201 Stainless Steel Sprung handles Includes escutcheons & fixing screws





Stainless Steel Escutcheons

teer Escatemeons

Finish

Yale RX-SS01-CE-01 Stainless Steel

Euro profile cylinder escutcheons Type: Clip-On cover

Aluminium Handles



Cortina Aluminium Handles

Finish

Yale R-A007-QE-09-01 **Antique Brass**

Material: Aluminium handles with zinc alloy rosette Sprung handle Supplied with keyhole Escutcheons (screw-on cover)

6

Cortina Aluminium Handles

Finish

Yale R-A007-QE-22-01 Satin Nickel

Material: Aluminium handles with zinc alloy rosette Sprung handle Supplied with keyhole Escutcheons (screw-on cover)



Milano Aluminium Handless

Finish

Yale R-A016-QE-09-01 **Antique Brass**

Material: Aluminium handles with zinc alloy rosette Sprung handle Supplied with keyhole Escutcheons (screw-on cover)



Milano Aluminium Handless

Finish

Yale R-A016-QE-22-01

16

Satin Nickel

Material: Aluminium handles with zinc alloy rosette
Sprung handle
Supplied with keyhole Escutcheons
(screw-on cover)

Aluminium Handles



Apollo Aluminium Handles

Finish

Yale

R-A027-QE-09-01

Antique Brass

Material: Aluminium handles with zinc alloy rosette Sprung handle Supplied with keyhole Escutcheons

(screw-on cover)



Apollo Aluminium Handles

Finish

Yale R-A027-QE-22-01 Satin Nickel

Material: Aluminium handles with zinc alloy rosette Sprung handle Supplied with keyhole Escutcheons (screw-on cover)



Venezia Aluminium Handles

Finish

Yale R-A055-QE-09-01 **Antique Brass**

Material: Aluminium handles with zinc alloy rosette Sprung handle Supplied with keyhole Escutcheons (screw-on cover)



Venezia Aluminium Handles

Finish


Yale R-A055-QE-22-01 Satin Nickel

Material: Aluminium handles with zinc alloy rosette Sprung handle Supplied with keyhole Escutcheons (screw-on cover)

Nightlatches & Rimlocks







Y3 Nightlatch


Finish

Yale P-Y3-SN-SN-60SA Satin Nickel

Slam lock latch
Can be deadlocked from the inside
Latch can be held back in open
position
Suitable as secondary security
device on external doors

Nightlatches & Rimlocks





Traditional Nightlatch

Yale YDY564G


Gold

Finish

Latch bolt automatically locks when door is closed
Snib button can be used to hold open latch bolt or to deadlock the door when in the closed position
Suitable for left and right hand inward opening doors
To be used as an additional lock on primary doors

Gate Locks Trellis Gates






Slam Hook Lock With Cylinder

Yale YDY24627SLAM-SS

For use on most sliding security gates
Mini oval cylinder for high security applications
Slam Lock | Anti-lift locating pin
Stainless steel face and strike plates
Includes escutcheon set
Supplied with 3 keys






Standard Hook Lock With Cylinder Yale YDY24627STD-SS

For use on most sliding security gates
Mini oval cylinder for high security applications
Anti-lift locating pin
Stainless steel face and strike plates
Includes escutcheon set
Supplied with 3 keys

Gate Locks

Swing Gates






5 Lever Security Gate Lock

Yale YDY2528/1

For use on security swing gates 5 Lever (400 key variations)
Double throw dead bolt 2 high security keys
Includes escutcheons






5 Lever Security Gate Lock Duo KA

Yale YDY2528/2

For use on security swing gates 5 Lever (400 key variations)
Double throw dead bolt
Duo pack (keyed alike)
Supplied with 4 keys
Includes escutcheons





Cylinder Security Gate Lock

Yale YDY/4545/NP

For use on security swing gates Euro Profile Cylinder for high security applications Double throw dead bolt Supplied with 3 keys Includes Euro Profile escutcheons

Door Hardware





Magnetic Door Stop

Yale YDYDH011ZN

Door stop with magnetic hold function Spring loaded stop Material: Zinc alloy Concealed mounting points with fixings accessories included

Finish

Satin Nickel

Door Hardware





Halfmoon Rubber Door Stop

Yale YDYDS002ZN


Halfmoon design Rubber bumper/stop Material: Zinc alloy Floor mount fixings included

Finish

Satin Nickel







Butt Hinge 100X76X2,5mm


Yale YDYBH4325PVD

Smooth running high quality hinges - two ball bearing SS201 grade stainless steel Supplied with self-tapping fixing screws

Finish

PVD Satin Brass





Butt Hinge 100X76X2.5mm


Yale YDYBH4325SS

Smooth running high quality hinges - two ball bearing SS201 grade stainless steel Supplied with self-tapping fixing screws

Finish

Stainless Steel





Flush Hinge 100X70X2.5mm


Yale YDYFH103PVD

Smooth running high quality hinges - two ball bearing SS201 grade stainless steel Supplied with self-tapping fixing screws

Finish

PVD Satin Brass





Flush Hinge 100X70X2.5mm

Yale YDYFH103SS

Smooth running high quality hinges - two ball bearing SS201 grade stainless steel Supplied with self-tapping fixing screws

Finish

Stainless Steel

Access Control






Electric Strike Kit

Yale YMM/ES/KIT

12 Volt AC Electric strike
Normally open circuit
High Security Mini oval cylinder
with 3 keys
Latch bolt
Face plates for cylinder
12 Volt Step down Transformer
and Push button included

Sliding Door Locks





Patio Door Lock


Yale YPDL/2KB

8mm locking bolt Push to lock button – key only needed to unlock Includes 2 x striking rings offering an optional secondary locking position

Finish

Powdercoated Dark Brown





Patio Door Lock


Yale YPDL/2KG

8mm locking bolt
Push to lock button – key only
needed to unlock
Includes 2 x striking rings offering
an optional secondary locking
position

Finish

Powdercoated Grey





Patio Door Lock

Yale YPDL/2KW


8mm locking bolt
Push to lock button – key only
needed to unlock
Includes 2 x striking rings offering
an optional secondary locking
position

Finish

Powdercoated White

Sliding Door Locks





Patio Door Lock Thumbturn


Yale YPDL/TT/B

8mm locking bolt Push to lock, thumb turn to open Includes 2 x striking rings offering an optional secondary locking position

Finish

Powdercoated Dark Brown





Patio Door Lock Thumbturn


Yale YPDL/TT/G

8mm locking bolt Push to lock, thumb turn to open Includes 2 x striking rings offering an optional secondary locking position

Finish

Powdercoated Grey





Patio Door Lock Thumbturn

Yale YPDL/TT/W

8mm locking bolt Push to lock, thumb turn to open Includes 2 x striking rings offering an optional secondary locking position

Finish

Powdercoated White

Safes & Safety Boxes





Combination Key Access - Basic Security Yale

Y500/187/1


Combination Key Access Box Strong Die-Cast Body Weather resistant case, for outdoor use Ideal storage of perimeter keys for family or response companies 4-dial re-settable combination lock Concealed fixings for maximum security

Finish

Black

Safes & Safety Boxes





Alarmed Safety Box - Small

Yale YEC/200/DB1 Black

Finish

Tamper Alarm Feature
Dimensions: 200x320x200mm
(External) 190x300x150mm
(Internal)
3 to 8 digit user code
Mass:5.4Kg

Wall Thickness: 1.5mm (body) Door Thickness: 3mm Low battery warning

2 x 16mm dead bolts (horizontal)

2 x Tubular keys







Yale YEC/250/DB1 Black

Finish

Tamper Alarm Feature
Dimensions: 250x350x250mm
(External) 240x340x200 (Internal)
3 to 8 digit user code
Mass:7.8Kg
Wall Thickness: 1.5mm (body)
Door Thickness: 3mm
Low battery warning
2 x 16mm dead bolts (horizontal)





Alarmed Safety Box - Large

Yale YEC/390/DB1

2 x Tubular keys

Finish Black

Tamper Alarm Feature
Dimensions: 390x350x360mm
(External) 380x340x310mm
(Internal)
3 to 8 digit user code
Mass:14.1Kg
Wall Thickness: 2mm (body)
Door Thickness: 3mm
Low battery warning
2 x 16mm dead bolts (horizontal)
2 x Tubular keys

Safes & Safety Boxes



Alarmed Safety Box - Laptop

Yale YLC/200/DB1 Black


Finish

Tamper Alarm Feature Dimensions: 200x430x350mm (External) 190x420x300mm (Internal) Fits 15" laptops 3 to 8 digit user code Mass:10.4Kg Wall Thickness: 2mm (body) Door Thickness: 3mm Low battery warning

2 x 16mm dead bolts (horizontal)

2 x Tubular keys






Alarmed Security Safe - Small

Yale YTS/200/DB1 Grey

Finish

Complies to SABS domestic safe standard - SANS 1761:2017 Dimensions: 200 x 310 x 200mm (External) 190 x 300 x 150mm (Internal) LCD Keypad, 3 – 8 digits PIN code and external emergency power terminal Integrated alarm feature (attack and tamper) Door thickness: 4 mm, wall thickness: 2 mm Integrated LED Light and key management hooks





Alarmed Security Safe - Medium

Yale YTS/250/DB1 Grey

Finish

Complies to SABS domestic safe standard - SANS 1761:2017 Dimensions: 250 x 350 x 250mm management hooks

Safes & Safety Boxes





Alarmed Security Safe - Large

Yale YTS/390/DB1 Grey

Finish

Complies to SABS domestic safe standard - SANS 1761:2017 Dimensions: 390 x 350 x 360mm (External) 380 x 340 x 310mm (Internal) LCD Keypad, 3 – 8 digits PIN code

and external emergency power terminal

Integrated alarm feature (attack and tamper)
Door thickness: 4 mm, wall

Alarmed Security Safe - Laptop


thickness: 2 mm Integrated LED Light and key

management hooks

Finish

Grey





Yale YTSL/200/DB1

Complies to SABS domestic safe standard - SANS 1761:2017 Dimensions: 200 x 430 x 350mm (External) 190 x 420 x 300mm (Internal)

LCD Keypad, 3 – 8 digits PIN code and external emergency power terminal

Integrated alarm feature (attack and tamper)
Door thickness: 4 mm, wall

thickness: 2 mm Integrated LED Light and key management hooks

Smart Security Alarm



Smart SR Home Alarm Kit

Yale SR-3200I

Control via Smartphone: Arm/ disarm and configure your alarm anytime, anywhere Kit includes: 1x Smart Hub, 1x PIR Motion Detector, 1x PIR Image Camera, 2x Door / Window Contact, 1x Keypad 94dB internal loud siren within the Smart Hub (868MHz Technology) All accessories within the kit are Pre-linked Expandable system: Add up to 40 devices to tailor the system. (Up to 6 out of 40 can be PIR Image / Video Cameras) No Monthly Fee



Smart SR Outdoor Siren & Strobe

Yale SR-BX-GRAY

104dB outdoor siren
Spring tamper
LED strobe
DIY Friendly - Wireless & easy to
pair with your Yale Home Alarm
System
2 Year Guarantee
Batteries Included



Smart SR Door / Window Contact

Yale SR-DC

Trigger the home smart alarm when the door / window has been opened
LED indicates activation
For internal use only
Security spring tamper
DIY Friendly - Wireless & easy to pair with your Yale Home Alarm SR
System
2 Year Guarantee
Batteries Included

Smart Security Alarm



Smart SR Outdoor Motion Detector Yale

SR-EIR

Activates the alarm when motion is detected
Weather resistant Outdoor PIR
The infrared sensor will pick up
movement and activate the siren
Detection range: 110° and 11m
Pet friendly - 4 sensitivity settings
(accommodate pets between
20 - 60kg)
DIY Friendly - Wireless & easy to
pair with your Yale SR Home Alarm
System
2 Year Guarantee
3.6V AA Lithium Batteries Included



Smart SR Smart Home Alarm Hub + Lock Module

Yale SR-HUB

Yale Smart Hub and Smart Lock Module (Alarm & Lock start up kit) Control your Yale Smart Lock via a smart phone Enables lock control with access rights and time scheduling Expandable system: add up to 40 lock / alarm devices to tailor the system. (Up to 6 out of 40 can be PIR Image/Video Cameras)



Smart SR Keyfob Remote

Yale SR-KF

Arm / disarm your alarm system Emergency trigger your alarm DIY Friendly - Wireless & easy to pair with your Yale SR Home Alarm System 2 Year Guarantee Batteries Included

Smart Security Alarm



Smart SR Wireless Keypad

Yale SR-KP

Arm, disarm or emergency trigger your alarm system
The disarming function is protected by the users PIN code Multiple keypads can be fitted throughout the property
DIY Friendly - Wireless & easy to pair with your Yale Home Alarm System
2 Year Guarantee
Batteries Included



Smart SR Smart Lock Module

Yale SR-LM

Connects Yale Smart Locks to the Yale Smart Home hub + app Control your Yale Smart Lock via a smart phone Enables lock control with access rights and time scheduling



Smart SR Panic Button

Yale SR-PB

Activate the alarm when the button is pressed
The panic button can be fixed or function as a mobile panic alarm DIY Friendly - Wireless & easy to pair with your Yale Home Alarm System
2 Year Guarantee
Batteries Included

Smart Security Alarm



Smart SR PIR With Snapshot Camera

Yale SR-PC

Activates alarm when motion is detected and sends an image to your smartphone For Indoor use only DIY Friendly - Wireless & easy to pair with your Yale SR Home Alarm System 2 Year Guarantee Batteries Included 2.4 Ghz - Zigbee technology



Smart SR PIR Motion Detector

Yale SR-PETPIR

Activates the alarm when motion is detected For indoor use only Pet-friendly up to 25kg DIY Friendly - Wireless & easy to pair with your Yale SR Home Alarm System 2 Year Guarantee Batteries Included



Smart SR PIR With Video Clip Camera

Yale SR-PVC

Activate the alarm when motion is detected and send a 10 second video clip to your smartphone Request a video clip at any point and time via the Yale Smart Home Alarm App DIY Friendly - Wireless & easy to pair with your Yale SR Home Alarm System 2 Year Guarantee Batteries Included 2.4 Ghz - Zigbee technology

Smart Security Alarm



Smart SR Smoke Detector

Yale SR-SD

Trigger the home smart alarm when smoke is detected (not heat sensitive) Independent internal siren - 85dB DIY Friendly - Wireless & easy to pair with your Yale sr Home Alarm System 2 Year Guarantee Batteries Included



Smart SR Internal Siren

Yale SR-SR

104dB internal siren
Spring tamper
DIY Friendly - Wireless & easy to
pair with your Yale Home Alarm
System
2 Year Guarantee
Batteries Included

Surveillance



Smart Home CCTV Kit - 4 Channel 2 Camera

Yale SV-4C-2ABFX

DVR/NVR, 4 Channel, 1TB hard drive 2 x 1080 wired outdoor bullet camera 2 x Chargers (Exchangeable plugs EU/UK) Cables and Yale mouse Quick installation Guide (GB, FR, ES, IT and DE) 2 x CCTV stickers

Smart Security Surveillance



Smart Home CCTV Wi-Fi Kit - 4 Channel 2 Camera

Yale

SV-4C-2DB4MX

DVR/NVR, 4 Channel, 1TB hard drive.

2 x 4MP WiFi outdoor bullet camera

3 x Chargers (Exchangeable plugs EU/UK)

Cables and Yale mouse

Quick installation Guide (GB, FR,

ES, IT and DE)

2 x CCTV stickers



Smart Home CCTV Kit - 8 Channel 4 Camera

Yale

SV-8C-4ABFX

DVR/NVR, 8 Channel, 2TB hard drive.

4 x 1080 wired outdoor bullet

2 x Chargers (Exchangeable plugs EU/UK)

Cables and Yale mouse

Quick installation Guide (GB, FR,

ES, IT and DE)

2 x CCTV stickers



Smart Home Wired Bullet Camera

Yale

SV-ABFX-B

1080 wired outdoor bullet camera 1 x Chargers (Exchangeable plugs EU/UK) BNC Cable 18m Quick Guide (GB, FR, ES, IT and DE)

Smart Security

Surveillance



Smart Home Wired Dome Camera

Yale

SV-ADFX-W

1080 wired outdoor dome camera
1 x Chargers (Exchangeable plugs
EU/UK)
BNC Cable 18m

Quick Guide (GB, FR, ES, IT and DE)



Smart Home All-In-One Wi-Fi Camera

Yale

SV-DAFX-W-EU

HD 1080p resolution
View via smartphone or tablet
10m enhanced night vision
Micro SD card slot (card not
included)
Built-in speaker & microphone
Integrated LED spotlight & warning
siren



Smart Home Outdoor Wi-Fi Camera

Yale

SV-DB4MX-B

4MP Wi-Fi outdoor bullet camera 1 x Chargers (Exchangeable plugs EU/UK) 6m extension power cable Quick installation Guide (GB, FR, ES, IT and DE)



Smart Home Indoor IP Camera 1080P

Yale

SV-DFFI-W-EU

Indoor Wi-Fi Camera HD 1080p resolution View via smartphone or tablet 8m enhanced night vision Built-in speaker & microphone Micro-SD card slot (card not included) Wi-Fi 2.4 GHz required

Smart Security Smart Locks





Keyless Connected Smart Lock

Finish

Yale YDC01Y3SN Satin Nickel

Digital touch screen keypad IP55 rated 4 - 10 digit PIN code 20 User ID's Retrofitable to 60mm backset nightlatches ZigBee and Z-Wave integration module available Compatible with the Yale Home App when connected to the Yale Smart Home alarm hub For inward opening doors only!





Monoblok Smart Lock

Finish

Yale YDM3168 Satin Nickel

Access via PIN code or RF key Mechanical key override Automatic locking Alarm (break-in/damage/fire) Operation status notification Voice prompt for programming and general use Low battery and emergency power 60mm backset Door Thickness: 40 to 105mm Dimensions: front body 311 (D) x 64 (W) x 26 (H) mm; back body 311 (D) x 72(W) x 31 (H)mm ZigBee and Z-Wave integration module available Compatible with the Yale Home App when connected to the Yale Smart Home alarm hub



Open your front door with your smartphone

Smart home security is as easy as pie. With the Yale Smart Home Hub, you can effortlessly control your security on your smartphone.

Using the Yale home app, you can link your Yale security products like your alarm, IP cameras, CCTV, and even your smart door lock with a Yale module.

By activating the Geo-notification phone setting, it will even remind you to arm the system if you left your home and forgot to do so. You can then arm the alarm using the Yale Home app.

So, you can turn on and off your alarm, and you can also control your Yale smart locks from anywhere in the world.

With the app's log, you can see when and who unlocked your smart door lock. Remotely grant or remove access codes for visitors and schedule times of entry for your domestic worker. Not only is this convenient, but this is especially useful when you are away.

Yale Trusted every day.








Digital Access Solutions









Aperio®

Expand your access control system with wireless lock technology



Do you have some doors that are access controlled, and some that have mechanical keys? Why manage two systems in parallel?

A mechanical master key system is expensive to run, due to secure key management costs and lack of flexibility in changing user access. Losing a master key means replacing mechanical cylinders and keys right across your facility. There's no shortcut.

How many replacement keys did you order last year? Every lost key costs you time and money – and an instant replacement is impossible. Stolen or copied keys are a constant security risk, with no electronic audit trail.

So, what's the 21st-century solution? Upgrade your doors to Aperio® to...


- Save time and money with keyless access control
- Connect more doors to your existing access control system
- Get more control with audit trails
- Solve the lost key problem by using secure RFID cards.
- Add access control to doors without the need for cabling
- Save energy with battery powered locks

Aperio[®] Security and Facility Managers have greater control, can easily respond to organisational changes and will only need to monitor a single security system, while users will only require a single RFID access control card.



To find out more contact your sales representative or ASSA ABLOY on 011 761 5000 or email za.info@assaabloy.com






Aperio H100 Handle

Integrates to existing access control system Suitable for wooden, steel and tubular frame doors (and glass doors with standard lock cases) Outside handle rotates freely - inside handle is always engaged LED for status visualisation

Left Hand: H100SDL-EU Right Hand: H100SDR-EU





Aperio C100 Double Knob Cylinder

50520190-0001

Supplied without communication hub 30mm x 30mm double cylinder Outside knob free wheeling - inside knob always


engaged
Freely rotating lock cam
Stores up to 10 emergency cards

Compatible with all DIN mortice locks Suitable for locks on glass door leafs and standard doors

LED for status visualisation


Aperio C100 Single Knob Cylinder







50720190-0-01
Supplied without communication hub
30mm single cylinder
Freely rotating lock cam
Stores up to 10 emergency cards
Compatible with all DIN mortice locks
Suitable for locks on glass door leafs and standard doors
LED for status visualisation



Aperio E100

5001-198A17212
Supplied without communication hub
Euro profile
40-50mm
Stores up to 10 emergency cards
High frequency reader only
8mm spindle
85mm centre
U-shape handle
Double piercing

Access Control

Aperio Wireless Door Locks





Aperio L100 Electronic lock with or without keypad reader

AL560-501150

With or without keypad reader

Main electronics inside - Reader element outside including emergency battery connector and indicator LED's

Outside handle controlled by electronics Inside handle always engaged (request to exit sensor included)

Integrated sensors for bolt and door position, mechanical key override

LED for status visualisation





Aperio KS100 Server Lock

KS100-640

Real-time communication to the access control system

Designed for standard 25mmx150mm server lock openings

Ideal for co-location data centers with multiple companies requiring access

For use on left or right hand doors

Standard server cabinet "Swing-handle" design Integrates to existing access control system Stores up to 10 emergency cards

Powered by PoE or external power supply

LED for status visualisation

Mechanical override possibility





HES KS200-640 Cabinet Lock

KS200-640

Server Cabinet Lock extends access control to protect data center assets

Hard wired Wiegand hub communication Integrates with existing electronic access control system

Mechanical key override capable with SFIC Lock and DPS status monitoring

Dual voltage 12 or 24 VDC

Non-handed

Designed for standard 25 mm x 150 mm server rack lock openings



Aperio K100 Cabinet Lock

K100-622-SE-B1

Suitable for cabinets and drawers where audit trail and monitoring is required
Cabinet lock latch bolt status monitoring
Online & offline transaction audit trail capabilities
Easy to install wireless lock
Low maintenance
50,000 cycles on CR123A battery
Low battery signalling and reporting
Two forms of override available, including
mechanical key override and battery jump start
pack



Aperio Communication Hub

500-35-00

Aperio Communication Hub Wiegand simple AH20 For connection to EAC system via Wiegand interface

Provides radio communication to the Aperio® door devices

For standard electrical installation boxes LED for status visualisation




Aperio PAP Software Set (online/offline)

500ZB-PAPUSB-00

The Aperio wireless dongle is connected directly to the PC via a USB connection
Communicates with the Aperio PAP Tool and establishes a wireless connection with the online components. The pre-set settings in the Aperio PAP Tool are transmitted to the escutcheons and cylinders via this wireless connection
The entire radio communication AES-128 bit encrypted when loading and transferring data





Spring Latch & Deadbolt

Q60X85MM-SS UNION 85mm centre 60mm backset Euro profile cylinder Commercial

SMARTair®

The access control system with multiple solutions and applications



What is SMARTair®?

SMARTair® is an access control solution that is easy to install, easy to manage and and easy to use. This wireless access control system is built around three main elements; an intuitive management software, a range of SMARTair® locks to secure just about any opening as well multiple credentials, giving users a choice from RFID cards to PIN codes and even mobile access.

With SMARTair® you can even open doors remotely.

SMARTair® features

- Wireless access control solution
- Easy to install
- Flexible management of access rights
- Real-time control
- Audit-trails

- Battery powered lasts up to 24 months depending on use
- Can be retrofitted to existing doors
- Cost effective
- Attractive design The elegant slimline look of SMARTair™ locks suit any building style.

SMARTair® Solutions Overview

SMARTair® Standalone



Programmable at each door & suitable for smaller sites with no need to run a software

SMARTair® Update on Card



Encode user cards directly for convenient access management & collects audit trails

SMARTair® Wireless Online



Maximum system capability for large and busy buildings with many doors. Allows for real-time access control

Mobile access control with SMARTair® Openow™



Replaces keys and smart-cards with secure credentials stored on a user's smartphone. Openow™ app unlocks any SMARTair device

To find out more or to request a demonstration contact your sales representative or ASSA ABLOY on 011 761 5000 or email za.info@assaabloy.com





SMARTair Electronic Escutcheon

MSMCC12SL1S008S
Escutcheon with or without cylinder piercing
Wireless and battery powered
Integrated RFID reader
Can be retrofitted
An optional additional handle and antibacterial surface for healthcare applications are available



SMARTair Electronic Escutcheon

MSMCC12SL1S008S
Escutcheon with Pin Code and Card
Escutcheon with or without cylinder piercing
Wireless and battery powered
Integrated RFID reader
Can be retrofitted
An optional additional handle and antibacterial
surface for healthcare applications are available



Cylinder Offset

M2X19 33X45T Turn knob cylinder Euro profile

M2UB0A60LP






SMARTair Lock body for wooden doors

Mortice lock for wooden doors
Conforms to the UNE-EN 12209 standard
EC certified
Reversible, silent latch in sintered steel
Profile of the latch: 17mm (extra security)
Distance between shafts: 85mm
Backsets: 60/70mm
Panic exit function
External protection device
Steel follower rod: 8mm
Deadbolt follower rod: 6mm
Optional round shape 1/2
TE-5 Euro profile cylinder with nickel steel keys
LP and HL finishes: cylinder finish in brass
HN, AI and NE finishes: cylinder finish in nickel

Access Control SMARTair Access Control



SMARTair Lock body for Aluminium doors

M4210305PNM
2240 AUT LOCK 2240 AUTO Series Automatic
locking system
Stainless steel frontplate and strikeplate
Backset 30mm
Distance between center 85mm
Maximum distance between hook and strikeplate
5mm





SMARTair Electronic Knob Cylinder

MSNCK13S530E30M SMARTair Knob Single Cylinder Mifare Upgrades existing mechanical cylinder to an access-controlled cylinder Integrated RFID reader Suitable for office and meeting room doors Compatible with glass, aluminium and wooden doors Easy retrofitting






SMARTair Electronic Knob Cylinder

MSNCK13S530E30M SMARTair Knob Double-sided cylinder Mifare

Upgrades existing mechanical cylinder to an access-controlled cylinder Integrated RFID reader Suitable for office and meeting room doors Compatible with glass, aluminium and wooden doors Easy retrofitting








SMARTair Small Reader

MSMAR2PDSSI
Suited for internal application
Wired wall readers with RFID reader suitable for access doors, turnstiles, barriers, and elevators
Wall reader with keypad for multi-authentication
(Different levels: PIN, PIN & CARD, CARD only)
Slim design version for narrow or aluminium profile doors






SMARTair Wall Reader

MSMR3PUSSB

Wired wall readers with RFID reader suitable for access doors, turnstiles, barriers, and elevators Wall reader with keypad for multi-authentication (Different levels: PIN, PIN & CARD, CARD only) Slim design version for narrow or aluminium profile doors





SMARTair Wall Reader

MSNCR2KUSSB

SMARTair reader with Pin Code and Card Built-in RFID capability Suitable for access doors, turnstiles, fences, barriers and elevators

Wall reader with keypad for multi-authentication (Different levels: PIN, PIN & CARD, CARD only)







SMARTair Relay Card

MSMCR2RXSSB

Elevator Controller with Wall Reader 8 relays

Can be a part of an Offline or Update-On-Card (UOC) system

13.56 MHz, MIFARE® technology

Contactless cards

2-4cm read/write distance

Temperature range: -10°C to 80°C

12/24V AC/DC power





SMARTair Cabinet Lock

MLOCKERL

SMARTair E Motion Lock for Lockers Integrated RFID reader

Suitable for healthcare facilities and student dorms Secures lockers, drawers, cupboards and cabinets





Mifare Access Card

M89100875

13.56 MHZ access cards available in 1K and 4K cards

Simple fix memory structure

Memory access conditions freely programmable 2 x 48 bit keys per sector for key hierarchy Personalization options (7B UID version only), supporting flexibility within 4-byte and 7-byte infrastructure, e.g. ISO shortcut, UID mapping and random ID

NXP originality signature to prove MIFARE Classic® authenticity





Mifare 1K Transporter Sticker

M89100981

13.56 MHZ access sticker cards available in 1K and 4K stickers

Simple fix memory structure

Memory access conditions freely programmable 2 x 48 bit keys per sector for key hierarchy Personalization options (7B UID version only), supporting flexibility within 4-byte- and 7-byte infrastructure, e.g. ISO shortcut, UID mapping and random ID

NXP originality signature to prove MIFARE Classic $\!(\!\!\!R\!\!\!)$ authenticity





SMARTair Energy Saver

MSTHDESC22TSB

White

The device helps reduce power consumption by turning off the power when a room is not occupied Can be used in offline or update-on-card version





SMARTair Wireless Hub

MSTWIRELESSHUB

Encrypted communications with secure protocol between the hub and locks
Real-time event modifications
Collection of events in real-time
Card cancellation
Remote opening
No specific wiring required



Purely electronic and cost effective access control system


Achieve a great deal with only a few components!

eCLIQ is an access control system based on ASSA ABLOY's group wide CLIQ technology. The system is essentially composed of electronic keys and electronic locking cylinders. eCLIQ is comprised of just a few components which achieve maximum efficiency by means of perfect interplay and that is reflected first and foremost in the outstanding cost-benefit relationship. With the large variety of available types of locking cylinders in the modular system, up to 200,000 cycles of maintenance-free use of the cylinders, their compatibility with all conventional doors and door systems, eCLIQ leaves open all possibilities for the design of a locking system.



Key Benefits


- Electronic access control without wiring
- Minimize risk of stolen keys
- Immediate audit trails
- Maximum flexibility to assign and revoke access rights
- IP67 rated keys
- IP67 rated padlock
- Easily replaced standard battery in the key
- 200,000 cycles of maintenance-free
- Portable programming devices





Access Control eCLIQ








eCLIQ Standard User Key

N109E-U-N N109E3-U-N

Used with the eCLIQ cylinders and padlocks Modern reversible key system Unique electronic and system encryption Data and power transmission to the cylinder is contact based and highly encrypted IP67 - protected against temporary immersion in water








eCLIQ Programming Key

N109-P-NR

Used with the eCLIQ programming device
Transfers up to 750 programming steps to cylinder
Can read up to 1500 events from cylinders and
transfers them to the software
Protected by 6-digit individual PIN code
Data and power transmission to the cylinder is
contact based and highly encrypted
IP67 rated - protected against temporary
immersion in water
30 000 locking operations







eCLIQ Connect Key

N110E2-U-R-NR

Incorporates Bluetooth® technology to update keys without a remote programming device at hand

Get changes to authorisations and time settings using the CLIQ® Connect app

Provides immediate audit trails when key is connected to the programming device or app Data and power transmission is contact based and highly encrypted

IP67 rated - protected against temporary immersion in water About 10 000 closing procedures by 1 000

Bluetooth® connections



eCLIQ Profile Double Cylinder

N531-30

N531-35

For use in entrance and exit doors as well as internal doors

Maintenance free for up to 200 000 cycles Splash-proof IP54

Dust and protection cap available for one or both sides

Cam made of break-proof, corrosion resistant stainless steel

Available in 30|30 and 35|35 lengths (other lengths available on request)

Brass cylinder housing components



eCLIQ Profile Knob Cylinder

N534-30D/30E N534-35D/35E

For use in internal doors

Maintenance free for up to 200 000 cycles Splash-proof IP54 rated

Dust and rain protection cap available for one or both sides

Cam made of break-proof, corrosion resistant stainless steel

Basic cylinder length 61mm (L=30|30mm)

Also available in lengths of 35|35mm with other lengths available on request

Brass cylinder housing components

Finish: Satin Nickel



eCLIQ Profile Single Cylinder

N532-38

For use on doors which only need locking on one side (e.g. gates)

Maintenance free for up to 200 000 cycles Splash-proof IP54 rated

Dust and rain protection cap available

Cam made of break-proof, corrosion resistant stainless steel


Available in 30mm

Brass cylinder housing components

Finish: Satin Nickel

Access Control eCLIQ





eCLIQ Server Rack Cylinder

N532V

Maintenance free for up to 200 000 cycles Splash-proof IP54

Dust and rain protection cap available for one or both sides


Cam made of break-proof, corrosion resistant stainless steel

Basic cylinder length 31mm

Finish: Satin Nickel

eCLIQ Switch Cylinder





N511

For use on machinery and vehicles which need an additional layer of security

Maintenance free for up to 200 000 cycles Splash-proof - IP54 rated


Dust and rain protection cap available Key rotation 60°

Brass cylinder housing components

Finish: Satin Nickel

eCLIQ Switch cylinder





N098-SDN N098-ODN

For use in retail environments on roller shutter doors

Maintenance free for up to 200 000 cycles Splash-proof IP54 rated

Dust and rain protection cap available for one or both sides


Fixed total length 47mm

Cam made of steel and is ordered in one of four positions

Cam radius 17mm Finish: Satin Nickel

eCLIQ Cam Lock Cylinder





N923-SDN N923-ODN

Secures cabinets, lockers and cupboards
Maintenance free for up to 200 000 cycles
Dust and rain protection cap available
Key withdrawal when locking lever is closed
Brass cylinder housing components
Finish: Matt Chrome Plated



eCLIQ Nightlatch Cylinder

N063

Utilised in government applications, sub-stations and transformer doors, as well as residential applications

Maintenance free for up to 200 000 cycles Dust and rain protection cap available for one or both sides

Anti-drill protection Finish: Satin Nickel





eCLIQ Padlocks

N316-2508 N316-5008

Used to secure gates, chains and electrical installations

Maintenance free for up to 200 000 cycles Dust and rain protection cap available Optionally IP67 certified with protective cap Key retaining in open position


Housing - Chrome Plated Brass

Cylinder - Nickel Plated Brass

Standard shackle clearance height 25mm & 50mm Hardened steel shackle as standard

Non-corrosive steel shackle 8mm diameter available for the 25mm padlock





eCLIQ Desk Programming Device

NP04

Provides a secure interface between the keys and the CLIQ Web Management Software Reads even memory in electronic E2 and E3 user keys

Programmes the E3 key to retrieve audit trails USB port standard fitting Powered via USB








eCLIQ Wall Programming Device


NR01

Fixed site device that enables user keys to be programmed near the work area Permits changes to times and authorisations as well as the read-out event logs Connection via standard network cable Mini-USB connection for data exchange over cable IP44 rated - drip water-proof

Access Control eCLIQ







eCLIQ Vandalism-Proof Programming Device

NR03

Programs user keys in remote unmonitored locations

Connected by standard network cable Suitable for outdoor usage and vandalism hazard

Permits changes to times and authorisations as well as the read-out of event logs Supports power over ethernet

Optional dust and rain cover available Vandalism resistant IK9

IP65 (when used with weather protection cap)





eCLIQ Mobile Programming Device

NR05

Ideal for shift supervisors or remote site leaders Portable - no need to be at the control room for key updates

Permits changes to time and authorisation keys as well as the read-out of event logs

Communicates via Bluetooth with a mobile iOS or Android Device

Powered by 4X AAA batteries



250kg Mini Magnetic Single Lock

AR-261-005

Suitable for use on aluminium, timber and steel doors

Compact case size & clean aesthetics Maintains a magnetic holding force of at least 250kg (550lbs)

Strong durability & low maintenance Fit any aluminium, timber or steel door CE marked to EMC Directive

Successfully completed 30 minute fire test Security pin feature - prevents unauthorised

bracket removal Monitored function

250kg Mini Magnetic Lock



AR-262-005

Suitable for use on aluminium, timber and steel doors

Compact case size & clean aesthetics Maintains a magnetic holding force of at least 250kg (550lbs)

Strong durability & low maintenance
Fit any aluminium, timber or steel door
CE marked to EMC Directive
Successfully completed 30 minute fire test
Security pin feature - prevents unauthorised bracket removal
Monitored function



260/280 Glass Armature Bracket

AR-268-600

Bracket for use with glass door For use with 260/280 series magnets

Width: 160mm Depth: 25mm

Satin Anodised Aluminium

Weight: 480g

Magnet Height: 62mm Magnet Length 160mm Magnet Depth: 25mm

Height 62mm



510kg Standard Magnetic Lock

AR-281-005

Suitable for use on aluminium, timber and steel doors

Compact case size and clean aesthetics Magnetic holding force of at least 510kg (1120 lbs) Security pin feature to prevent unauthorised removal of the magnet Available in double magnet model

Available in double magnet mode Built in voltage spike suppressor Monitored function





510kg Mortice Standard Magnetic Lock

AR-282-005 Monitored


Mortice mounted for single action swinging or sliding door

Surface mounted double direct-pull magnet 12/24vDC

Monitored function

Suitable for timber or metal door applications





External Gate Lock

AR-291-005

Monitored

IP67

To facilitate remote access and exit control of any external gate/barrier

Maintains a magnetic holding force of at least 540kg

Independently tested to achieve an ingress protection rating of IP67


Built in voltage spike suppressor

User selectable dual voltage - 12 or 24vDC

Reed switches monitoring as standard

Dual fixing positions to suit both side and face fix applications

Suitable for use on aluminium, timber and steel doors



Mortice Mini Shear Lock

EDS-1354-0100 CE Marked to EMC Directive Mortice or surface versions Can be fitted into the head or vertical locking stile

Can be fitted into the head or vertical locking stile Suitable for aluminium, timber, steel and glass doors

Compact slim line size - 30mm Nominal 1500kg shear holding force Adjustable locking time 1-30 secs Suitable for door gaps up to 8mm Supplied with 3m cable Non-handed

Access Control Accessories






Power Supplies 12V DC 3AMP

EDS-YP902 3amp with Tx box With battery space for battery back up





12V8AH GEL Battery

EDS-862-20-GEL8

Suitable for use in battery backup power supplies Maintenance free - sealed GEL (Gelled Electrolyte Lead) acid

Nominal voltage: 12V Rated capacity: 8Ah Weight: 2.30 kg





Red Break Glass

BGLASS-R Red break glass box





Green Break Glass

BGLASS-G Resettable green break glass box





No Touch Exit Device

EDS-K1-1 LED Indicator Input Volt.: DC 12V Contact Rating: 3A/DC 30V Durable stainless steel plate Detection range: 0.1 - 10cm





Pin Code Weather Proof

YLIYK-568L Numeric access control keypad Supports touch-less card reading Supports up to 500 users Suitable for outdoor installation






Keypad Reader and Controller Combo

AC-G43
500 user self contained PIN controller
2x 5A Output Relays and 2 inputs
3 security modes and 3 user levels
Weather resistant
Illuminated keys
Ideal for applications with frequent night time
traffic and dark difficult visibility
Works on 12-24 VAC or 16-24 VDC 10-Wire
Interface





Eff Eff Electric Strike

E7A-10602D1139

12V DC

Fail Secure

Suitable for all common striking plates

Adjustable latch

Due to 180° fitting, can be used DIN right and left

200,000 cycle testing


Break-in Resistance of 3500N

Voltage 6-12V AC/DC

Height: 75mm Width: 20mm

Depth: 28mm





Eff Eff Electric Strike

17KL-GY

Fail Secure

Universally applicable against the most common

push-in door locks

The bolt catcher can be adjusted 4 mm horizontally

after installation

Universal direction of rotation

Essential parts are hardened

Low maintenance

Locked without voltage





Eff Eff Electric Strike

27KL-GY

Fail Safe

Suitable for all common striking plates

Due to 180° fitting, can be used DIN right and left

Hold open function

Break-in resistance of 3500N


Adjustable latch

Height: 75mm

Width: 20mm

Depth: 28mm





Eff Eff Electric Strike

37KL-SS

With Hold Open Function

Suitable for all commonly used striking plates

Can be mounted DIN right or left by turning over


180°

Break-in Resistance of 3500N

Height: 75mm Width: 20.5 mm

Depth: 28mm






Eff Eff Sliding Door Latch Without Cylinder

1112-GY
Sliding door hook latch
Standard strike
Excludes cylinder
Designed for use with the 112 Series and 312 Series electric strike






Eff Eff Electric Strike Sliding Door

112KL-GY Electric strike for sliding door or gate Water-proof for outdoor use Break-in resistance of 3000N Universal DIN direction Accessories for hook type lock






Trimec Electric Strike

TS101A
Stainless steel striker
Extra length for latch
3 hardened locking pins
IP56 weather resistant option available
Cycle tested to 1 000 000 operations
Static tested to 1363kg holding force
Fail secure and fail safe option





Trimec Electric Strike

ES9000

Suits harsh commercial environments Operates up to 25kg of pre-load pressure on the keeper

Multi voltage 10 - 30Vdc

Field changeable settings from fail safe to fail secure


Tested in excess of 2 million cycles Fire-rated up to 4 hours on fire door assemblies in accordance with AS1905.1.2005

ASSA ABLOY CATALOGUE 2021/22

Weather resistant Non-handed

CE approved





12V DC Fail Secure Electric Strike

7100-310-628 Adams Rite

Suitable for use on aluminium doors


Non-handed

The compact mechanism fits into an aluminium jamb section as shallow as 44.45mm

Round corners of faceplate to aid installation into aluminium doors

Flat faceplates for mounting in the frame of a single action single leaf doors





12V DC Fail Safe Electric Strike

7100-315-628 Adams Rite 12vDC

Suitable for use on aluminium doors


Non-handed

The compact mechanism fits into an aluminium jamb section as shallow as 44.45mm

Round corners of faceplate to aid installation into aluminium doors

Flat faceplates for mounting in the frame of a single action single leaf doors






Deadlatch 24mm B/S

4750-200-6 Adams Rite Flat Face separate Euro Profile Cylinder Non-handed

Can be used in conjunction with the 7100, 7400 and TS101A series Electric Strike to provide remote access control

Operates with standard Euro cylinder Designed for use on aluminium doors Independently tested to 1 million cycles





Deadlatch 37mm B/S


4750-400-6 Adams Rite Flat Face Euro Profile Cylinder Non-handed

Can be used in conjunction with the 7100, 7400 and TS101A series electric strike to provide remote access control

Operates with standard Euro cylinder Designed for use on aluminium doors Independently tested to 1 million cycles

Access Control Electric Strikes





Deadlatch 24mm B/S


4710-200-6 Adams Rite Flat Face Round Cylinder Right Hand

Heavy duty Deadlatch offers flexible traffic control Operates using mortice cylinder, thumbturn (both with MS® cam) or range of Adams Rite furniture Can be used in conjunction with 7100 and TS101A series Electric Strikes to provide remote access control

Designed for use on aluminium doors Latchbolt reversible and supplied non-handed unless specified Maximum operational door gap is 5mm


Independently tested to 1 million cycles





Deadlatch 37mm B/S

4710-400-6
Adams Rite
Flat Face
Round Cylinder
Right Hand
Heavy duty Deadlatch offers flexible traffic control
Designed for use on aluminium doors
Latchbolt reversible and supplied non handed
unless specified
Maximum operational door gap is 5mm
Independently tested to 1 million cycles



Round Cylinder

4036-61-01-628
Adams Rite
Suitable for use with round screw in cylinder locks
Supplied with 3 keys per cylinder
Supplied with 6mm trim ring
Guarantee 3 years
Thumbturn version available






Faceplate for Deadlatch Lock

24-4700-000-628 Adams Rite Series 4750 and 4710





1391 Solenoid Bolt

1391-1042 Adams Rite 12V DC

Used to facilitate the remote access and exit control of aluminium, timber or steel doors Holding force in excess of 1000kg Slimline style allows the lock to be concealed fitted into the door frame

Stainless steel deadbolt has a 16mm throw Suitable for single and double action doors (with positive centering door closers)

Can be fitted into head or into vertical locking stile





1391 Surface Mount Box


1391-3042 Adams Rite 12V DC

Used to facilitate the remote access and exit control of aluminium, timber or steel doors Holding force in excess of 1000kg Slimline style allows the lock to be concealed fitted into the door frame Stainless steel deadbolt has a 16mm throw

Stainless steel deadbolt has a 16mm throw Suitable for single and double action doors (with positive centering door closers)

Can be fitted into head or into vertical locking stile





Abloy Electric Lock

EL560 60/50mm

Handle controlled solenoid lock used in timber and metal doors

Suited for medium traffic doors

Can be electrically controlled by access control system or by a remote control system such as timer, keypad or push button

Can be used both in exit doors and fire rated doors (EN)


Suitable for interior doors

Only outside handle is electrically controlled The lock can always be opened by inside handle Possible mechanical opening by cylinder

Access Control

Electric Locks





Abloy Electric Lock

EL561 60/50mm

Access In & Out

Handle controlled solenoid lock used in timber and metal doors

Suited for medium traffic doors


Can be electrically controlled by access control system or by a remote control system such as timer, keypad or push button

Can be used on fire rated doors (EN)

Recommended to be used in interior doors Both inside and outside handles are electrically

Possible mechanical opening by cylinder





Abloy Electric Lock

EL460

35mm


Handle controlled solenoid lock used in narrow profile doors

Suited for medium traffic doors

Can be electrically controlled by access control system or by a remote control system such as timer, keypad or push button

Can be used both in exit and fire rated doors (EN) Recommended to be used in interior doors Only outside handle is electrically controlled The lock can always be opened by inside handle Possible mechanical opening by cylinder





Abloy Electric Lock

EL461

35mm

Access In & Out

Handle controlled solenoid lock used in narrow profile doors

Suited for medium traffic doors


Can be electrically controlled by access control system or by a remote control system such as timer, keypad or push button

Can be used in fire rated doors (EN)

Recommended to be used in interior doors Both inside and outside handles are electrically controlled

Possible mechanical opening by cylinder





Motorized Lock

EL520 60mm


Timber doors

Motor lock used in wooden and metal doors Motor locks are best suited in high traffic doors Can be electrically controlled by access control system or by a remote control system such as timer, keypad or push button

The locks can be used both in exit and fire rated doors (EN)

Recommended to be used in high traffic doors





Solenoid Lock

L-4040001 25/30/35mm Adjustable Fail Secure with EA307


Can be used in aluminium swinging doors Can be controlled by a variety of control devices such as card reader, keypad or timer

The lock can be connected to automatic swing door operator

Frame mounting above the door is also possible Not for use in fire rated doors

Typically used in exterior doors of apartment buildings and interior doors of business premises Door can be opened by pushing or pulling when electric control is switched on





Abloy Electric Lock

EDS-EL502

60mm

Fail Secure

Push & pull function solenoid lock for timber and metal doors

Can be used in swinging doors

Can be controlled by a variety of control devices such as card reader, keypad or timer

The lock can be connected to automatic swing door operator

Frame mounting above the door is also possible Not for use in fire rated doors

Typically used in exterior doors of apartment buildings and interior doors of business premises Door can be opened by pushing or pulling when electric control is switched on






EA Cables

EA218-000000 Cable 6m, EL420-EL560 EA219-000000 Cable 10m, EL420-EL560 EA221-000000 Cable 10m, EL402, EL502 EA322-100000 Strike Plate EA288-001000 Splint Spindle 47/50mm, 8mm EA288-002000 Splint Spindle 57/50mm, 8mm





Stainless Steel Door Loop

FA280

Designed to ensure the unbroken transfer of cable between the door and the frame

The maximum diameter of the cable is 7,5 mm and it is recommended to use multicore cable because of its increased bending strength

When the opening angle of the door is more than 120° or the distance between the hinge and the door frame is more than 20 mm, the long lead cover EA281 should be used

HID





iClass SE R10 Contactless Smart Card Reader

iClass SE R10 iClass SE RP10 Wiegand Pigtail Standard Configuration Settings

Cost-Effective Platform – designed for secure card or mobile credential deployments

Simplified Bluetooth Configuration – streamlined selection, ordering and management of reader inventory

Made for Seos and BLE enabled


Includes intelligent power management which can reduce power consumption by as much as 30%





iClass 2k Bits


2000CGGNN HID Card Configured non-programmed Plain white front and back No external numbers



Inward Opening Steel Gates RH

68000601

Automatic exterior side locking
Works on both swing gates and doors
Compact and secure single unit steel case rim lock
Screw or weldable steel surface mounting with left
hand-inward position and reversible deadlatch
Steel and brass construction for secure and
corrosion resistant all weather applications




Inward Opening Steel Gates RH with Button

68080601

Automatic exterior side locking
Works on both swing gates and doors
Compact and secure single unit steel case rim lock
Screw or weldable steel surface mounting with left
hand-inward position and reversible deadlatch
Steel and brass construction for secure and
corrosion resistant all weather applications

Black Series






Bontebok Black Lever Handle on Rose

UNION 6272-06SSBLK Suitable for external and coastal applications

Finish

Matte Black





Impala Black Lever Handle on Rose


UNION 6274-06SSBLK Suitable for external and coastal applications

Finish

Matte Black

Pull Handles






Pull Handle

UNION 5209BBSSBLK Suitable external applications Back-to-back (Pair)

Finish

Matte Black





Pull Handle

UNION 520286-400BBSSBLK Suitable external applications Back-to-back (Pair)


Finish

Matte Black

Cylinder Locks







Euro Profile Double Cylinder

UNION
2X18BL
5 pin cylinder
Supplied with sawn key
5 year warranty
Cylinder length: 66mm
Available as KD, KA, MKD and GMK

Finish

Black Series Cylinder Locks



Euro Profile Thumbturn Cylinder Finish

UNION 2X19BL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 66mm Available as KD, KA, MKD and GMK Matte Black



Euro Profile Single Cylinder

UNION 2X20BL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 42.5mm Available as KD, KA, MKD and GMK

Finish

Matte Black





Black rack and pinion door closer Finish with guide rail

ASSA ABLOY DC135BLK Rack and pinion door closer with guide rail Certified in compliance with EN 1154, size 3 For single action doors up to 950mm wide Can be used on left and right-handed doors Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Closing force configurable Opening angle up to 180°



Black Door closer with Cam-Motion® technology and guide rail

ASSA ABLOY DC500BLK

Door closer with Cam-Motion® technology

Certified in compliance with EN

1154, size 1-4

For single action doors up to

1100mm wide

Fulfils barrier-free building requirements (EA / CEN TR 15894)

Can be used for left and

right-handed doors

Suitable for fire and smoke protec-

tion doors

Adjustable closing speed, latching


speed and backcheck

Variable adjustable closing force

Opening angle up to 160°

Hold-open variant available Hold-open angle 130°

Escutcheons



Euro Profile Escutcheon – Round

UNION SS5305-05SSBLK


Finish

Finish

Matte Black

Matte Black






Keyhole Escutcheon – Round

UNION SS5305-24SSBLK

Finish

Matte Black





Euro Profile Escutcheon – Square


UNION SS5306-05SSBLK

Finish

Black Series

Escutcheons





Keyhole Escutcheon – Square


UNION SS5306-24SSBLK

Finish

Matte Black

Architectural Hardware






Ball Bearing Butt Hinge

UNION JH-BB-STD-2-BLK Grade 304 stainless steel BS EN 1935:2002 Grade 13

Finish

Matte Black





Half Moon Doorstop

UNION 87001SSBLK

Finish

Matte Black

Flush Handles






Flush handle

UNION SS5004SSBLK

Finish

Matte Black





Flush handle


UNION 99004SSBLK

Finish










Bathroom Escutcheon - Round

UNION SS5305-73SSBLK 8mm spindle Finish

Matte Black








Bathroom Escutcheon - Square

UNION SS5306-73SSBLK 8mm spindle **Finish**

Door Furniture




Valli & Valli Designer Range Designer Pull Handles



Valli & Valli Designer Range Designer Pull Handles





Pull Handle

Brass VV-K1210-PB VV-K1210-SC VV-K1210-ANT VV-K1210-SB



Polished Brass Satin Chrome Antique Satin Brass






Pull Handle

Aluminium VV-K1231-300-SC VV-K1231-300-CH VV-K1231-600-SC VV-K1231-600-CH

Finishes

Satin Chrome Chrome






Pull Handle

Aluminium VV-K1235-300-SC VV-K1235-300-CH VV-K1235-600-SC VV-K1235-600-CH

Finishes

Satin Chrome Chrome





Pull Handle

Brass VV-K1055-300-SC VV-K1055-300-CH VV-K1055-600-SC VV-K1055-600-CH

Finishes

Satin Chrome Chrome






Pull Handle

Brass VV-K1056-300-CH VV-1056-600-CH

Finishes

Chrome

Valli & Valli Designer Range Designer Pull Handles




Pull Handle

Brass VV-K359-649-CH VV-K359-649-SC

Finishes

Chrome Satin Chrome




Lever Handle

Brass VV-H372-R8 (Keyhole Escutcheon) VV-H372-R8Y (Euro Profile Escutcheon)

Finishes

Satin Chrome Chrome




Lever Handle

Brass VV-H370-R8 (Keyhole Profile Escutcheon)

Finishes

Satin Chrome Chrome




Lever Handle

Brass VV-H356-R8 (Keyhole Escutcheon) VV-H369-R8Y (Euro Profile Escutcheon)

Finishes

Satin Chrome Chrome




Lever Handle

Brass VV-H369-R8 (Keyhole Escutcheon) VV-H369-R8Y (Euro Profile Escutcheon)


Finishes

Satin Chrome Chrome


Designer Lever Handles



Designer Lever Handles



Designer Lever Handles




Lever Handle

Brass VV-H174-R8 (Keyhole Escutcheon) VV-H174-R8Y (euro Profile Escutcheon)

Finishes

Polished Brass




Lever Handle

Brass VV-H123-R8 (Keyhole Escutcheon) VV-H123-R8Y (Euro Profile Escutcheon)

Finishes

Polished Brass Antique Brass




Lever Handle

Brass VV-H120-R8 (Keyhole Escutcheon) VV-H120-R8Y (Euro Profile Escutcheon)

Finishes

Polished Brass






Lever Handle

Brass VV-H198-R8 (Keyhole Escutcheon) VV-H198-R8Y (Euro Profile Escutcheon)

Finishes

Polished Brass Satin Chrome




Lever Handle

Brass VV-H1034-R8 (Keyhole Escutcheon) VV-H1034-R8Y (Euro Profile Escutcheon)

Finishes

Chrome Satin Chrome

Designer Lever Handles





Lever Handle

316 Grade stainless steel VV-H5023-R8 (Keyhole Escutcheon) VV-H5023-R8Y (Euro Profile Escutcheon)

Finishes

Satin Stainless Steel






Lever Handle

Brass VV-H1057-R8 (Keyhole Escutcheon) VV-H1057-R8Y (Euro Profile Escutcheon)

Finishes

Polished Brass Chrome





Lever Handle


Brass VV-H1056-R8 (Keyhole Escutcheon) VV-H1056-R8Y (Euro Profile Escutcheon)

Finishes

Chrome

Designer Knob Handles






Knob Turn Handle

Brass VV-K5056

Finishes

Chrome






Knob Turn Handle

Aluminium VV-K1055-R8 (Keyhole Escutcheon) VV-K1055-R8Y (Euro Escutcheon)

Finishes

Chrome Satin Chrome

Antelope Series On Rose




Springbok Lever Handle

UNION 6270-06SS

Finish

Stainless Steel






Bontebok Lever Handle

UNION 6272-06SS

Finish

Stainless Steel




Tsessebe Lever Handle

UNION 6273-06SS

Finish

Stainless Steel





Impala Lever Handle

UNION 6274-06SS

Finish

Stainless Steel




Nyala Lever Handle

UNION 6276-06SS

Finish


Stainless Steel

Sandpiper Tubular Series On Rose



Sandpiper Tubular Series On Rose






Falcon Lever Handle

UNION 6255-06SS

Finish

Stainless Steel





Eagle Lever Handle


UNION SS6EA00-06SS

Finish

Stainless Steel

Tubular Stainless Steel Series On Backplate






Tubular Lever Handle

UNION
152X45mm Plate
6145-05SS Euro profile
6145-06SS Blank
6145-13SS Oval profile
6145-24SS Keyhole profile
6145TL-73SS Bathroom (LH)
6145TR-73SS Bathroom (RH)
Spindle size for bathroom variant
5mm

Finish

Stainless Steel






Tubular Lever Handle

UNION 152X76mm Plate SS6163-05SS Euro profile SS6163-06SS Blank SS6163-13SS Oval profile SS6163-24SS Keyhole profile SS6163TL-73SS Bathroom (LH) SS6163TR-73SS Bathroom (RH) Spindle size for bathroom variant 5mm

Finish


Stainless Steel



80

Tubular Stainless Steel Series On Backplate





Tubular Lever Handle

UNION 152X152mm Plate SS6166-05SS Euro profile SS6166-06SS Blank SS6166-13SS Oval profile SS6166-24SS Keyhole profile SS6166TL-73SS Bathroom (LH) SS6166TR-73SS Bathroom (RH) Spindle size for bathroom variant


Finish

Stainless Steel

Dove Lever Furniture

Dove Lever Handles





Dove 22mm Lever Handles


UNION
152X76mm Plate
SS6D63-22-05SS Euro Profile
SS6D63-22-06SS Blank
SS6D63-22-13SS Oval profile
SSD63-22-24SS Keyhole profile
SS6D63-22TL-73SS Bathroom (LH)
SS6D63-22TR-73SS Bathroom
(RH)
Spindle size for bathroom variant
5mm

Finish

Stainless Steel



Door Furniture



Dove 22mm Lever Handles

UNION
152X152mm Plate
SS6D66-22-05SS Euro Profile
SS6D66-22-06SS Blank
SS6D66-22-13SS Oval profile
SSD66-22-24SS Keyhole profile
SS6D66-22TL-73SS Bathroom (LH)
SS6D66-22TR-73SS Bathroom
(RH)
Spindle size for bathroom variant
5mm

Finish


Stainless Steel



Narrow Stile Lever Handles

Narrow Stile Lever Handles






Narrow Stile Lever Handle

UNION QH26SN01 Euro 85mm

Finish

Satin Nickel (SN) Brown (BR) Black (BLK) White (WH)






Sandpiper Narrow Stile Lever Handle

UNION 6503-05SS Euro 85mm

Finish

Stainless Steel






Sandpiper Narrow Stile Lever Handle

UNION 6601-06SS

Finish

Stainless Steel




Sandpiper Narrow Stile Lever Handle

UNION 6604-06SS

Finish


Stainless Steel





Seagull Lever Handle


UNION 229X44mm Plate SS6SG01-44-05SS Euro Profile SS6SG01-44-09SS Euro profile 47mm SS6SG01-44-13SS Oval profile SS6SG01-44-24SS Keyhole profile SS6SG01-44-73SS Bathroom (LH & RH)



Finish

Stainless Steel

82




Dove Lever Handle on Rose

UNION AL6D00-06AS

Finish

Anodised Silver






Dove Lever Handle on Plate

UNION 150x50mm Plate AL6D20-05A Euro profile AL6D20-06AS Blank AL6D20-13AS Oval profile AL6D20-24AS Keyhole profile AL6D20TL-73AS Bathroom (LH) AL6D20TR-73AS Bathroom (RH)

Finish

Anodised Silver






Dove Lever Handle on Plate

UNION 150X45mm Plate AL6D45-05AS Euro profile AL6D45-06AS Blank AL6D45-13AS Oval profile AL6D45-24AS Keyhole profile AL6D45TL-73AS Bathroom (LH) AL6D45TR-73AS Bathroom (RH)

Finish

Anodised Silver






Dove Lever Handle on Plate

UNION
152X76mm Plate
AL6D63-05AS Euro profile
AL6D63-06AS Blank
AL6D63-13AS Oval profile
AL6D63-24AS Keyhole profile
AL6D63TL-73AS Bathroom (LH)
AL6D63TR-73AS Bathroom (RH)


Finish



Aluminium Lever Handles

Dove Series






Dove Lever Handle on Plate

UNION 152X152mm Plate AL6D66-05AS Euro profile AL6D66-06AS Blank AL6D66-13AS Oval profile AL6D66-24AS Keyhole profile AL6D66TL-73AS Bathroom (LH) AL6D66TR-73AS Bathroom (RH)

Finish

Anodised Silver





Dove Lever Handle on Plate


UNION 152X176mm Plate AL6D67-05AS Euro profile AL6D67-06AS Blank AL6D67-13AS Oval profile AL6D67-24AS Keyhole profile AL6D67TL-73AS Bathroom (LH) AL6D67TR-73AS Bathroom (RH)

Finish

Anodised Silver

Teal Series






Teal Lever Handle on Rose

UNION AL6T00-06AS

Finish

Anodised Silver







Teal Lever Handle on Plate

UNION 150X50mm Plate AL6T20-05AS Euro profile AL6T20-06AS Blank AL6T20-13AS Oval profile AL6T20-24AS Keyhole profile AL6T20TL-73AS Bathroom (LH) AL6T20TR-73AS Bathroom (RH)

Finish






Teal Lever Handle on Plate

UNION 150X45mm Plate AL6T45-05AS Euro profile AL6T45-06AS Blank AL6T45-13AS Oval profile AL6T45-24AS Keyhole profile AL6T45TL-73AS Bathroom (LH)

Finish

Anodised Silver





Teal Lever Handle on Plate


AL6T45TR-73AS Bathroom (RH)

UNION 152X76mm Plate AL6T63-05AS Euro profile AL6T63-06AS Blank AL6T63-13AS Oval profile AL6T63-24AS Keyhole profile AL6T63TL-73AS Bathroom (LH) AL6T63TR-73AS Bathroom (RH)

Finish

Anodised Silver






Teal Lever Handle on Plate

UNION 152X152mm Plate AL6T66-05AS Euro profile AL6T66-06AS Blank AL6T66-13AS Oval profile AL6T66-24AS Keyhole profile AL6T66TL-73AS Bathroom (LH) AL6T66TR-73AS Bathroom (RH)

Finish

Anodised Silver






Teal Lever Handle on Plate

UNION 152X50mm Plate AL6T67-05AS Euro profile AL6T67-06AS Blank AL6T67-13AS Oval profile AL6T67-24AS Keyhole profile AL6T67TL-73AS Bathroom (LH) AL6T67TR-73AS Bathroom (RH)


Finish



Aluminium Lever Handles

Teal Series






Waterbok Lever Handle on Rose

UNION AL6W00-06AS Anodised Silver

Finish

Waterbok Series





Waterbok Lever Handle on Plate Finish

UNION 150X50mm Plate AL6W20-05AS Euro profile AL6W20-06AS Blank AL6W20-13AS Oval profile AL6W20-24AS Keyhole profile AL6W20TL-73AS Bathroom (LH) AL6W20TR-73AS Bathroom (RH) Anodised Silver





Waterbok Lever Handle on Plate Finish

UNION 150X45mm Plate AL6W45-05AS Euro profile AL6W45-06AS Blank AL6W45-13AS Oval profile AL6W45-24AS Keyhole profile AL6W45TL-73AS Bathroom (LH) AL6W45TR-73AS Bathroom (RH) Anodised Silver







Waterbok Lever Handle on Plate

UNION 152X76mm Plate AL6W63-05AS Euro profile AL6W63-06AS Blank AL6W63-13AS Oval profile AL6W63-24AS Keyhole profile AL6W63TL-73AS Bathroom (LH) AL6W63TR-73AS Bathroom (RH) Anodised Silver

Finish








Waterbok Lever Handle on Plate Finish

UNION 152X152mm Plate AL6W66-05AS Euro profile AL6W66-06AS Blank AL6W66-13AS Oval profile AL6W66-24AS Keyhole profile AL6W66TL-73AS Bathroom (LH) AL6W66TR-73AS Bathroom (RH) Anodised Silver






Waterbok Lever Handle on Plate Finish

UNION 152X50mm Plate AL6W67-05AS Euro profile AL6W67-06AS Blank AL6W67-13AS Oval profile AL6W67-24AS Keyhole profile AL6W67TL-73AS Bathroom (LH) AL6W67TR-73AS Bathroom (RH) Anodised Silver

Bishop Series





Bishop Lever Handle


UNION
AL684-05AS Euro profile
AL684-06AS Blank
AL684-09AS Euro profile (47mm)
AL684-13AS Oval profile
AL684-24AS keyhole profile
AL684TL-73AS Bathroom (LH)
AL684TR-73AS Bathroom (RH)

Finish

Anodised Silver

Protea Series





Protea Lever Handle

UNION
CB612-05 Euro profile
CB612-06 Blank
CB612-09 Euro profile (47mm)
CB612-13 Oval profile
CB612-24 keyhole profile
CB612RL-73 Bathroom (LH)
CB612TR-73 Bathroom (RH)

Finish

Satin Chrome (SC) Chrome Plated (CH)



Cast Zinc Handles

Protea Series





Weaver Knob Handle


UNION CB5240

Finish

Polished Brass (PB)

Gower Series






Gower Lever Handle

UNION CZ682-05 Euro profile CZ682-06 Blank CZ682-09 Euro profile (47mm) CZ682-13 Oval profile CZ682-24 keyhole profile CZ682RL-73 Bathroom (LH) CZ682TR-73 Bathroom (RH)

Finish

Chrome Plated (CH)
Satin
Chrome(SC)





Radius Lever Handle


UNION CZ692-05 Euro profile CZ692-06 Blank CZ692-09 Euro profile (47mm) CZ692-13 Oval profile CZ692-24 keyhole profile CZ692RL-73 Bathroom (LH) CZ692TR-73 Bathroom (RH)

Finish

Chrome Plated (CH)
Satin
Chrome(SC)



88



Aluminium Pull Handle

UNION AL5512-200BBAS (back-to-back) (Pair)

AL5512-200BTAS (bolt-through) (Each)

AL5512-200FLAS (flange fixing) (Each)

AL5512-300BBAS (back-to-back) (Pair)

AL5512-300BTAS (bolt-through) (Each)

AL5512-300FLAS (flange fixing) (Each)

Finish

Silver

Anodised

Finish

Silver

Anodised

UNION AL5515-111BBAS (back-to-back) (Pair)

Aluminium Pull Handle

AL5515-111BTAS (bolt though) (Each)

AL5515-111FLAS (flange fixing) (Each)

AL5515-150BBAS (back-to-back)

AL5515-150BTAS (bolt through) (Each)

AL5515-150FLAS (flange fixing) (Each)

AL5515-200BBAS (back-to-back) (Pair)

AL5515-200BTAS (bolt through) (Each)


AL5515-200FLAS (flange fixing) (Each)

AL5515-300BBAS (back-to-back)


AL5515-300BTAS (bolt through)

(Each)

AL5515-300FLAS (flange fixing) (Each)








Aluminium Pull Handles

Dove Pull Handles





Dove Pull Handle


UNION 45x192mm Plate AL5D02AS Blank

45x254mm Plate
AL5D03AS Oval profile
AL5D04AS Round profile
AL5D05AS Keyhole profile
AL5D06AS Euro profile
AL5D07I Bathroom indicator
AL5D07T Bathroom thumb turn

Finish

Anodised Silver






Dove Pull Handle

UNION AL5D63-06 Blank

Finish

Anodised Silver






Dove Pull Handle

UNION 152x152mm Plate AL5D66-06AS Blank AL5D66 L/R-05AS Euro profile AL5D66 L/R-13AS Oval profile AL5D66 L/R-24AS keyhole profile AL5D66TL/TR-73AS Bathroom set (incl. thumb turn)

Finish

Anodised Silver





Dove Pull Handle

UNION 178x152mm Plate AL5D67-06AS Blank AL5D67 L/R-05AS Euro profile AL5D67 L/R-13AS Oval profile AL5D67 L/R-24AS keyhole profile AL5D67TL/TR-73AS Bathroom set (incl. thumb turn)

Finish







Cupboard Pull Handle

UNION AL5123AS AL5516AS


Finish

Anodised Silver

Stainless Steel Pull Handles

Flush Finger Pull Handles






Finger Pull Handle

UNION FFP65X50 44x62mm

Finish

Stainless Steel





Flush Finger Pull Handle

UNION 99004SS

Finish

Stainless Steel






Flush Finger Pull Handle

UNION SS5004SS


Finish

Stainless Steel



Dove Pull Handles






Dove Pull Handle

UNION 76x152mm Plate SS5D63-06SS

Finish

Stainless Steel






Dove Pull Handle

UNION 152x152mm Plate SS5D66L/R-06SS Blank SS5D66-06L/R-05SS Euro profile SS5D66L/R-13AS Oval profile SS5D66L/R-24AS Keyhole profile SS5D66L/R-73SS Bathroom profile

Finish

Stainless Steel





Dove Pull Handle


UNION
176x152mm Plate
SS5D67-06SS Blank
SSD67L/R-05SS (Euro profile
SS5D67L/R-13SS Oval profile
SS5D67L/R-24SS Keyhole profile

Finish

Stainless Steel

Kinglet Square 'T' Pull Handles





Kinglet Pull Handle

UNION 22x200mm 500286-200BTSS (bolt through) 520286-200BBSS (back-to back)

30x400mm 520826-400BBSS (back-to-back) (Pair) 500286-400BTSS (bolt through) (Each)

30x600mm 520286-600BBSS (back-to-back) (Pair) 500286-400BTSS (bolt through) (Each)



Finish

Kinglet Square 'T' Pull Handles





Kinglet Pull Handle

UNION 22x200mm 5002862-200BTSS (bolt through) 5202862-200BBSS (back-to back)

30x400mm 5208262-400BBSS (back-to-back) (Pair) 502862-400BTSS (bolt through) (Each)

30x600mm 5202862-600BBSS (back-to-back) 502862-400BTSS (bolt through) (Each)

Sandpiper Pull Handles





Sandpiper Pull Handle

UNION 22x150mm PHD-BB-150-22SS (back-to-back) PHD-BT-150-22SS (bolt through) (Each) PHD-CF-150-22SS (flange fixing) (Each)

22x225mm PHD-BB-225-22SS (back-to-back) PHD-BT-225-22SS (bolt through) (Each) PHD-CF-225-22SS (flange fixing) (Each)


22x300mm PHD-BB-300-22SS (back-to-back) (Pair) PHD-BT-300-22SS (bolt through) (Each) PHD-CF-300-22SS (flange fixing) (Each)

Finish

Finish

Stainless Steel


Sandpiper Pull Handles



94

Sandpiper Pull Handles





Sandpiper Pull Handle

Finish

UNION 350x32mm 5215BBSS (back-to-back) (Pair) 5215BTSS (bolt through) (Each)

457x32mm 5905BBSS (back-to-back) (pair)

5905BTSS (bolt through) (pair)

Stainless Steel





Sandpiper Pull Handle

Finish

UNION 600x400x32mm 5920BBSS (back-to-back) (Pair) 5920BTSS (bolt through) (Each) Stainless Steel






Sandpiper Pull Handle

Finish

UNION 400x350mm 5928BBSS (back-to-back) (Pair) Stainless Steel

22mm Pull Handle Range






22mm Pull Handle

Finish

UNION 228x76mm Plate SS5D93-22-06SS Blank

22mm Pull Handle Range






22mm Pull Handle

UNION 228x152mm Plate SS5D96-22-06SS Blank SS5D96-L/R-22-05SS Euro profile SS5D96-L/R-22-13SS Oval profile SS5D96-L/R-22-24SS Keyhole profile SS5D96-TL/RT-22-73SS Bathroom profile

Finish

Stainless Steel






22mm Pull Handle

UNION 304x76mm Plate SS5D76X304-06SS Blank

Finish

Stainless Steel






22mmPull Handle

UNION
304x152mm Plate
SS5D152x301-06SS Blank
SS5D152x301-L/R-05SS Euro
profile
SS5D152x301-L/R-13SS Oval
profile
SS5D152x301-L/R-24 Keyhole
profile
SS5D152x301-TL/TRSS Bathroom
Profile

Finish




Door Hardware



Door & Specialised Hardware Hooks & Multiracks





Hat and Coat Hook

UNION AL8101AS



Anodised Silver





Multirack Two Hat and Coat Hook UNION AL8102AS

Finish

Anodised Silver



Multirack Three Hat and Coat Hook UNION AL8103AS

Finish

Anodised Silver






Multirack Four Hat and Coat Hook UNION AL8104AS

Finish

Anodised Silver





Hat and Coat Hook


UNION AL8721AS **Finish**

Anodised Silver

98

Door & Specialised Hardware Hooks & Multiracks






Coat Hook Rubber Tipped UNION **AL8722AS**

Finish

Anodised Silver






Robe Hook

UNION AL8723AS **Finish**

Anodised Silver






Hat and Coat Hook with Buffer **UNION** SS8025SS

Finish

Stainless Steel

Door Stops





Aluminium Half Moon Door Stop

UNION 9002AS

Finish

Anodised Silver





Wall Door Stop

UNION 99011SS **Finish**

Door Stops





Wall Protection Door Stop

UNION 99022SS



Stainless Steel






Round Door Stop

UNION AL8730AS **Finish**

Anodised Silver






Door Stop

UNION CZ8371SC Finish

Satin Chrome

Door & Wall Stops






Magnetic Door Stop

UNION 87002SN Wall or floor mounted

Finish

Satin Nickel





Magnetic Door Stop

UNION 87003SN Wall or floor mounted

Finish

Satin Nickel




Accessible Facility Indicator Bolt

UNION 37651AS Anodised Silver

Finish





WC Indicator Bolt

UNION AL8098AS Surface mounted Finish


Anodised Silver



WC Indicator Bolt

UNION SS8023SS Surface mounted **Finish**

Stainless Steel




WC Indicator Bolt

UNION AL8294AS

Finish

Anodised Silver






WC Indicator Bolt

UNION CZ80941CHR CZ80941SCR Surface mounted

Finish

Chrome Plated Satin Chrome

Fire Bolts & Cover Turns




Fire Escape Redlam Bolt

UNION 8066 8066-TUBE-ONLY

Finish

Red






Covered Emergency Exit Turnknob

UNION 8070AS Spindle 8mm . Complete Kit

Finish

Black Plastic (rose) Clear Plastic (dome)





Covered Emergency Exit

UNION 8071 For Oval/Euro profile Cylinders

Finish

Black Plastic (rose) . Clear Plastic (dome)





Emergency Exit Replacement Cover Only UNION


8070-1PX

Finish

Clear Plastic

Hinges





Sinkless Aluminium Hinge


UNION 8352-100 100x73x3mm 8352-200 200x72x3mm

Finish

Satin Nickel White Black Bronze

Hinges






Stainless Steel Ball Bearing Sinkless Hinge UNION 8352-100FLSS Grade 304 stainless steel 100x75x3mm Finish

Stainless Steel






Satin Brass Ball Bearing Butt Hinge UNION 8352-100SB 100x75x3mm **Finish**

Satin Brass






Powerload Bronze Bushed Washer Hinge UNION 8352-100SS/2 Grade 304 stainless steel 100x88x3mm **Finish**

Stainless Steel






Aluminium Butt Hinge

UNION AL8352-100AS 100x75x3.5mm **Finish**

Anodised Silver






Ball Bearing Butt Hinge

UNION JH-BB-STD-2-SS Grade 304 Stainless Steel 8352-100SS201 Grade 201 Stainless Steel Finish

Hinges






Falling Butt Hinge

tt Hinge

UNION X-SS194FSL-3-SS (Right hand door) X-SS194FSR-3-SS (Left hand door) Grade 304 stainless steel Door will rest in open position Stainless Steel

Finish






Rising Butt Hinge

Finish

UNION Stainless Steel
X-SS194RSL-3-SS (Right hand
door)
X-SS194RSR-3-SS (left hand door)
Grade 304 stainless steel
Door will rest in closed position






Ball Bearing Security Butt Hinge

Finish

UNION 8352-100SS/2SP Grade 304 stainless steel with 2 security pins 100x75x3mm Stainless Steel

Flush Bolts






Automatic Flush Bolt

Finish

UNION 0149 Stainless Steel





Flush Bolt


UNION 8052-150PL 8052-150SC 8052-200PL 8052-200SC

Finish

Satin Chrome Polished Brass

Flush Bolts






Flush Bolt

UNION AL8208-150AS AL8208-225AS AL8208-300AS AL8208-450AS AL8208-600AS



Anodised Silver





Flush Bolt for Metal Doors

UNION AL8208-180AS/MD **Finish**

Anodised Silver



Flush Bolt Extension Kits


UNION AL-EXT-300AS AL-EXT-600AS AL-EXT-900AS for AL8208-180AS/MD

Finish

Anodised Silver

Dust Proof Strikes






Dust Proof Strike

UNION 8852SC

Finish

Satin Chrome Polished Brass





Dust Proof Strike


UNION YCS80 for use with the 0149 Automatic Flush Bolt

Finish

Satin Chrome

Door Viewers





Door Viewer


UNION 99200CH 99200PL 200° view

Finish

Chrome Polished Brass

Roller Catch





Adjustable Roller Catch

UNION ARC1182SS

Finish

Stainless Steel

Push PlatesAluminium Push Plates






Push Plates

UNION 76x152mm AL5063-06AS Blank AL5063-05AS Euro AL5063-13AS Oval AL5063-24AS Keyhole

Finish

Anodised Silver






Push Plates

UNION 152x152mm AL5066-06AS Blank AL5066L/R-05AS Euro AL5066L/R-13AS Oval AL5066L/R-24AS Keyhole

Finish

Anodised Silver





Push Plates

UNION 178x152mm AL5067-06AS Blank AL5067L/R-05AS Euro AL5067L/R-13AS Oval AL5067L/R-24AS Keyhole

Finish

Anodised Silver






Push Plates

UNION 76x152mm SS5063-06SS Blank SS5063-05SS Euro SS5063-13SS Oval SS5063-24SS Keyhole

Finish

Stainless Steel






Push Plates


UNION 152x152mm SS5066-06 Blank SS5066-L/R-05 Euro SS5066-L/R-13 Oval SS5066-L/R-24 Keyhole

Finish

Stainless Steel








Push Plates

UNION 178x152mm SS5067-06 Blank SS5067-L/R-05 Euro SS5067-L/R-13 Oval SS5067-L/R-24 Keyhole

Finish

Stainless Steel







Push Plate

UNION 76x228mm Plate SS76X228-06 Blank

Finish

Stainless Steel





Push Plate

UNION 78x228mm Plate SS5023-06-228W Blank SS5023L/R-05-228W Euro SS5023L/R-13-228W Oval SS5023L/R-24-228W Keyhole

Ordered as left or right

Finish

Push Plates

Stainless Steel Push Plates





Push Plate

UNION 76x304mm Plate SS76X304-06SS Blank

Finish

Stainless Steel





Push Plate

UNION 304x152mm Plate SS5023-06-304W Blank SS5023-L/R-05-304W Euro SS5023-L/R-13-304W Oval SS5023-L/R-24-304W Keyhole

Ordered as left or right

Finish

Stainless Steel

Signage / Engraved Plates

Engraved Plates





Signage & Engraved Plates

UNION 152x152mm Plate AL5066-06AS 3mm aluminium full infill engraved plates SS5066-06SSS 1.6mm 304 stainless steel full infill engraved plates SS5066-06SSE 1.6mm 430 stainless steel outline

Finish

Stainless Steel Anodised Silver

New Signage






Signage & Engraved Plates

engraved plates

UNION 152mm X 152mm SS5066-06SSSE24 AL5066-06ASE24 SS5066-06SSSE25 AL5066-06ASE25 SS5066-06ASE26 AL5066-06ASE26 Stainless Steel models: 2mm plate thickness Stainless steel grade 304 Aluminium models: 3mm plate thickness

Finish

Stainless Steel Anodised Silver










Narrow Stile Escutcheon

UNION AL582RT-05 Euro AL584RT-24 Keyhole

Finish

Anodised Silver





Escutcheons


UNION
AL584-05AS Euro
AL584-13AS Oval
AL584-24AS Keyhole



Anodised Silver








Brass Escutcheons

Brass Escutcheons







Escutcheons

UNION PB5375-05 Euro PB5375-13 Oval PB5375-24 Key




Polished Brass

Brass Escutcheons

Brass Escutcheons





Escutcheon Bathroom

UNION PB5375-73


Finish

Polished Brass

Stainless Steel Escutcheons

Stainless Steel Round & Narrow Stile escutcheon






Narrow Stile Escutcheon

UNION PZ-05 Euro

Finish

Stainless Steel






Bathroom Escutcheon

UNION SS5004-73 W/C 8mm Spindle

Finish



Round Escutcheons

UNION SS5305-05SS Euro SS5305-13SS Oval SS5305-24SS Keyhole

Finish

Stainless Steel



UNION SS5305-73 W/C 8mm Spindle


Finish

Stainless Steel



Stainless Steel Kinglet Square Escutcheons





Square Escutcheon


UNION SS5306-05SS Euro SS5306-13SS Oval SS5306-24SS Keyhole

Finish

Kinglet Square Escutcheon Stainless Steel Kinglet Square Escutcheons







Bathroom Escutcheon

UNION SS5306-73 W/C

Finish

Stainless Steel

Aluminium Push Plates

Aluminium Push Plates




Part Number	Size
AL5023-228W	Push Plate 152X228X3mm AS
AL5023-304W	Push Plate 152X304X3mm AS
AL5023-380W	Push Plate 152X375X3mm AS
AL5023-456W	Push Plate 152X456X3mm AS
AL5023-532W	Push Plate 152X532X3mm AS
AL5023-608W	Push Plate 152X608X3mm AS
AL5023-684W	Push Plate 152X684X3mm AS
AL5023-760W	Push Plate 152X760X3mm AS
AL5023-836W	Push Plate 152X836X3mm AS
AL5023-912W	Push Plate 152X912X3mm AS
AL5023-988W	Push Plate 152X988X3mm AS

Stainless Steel Push Plate

Stainless Steel Push Plates



Part Number	Size
SS5023-228W	Push Plate 152X228X1.2mm SS
SS5023-304W	Push Plate 152X304X1.2mm SS
SS5023-380W	Push Plate 152X380X1.2mm SS
SS5023-456W	Push Plate 152X456X1.2mm SS
SS5023-532W	Push Plate 152X532X1.2mm SS
SS5023-608W	Push Plate 152X608X1.2mm SS
SS5023-760W	Push Plate 152X760X1.2mm SS
SS5023-836W	Push Plate 152X836X1.2mm SS
SS5023-912W	Push Plate 152X912X1.2mm SS
SS5023-988W	Push Plate 152X988X1.2mm SS



Stainless Steel Kick Plates

Stainless Steel Kick Plates

Part Number	Size
SS5089-150W	Kick Plate 150X800X1.2mm SS
SS5089-200W	Kick Plate 200X800X1.2mm SS
SS5089-250W	Kick Plate 250X800X1.2mm SS
SS5089-300W	Kick Plate 300X800X1.2mm SS
SS5089-350W	Kick Plate 350X800X1.2mm SS
SS5089-400W	Kick Plate 400X800X1.2mm SS
SS5089-450W	Kick Plate 450X800X1.2mm SS
SS5089-500W	Kick Plate 500X800X1.2mm SS
SS5089-550W	Kick Plate 550X800X1.2mm SS
SS5089-600W	Kick Plate 600X800X1.2mm SS
SS5089-650W	Kick Plate 650X800X1.2mm SS
SS5089-700W	Kick Plate 700X800X1.2mm SS
SS5089-750W	Kick Plate 750X800X1.2mm SS
SS5089-800W	Kick Plate 800X800X1.2mm SS
SS5089-850W	Kick Plate 850X800X1.2mm SS
SS5089-900W	Kick Plate 900X800X1.2mm SS
SS5089-950W	Kick Plate 950X800X1.2mm SS


Cylinders



Mul-T-Lock Patented Cylinders

Interactive Patented Cylinders





Double Cylinder Euro Profile

Available in

M2X18AIPL - Brass
M2X18AISC - Satin Chrome
High security cylinder with 10 pins
Supplied with 2 flat keys and security card
Anti-drill
Anti-bump
Anti-pick
5 Year Warranty
Cylinder length: 66mm

KA, MKD, GMK





Thumb Turn Cylinder Euro Profile Available in


M2X19AIPL - Brass
M2X19AISC - Satin Chrome
High security cylinder with 10 pins
Supplied with 2 flat keys and security card
Anti-drill
Anti-bump
Anti-pick
5 Year Warranty
Cylinder length: 66mm

KA, MKD, GMK









Single Cylinder Euro Profile

Available in

M2X20AIPL - Brass
M2X20AISC - Satin Chrome
High security cylinder with 10 pins
Supplied with 2 flat keys and security card
Anti-drill
Anti-bump
Anti-pick
5 Year Warranty


Cylinder length: 42.5mm

 $\mathsf{KA}, \mathsf{MKD}, \mathsf{GMK}$

Mul-T-Lock Patented Cylinders

Interactive Patented Cylinders







M2X6AIPL - Brass
M2X6AISC - Satin Chrome
High security cylinder with 10 pins
Supplied with 2 flat keys and security card
Anti-drill
Anti-bump
Anti-pick
5 Year Warranty
Cylinder length: 66mm

Double Cylinder Oval Profile






Thumb Turn Cylinder Oval Profile

M2X13AIPL - Brass
M2X13AISC - Satin Chrome
High security cylinder with 10 pins
Supplied with 2 flat keys and security card
Anti-drill
Anti-bump
Anti-pick
5 Year Warranty
Cylinder length: 66mm






Single Cylinder Oval Profile

M2X8AIPL - Brass
M2X8AISC - Satin Chrome
High security cylinder with 10 pins
Supplied with 2 flat keys and security card
Anti-drill
Anti-bump
Anti-pick
5 Year Warranty
Cylinder length: 42.5mm







Double Cylinder Euro Profile

ASSA ABLOY CY110KDED3333SN Medium security cylinder with 6 Supplied with 2 flat keys and a security card 240 hour corrosion resistance Anti-drill Anti-pick Anti-pull 10 Year warranty

Thumb Turn Double Cylinder


Medium security cylinder with 6


Supplied with 2 flat keys and a

Finish Satin Nickel Available as KA, MKD, GMK









240 hour corrosion resistance Anti-drill Anti-pick Anti-pull 10 Year warranty

Euro Profile

ASSA ABLOY

security card

pins


CY110ET3333SN

Finish Satin Nickel Available as KA, MKD, GMK









Single Cylinder Euro Profile


ASSA ABLOY CY110KDES3310SN Medium security cylinder with 6 pins Supplied with 2 flat keys and a security card 240 hour corrosion resistance Anti-drill Anti-pick Anti-pull 10 Year warranty

Finish Satin Nickel Available as KA, MKD, GMK

Mul-T-Lock Non-Patented Cylinders

Classic Cylinders






Double Cylinder Euro Profile

M2X18APL - Brass M2X18ASC - Satin Chrome Medium Security cylinder with 10 Supplied with 2 keys and security card Anti-pick Anti-drill 5 Year warranty Cylinder length: 66mm










Thumb Turn Double Cylinder Euro Profile

M2X19APL - Brass M2X19ASC - Satin Chrome Medium Security cylinder with 10 pins Supplied with 2 keys and security card Anti-pick Anti-drill 5 Year warranty Cylinder length: 66mm







Single Cylinder Euro Profile

M2X20APL - Brass M2X20ASC - Satin Chrome Medium Security cylinder with 10 pins Supplied with 2 keys and security card Anti-pick Anti-drill 5 Year warranty Cylinder length: 42.5mm


Mul-T-Lock Non-Patented Cylinders

Classic Cylinders










Double Cylinder Oval Profile

M2X6APL - Brass M2X6ASC - Satin Chrome Medium Security cylinder with 10 Supplied with 2 keys and security card Anti-pick Anti-drill 5 Year warranty Cylinder length: 66mm




Thumb Turn Cylinder Oval Profile

M2X13APL - Brass M2X13ASC - Satin Chrome Medium Security cylinder with 10 pins Supplied with 2 keys and security card Anti-pick Anti-drill 5 Year warranty Cylinder length: 42,5mm








Single Cylinder Oval Profile

M2X8APL - Brass M2X8ASC - Satin Chrome Medium Security cylinder with 10 Supplied with 2 keys and security card Anti-pick Anti-drill 5 Year warranty Cylinder length: 42.5mm

Mul-T-Lock Non-Patented Cylinders

7x7 Cylinders





Double Cylinder Euro Profile

M72X18PL - Brass M72X18SC - Satin Chrome Basic security cylinder with 7 pins Supplied with 2 reversible keys and secuirty card 5 Year warranty Cylinder length: 62mm






Knob Cylinder Euro Profile

M72X19PL - Brass M72X19SC - Satin Chrome Basic security cylinder with 7 pins Supplied with 2 reversible keys and secuirty card 5 Year warranty Cylinder length: 62mm






Single Cylinder Euro Profile

M72X20PL - Brass M72X20SC - Satin Chrome Basic security cylinder with 7 pins Supplied with 2 reversible keys and secuirty card 5 Year warranty Cylinder length: 42.5mm










Rim Cylinder

UNION 1X1SC 1x1PL 5 year warranty

Finish

Satin Chrome Brass





Double Cylinder Euro Profile

UNION
2X18SC
2X18PL
5 pin cylinder
Supplied with sawn key
5 year warranty
Cylinder length: 66mm
Available as KD, KA, MKD and GMK

Finish

Satin Chrome Brass



Thumb Turn Double Cylinder Euro Profile

UNION 2X19SC 2X19PL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 66mm Available as KD, KA, MKD and GMK **Finish**

Satin Chrome Brass




Single Cylinder Euro Profile

UNION
2X20SC
2X20PL
5 pin cylinder
Supplied with sawn key
5 year warranty
Cylinder length: 42.5mm
Available as KD, KA, MKD and GMK

Finish

Satin Chrome Brass



Thumb Turn Single Cylinder Euro Profile

UNION 2X815/HNP 2X815/HPL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 32mm

Finish

Satin Chrome Brass



Double Privacy Cylinder Euro Profile


Double Cylinder Oval Profile

UNION 2X815/TNP 2X815/TPL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 66mm

Finish

Satin Chrome Brass





UNION 2X6SC 2X6PL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 66mm Satin Chrome

Finish

Brass






Thumb Turn Double Cylinder Oval Profile

UNION 2X13SC 2X13PL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 66mm Finish

Satin Chrome Brass






Single Cylinder Oval Profile

UNION 2X8SC 2X8PL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 32mm **Finish**

Satin Chrome Brass





Oval Profile Privacy Cylinder

UNION 2X13/TSC 2X13/TPL 5 pin cylinder Supplied with sawn key 5 year warranty Cylinder length: 66mm Finish

Satin Chrome Brass




Rack & Pinion Door Closers










DC120

ASSA ABLOY DC120 EN 2/3/4

Technical Attributes

Rack and pinion door closer with link arm Certified in compliance with EN 1154, size 2/3/4 For single action doors up to 1100mm wide Can be used on left and right-handed doors Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Closing force configurable Opening angle up to 180° (104° on EN4 mounting position)






DC135

ASSA ABLOY DC135 EN 3

Technical Attributes

Rack and pinion door closer with guide rail Certified in compliance with EN 1154, size 3 For single action doors up to 950mm wide Can be used on left and right-handed doors Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Closing force configurable Opening angle up to 180°



Please consult fire certificates for additional information on fire-rating

Rack & Pinion Door Closers



DC140


ASSA ABLOY DC140 EN 2/3/4/5


Technical Attributes


Rack and pinion door closer with link arm Certified in compliance with EN 1154, size 2/3/4/5 For single action doors up to 1100mm wide Can be used on left and right-handed doors Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Closing force configurable Opening angle up to 180°













DC200


ASSA ABLOY DC200 DC200HO (hold-open) EN 2-4




Rack and pinion door closer with link arm
Certified in compliance with EN 1154, size 2-4
For single action doors up to 1100mm wide
Can be used on left and right-handed doors
Suitable for fire and smoke protection doors
Adjustable closing speed, latching speed and backcheck
Variable adjustable closing force
Opening angle up to 180°
Hold-open variant available
Hold-open angle between 75° - 150°









Please consult fire certificates for additional information on fire-rating

Rack & Pinion Door Closers




DC300

ASSA ABLOY DC300 DC300DA (delayed action) DC300HO (hold-open) EN 3-6

Technical Attributes

Rack and pinion door closer with link arm
Certified in compliance with EN 1154, size 3-6
For single action doors up to 1400mm wide
Can be used on left and right-handed doors
Suitable for fire and smoke protection doors
Adjustable closing speed, latching speed and backcheck
Variable adjustable closing force
Opening angle up to 180°
Hold-open variant available
Hold-open angle between 75° - 150°
Delayed action variant available with adjustable delayed closing






DC300TANDEM

ASSA ABLOY DC300TANDEM EN > 7

Technical Attributes

Rack and pinion door closer with link arm Two door closers interlinked for extra wide and heavy doors Double closing torque of DC300, EN size > 7 For single action doors up to 1800mm wide Can be used on left and right-handed doors Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Variable adjustable closing force Opening angle up to 180°



Please consult fire certificates for additional information on fire-rating

Cam-Motion® Door Closers




DC500

ASSA ABLOY DC500 DC500HO (hold-open) EN 1-4

Technical Attributes

Door closer with Cam-Motion® technology
Certified in compliance with EN 1154, size 1-4
For single action doors up to 1100mm wide
Fulfils barrier-free building requirements (EA / CEN TR 15894)
Can be used for left and right-handed doors
Suitable for fire and smoke protection doors
Adjustable closing speed, latching speed and backcheck
Variable adjustable closing force
Opening angle up to 170° (non-hinge side 120°)
Hold-open variant available
Hold-open angle 130°







DC700

ASSA ABLOY DC700 DC700HO DC700DA EN 3-6




Door closer with Cam-Motion® technology
Certified in compliance with EN 1154, size 3-6
For single action doors up to 1400mm wide
Fulfils barrier-free building requirements (EA / CEN TR 15894)
Can be used for left and right-handed doors
Suitable for fire and smoke protection doors
Adjustable closing speed, latching speed and backcheck
Variable adjustable closing force
Opening angle up to 170° (non-hinge side 120°)
Hold-open variable available
Hold-open angle 130°
Delayed action variant available
Delayed closing variable from max. opening angle to 70°









Cam-Motion® Door Closers



DC700G-FM

ASSA ABLOY DC700G-FM EN 3-6

Technical Attributes

Free-Motion® door closer with free-swing function starting from a door opening angle 0°

Certified in compliance with EN 1155/1154, size 3-6 Easy, initial door opening due to the rapidly decreasing opening force. When active, the free-swing function enables permanent opening of the door without the resistance of the door closer


Door remains in free-swing mode until power supply is switched-off

For single action doors up to 1400mm wide
Fulfils barrier-free building requirements (EA / CEN TR 15894)
Can be used for left and right-handed doors

Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Variable adjustable closing force

Opening angle up to 160

Hold-open variant available Hold-open angle 130°



DC700G-CM

ASSA ABLOY DC700G-CM EN 3-6


Technical Attributes

Cam-Motion® door closer with integrated Close-Motion® element for safe and noiseless closing
The door can be pulled closed safely and quietly from an angle of

Certified in compliance with EN 1154, size 3-6 For single action doors up to 1400mm wide Can be used for left and right-handed doors Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Variable adjustable closing force Opening angle up to 170°







Electromechanical Door Closers



FD460-DC500

ASSA ABLOY FD460-DC500 EN 1-4


Technical Attributes

Door closer with Cam-Motion® technology and guide rail with electromechanical hold open device Certified in compliance with EN 1155, size 1-4 For single leaf doors up to 1100mm wide Can be used for left and right-handed doors Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Variable adjustable closing force Opening angle up to 130° Hold open angle between 70°-130°














ASSA ABLOY FD461-DC500 EN 1-4











Technical Attributes

Door closer with Cam-Motion® technology and guide rail with integrated mechanical coordinator Certified in compliance with EN 1158, size 1-4 For double leaf doors 1250 - 2800mm wide Correct closing sequence guaranteed for double leaf doors, inactive leaf closes before active leaf starts to close Active leaf able to stay open in any selected angle up to 150° when inactive leaf is open Suitable for fire and smoke protection doors Adjustable closing speed, latching speed and backcheck Variable adjustable closing force Opening angle of active leaf (hinge side / non-hinge side) 150° / 120° Opening angle of inactive leaf (hinge side / non-hinge side) 170° / 120°



Electromechanical Door Closers



FD462-DC500

ASSA ABLOY FD462-DC500 FN 1-4

Technical Attributes


Door closer with Cam-Motion® technology and guide rail with integrated mechanical coordinator and two electromechanical hold open devices

Certified in compliance with EN 1158 and EN 1155, size 1-4 For double leaf doors 1250 - 2800mm wide

Correct closing sequence guaranteed for double leaf doors, inactive leaf closes before active leaf starts to close Suitable for fire and smoke protection doors

Adjustable closing speed, latching speed and backcheck Variable adjustable closing force
Opening angle of active leaf (hinge side / non-hinge side) 120°
Hold open angle of inactive leaf (hinge side / non-hinge side) between 70° - 120°

Possible to keep active leaf or both door leaves open electromechanically













FD464-DC500

ASSA ABLOY FD464-DC500 EN 1-4



Door closer with Cam-Motion® technology and guide rail with integrated mechanical coordinator and one electromechanical hold open device

Certified in compliance with EN 1158 and EN 1155, size 1-4 For double leaf doors 1250 - 2800mm wide

Correct closing sequence guaranteed for double leaf doors, inactive leaf closes before active leaf starts to close


Suitable for fire and smoke protection doors

Adjustable closing speed, latching speed and backcheck Variable adjustable closing force
Opening angle of active leaf (hinge side / non-hinge side)


Hold open angle of inactive leaf (hinge side / non-hinge side) 70° - 130° / 70° - 120°











Electromechanical Door Closers





FD460-DC700 EN 3-6


Technical Attributes

Door closer with Cam-Motion® technology and guide rail with electromechanical hold open device
Certified in compliance with EN 1155, size 3-6
For single leaf doors up to 1400mm wide
Can be used for left and right-handed doors
Suitable for fire and smoke protection doors
Adjustable closing speed, latching speed and backcheck
Variable adjustable closing force
Opening angle up to 130°
Hold open angle between 70°-130°











FD461-DC700

ASSA ABLOY FD461-DC700 EN 3-6







Technical Attributes

Door closer with Cam-Motion® technology and guide rail with integrated mechanical coordinator
Certified in compliance with EN 1158, size 3-6
For double leaf doors 1250 - 2800mm wide
Correct closing sequence guaranteed for double leaf doors, inactive leaf closes before active leaf starts to close
Active leaf able to stay open in any selected angle up to 150° when inactive leaf is open
Suitable for fire and smoke protection doors
Adjustable closing speed, latching speed and backcheck
Variable adjustable closing force
Opening angle of active leaf (hinge side / non-hinge side)
150° / 120°
Opening angle of inactive leaf (hinge side / non-hinge side)



Electromechanical Door Closers



FD462-DC700

ASSA ABLOY FD462-DC700 EN 3-6

Technical Attributes

Door closer with Cam-Motion® technology and guide rail with integrated mechanical coordinator and two electromechanical hold open devices

Certified in compliance with EN 1158 and EN 1155, size 3-6 For double leaf doors 1250 - 2800mm wide

Correct closing sequence guaranteed for double leaf doors, inactive leaf closes before active leaf starts to close Suitable for fire and smoke protection doors

Adjustable closing speed, latching speed and backcheck Variable adjustable closing force

Opening angle of active leaf (hinge side / non-hinge side) 120° Hold open angle of inactive leaf (hinge side / non-hinge side)

between 70° - 120° Possible to keep active leaf or both door leaves open

electromechanically













FD464-DC700

ASSA ABLOY FD464-DC700 EN 3-6



Door closer with Cam-Motion® technology and guide rail with integrated mechanical coordinator and one electromechanical hold open device

Certified in compliance with EN 1158 and EN 1155, size 3-6 For double leaf doors 1250 - 2800mm wide

Correct closing sequence guaranteed for double leaf doors, inactive leaf closes before active leaf starts to close Suitable for fire and smoke protection doors

Adjustable closing speed, latching speed and backcheck Variable adjustable closing force

Opening angle of active leaf (hinge side / non-hinge side)

150° | 120° Hold open angle of inactive leaf (hinge side | non-hinge side)

70° - 130° / 7ŏ° - 120°











Concealed Cam-Motion® Door Closers



DC840

ASSA ABLOY DC840 DC850HO (hold-open) EN 1-4

Technical Attributes

Concealed door closer with Cam-Motion® technology and concealed guide rail

Fulfils barrier-free building requirements (EA / EN TR 15894) Certified in compliance with EN 1154, size 1-4


Suitable for fire and smoke protection doors

For single doors up to 1100mm wide Can be used for left and right-handed doors

Closing speed and latching speed adjustable

Built-in backcheck

Opening angle up to 120°





DC860

ASSA ABLOY DC860

DC860 (hold-open)

EN 1-5



Concealed door closer with Cam-Motion® technology and concealed guide rail Fulfils barrier-free building requirements (EA / EN TR 15894)

Certified in compliance with EN 1154, size 1-4


Suitable for fire and smoke protection doors For single doors up to 1250mm wide Can be used for left and right-handed doors

Closing speed and latching speed adjustable

Built-in backcheck

Opening angle up to 120°

To be used on doors with a minimum thickness of 54mm



Gate Closers




DC680G


ASSA ABLOY DC680G

Technical Attributes

Suitable for non-paneled garden and pedestrian gates Adjustable size

For single action gate leaf from 600mm up to 1400mm
Gate closer manufactured from heavy duty cast iron
Independent closing and latch speeds controlled by thermostatic
valves ensuring stable closing times at different temperatures
Soft opening and strong closing





Door Closers

Floor Springs



DC420

ASSA ABLOY

DC420


DC420HO (90° hold-open)

DC420DA (double action)

DC420DAHO (double action with 90° hold-open)

EN 2/3/4







Suitable for fire and smoke protection doors

For double and single doors up to 100kg and 1100mm wide Hydraulic control over 175° in both swing directions Adjustable door speed and latching speed from top regulating

Available with hold-opening angle 90°



Please consult fire certificates for additional information on fire-rating



Floor Springs









DC477

ASSA ABLOY DC477 DC477HO (90° hold-open) DC477DA (double action)


DC477DAHO (double action action with 90° hold-open) EN 2-4

Technical Attributes

Floor spring with adjustable closing force for large and heavy doors Certified in accordance with EN 1154, size 2-4, cycle test over 1,000,000 cycles

Suitable for fire and smoke protection doors
For double and single doors up to 170kg and 1100mm wide
Hydraulic control over 175° in both swing directions
Adjustable door speed and latching speed from top regulating

Available with hold-opening angle 90°





DC475

ASSA ABLOY DC475 DC475HO (90° hold-open) DC475DA (double action) DC475DAHO (double action with 90° hold-open) EN 3-6


Technical Attributes


Floor spring with adjustable closing force for large and very heavy doors

Certified in accordance with EN 1154, size 3-6, cycle test over 1,000,000 cycles

Suitable for fire and smoke protection doors
For double and single doors up to 300kg and 1400mm wide
Hydraulic control over 175° in both swing directions
Adjustable door speed and latching speed from top regulating
valves

Available with hold-opening angle 90°





Please consult fire certificates for additional information on fire-rating

Transom Closers




773/774

UNION 773 774 EN 3

Technical Attributes


Transom concealed door closer Transom concealed door closer
Fixed EN size 3
Fittings for timber and aluminium doors frames
Metal cover plate (773Tl) for timber application to be ordered
separately
For glass doors consult your ASSA ABLOY representative for full
specification required
Selectable speed control with speed control valve
Non-hold open or 90° hold-open options available
Maximum opening angle 120° in both directions
(use of floor mounted door stops recommended)



Panic Escape Devices







ExiSAFE Single Door Panic Hardware

UNION J-CE853PL-SIL (timber doors) J-CE853PM-SIL (metal doors)

Technical Attributes

Single point lateral locking
Suitable for timber (120min) and metal fire doors (240min)
Manufactured in Britain
10 Year Guarantee
200,000 cycle durability
Max. door width 1230mm
Optional Outside Access Device:
J-CE855OADK-SIL
J-CE855OADL-SIL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A





ExiSAFE Single Door Panic Hardware

UNION J-CE851PB-SIL (timber doors) J-CE851PBM-SIL (metal doors)

Technical Attributes

Two-point top and bottom latching
Suitable for timber (120min) and metal fire doors (240min)
Suitable for non-rebated double doors (will require 2 units)
Manufactured in Britain
10 Year Guarantee
200,000 cycle durability
Max. door width 1230mm
Max. door height 2440mm
Optional Outside Access Device:
-J-CE855OADL-SIL
J-CE855OADK-SIL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A



Escape Hardware

ExiSAFE



ExiSAFE Double Door Panic Hardware

UNION

J-CE852DDREB-SIL (timber doors)
J-CE852DREBM-SIL (metal doors)

Technical Attributes

Three point locking top, bottom and lateral
Suitable for timber (120min) and metal fire doors (240min)
Suitable for rebated double doors
Manufactured in Britain
10 Year Guarantee
200,000 cycle durability
Max. door width 1230mm
Max. door height 2440mm
Optional Outside Access Device:
-J-CE855OADL-SIL
J-CE855OADK-SIL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A





UNION

J-CE854EL-SIL (timber doors) J-CE854ELM-SIL (metal doors)


Technical Attributes

Single point panic latch
Suitable for timber (120min) and metal fire doors (240min)
Suitable for internal escape route doors
Manufactured in Britain
10 Year Guarantee
200,000 cycle durability
Max. door width 1230mm
Max. door height 2440mm
Optional Outside Access Device:
-J-CE855OADL-SIL
J-CE855OADK-SIL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 4 | 2 | B | B







ExiSAFE Outside Access Device (Knob)

UNION J-CE855OADK-SIL

Technical Attributes

Suitable for timber (120min) and metal fire doors (240min)
Knob outside access device for fire exit door which need to be
accessed from the outside
Manufactured in Britain
10 Year Guarantee
Max door width 45mm
Can only be used with a rear screw retaining half cylinder
Excludes cylinder

BS EN 1125 BS EN 179





ExiSAFE Outside Access Device (Lever)

UNION J-CE855OADL-SIL

Technical Attributes

Suitable for timber (120min) and metal fire doors (240min) Lever outside access device for fire exit door which need to be accessed from the outside Manufactured in Britain 10 Year Guarantee Max door width 60mm Can only be used with Master Keyed Systems

BS EN 1125 BS EN 179







UNION J-881-SIL (900mm) J-881-W-SIL (1200mm)

Technical Attributes

Single point lateral locking touch bar Max. door width 900mm/1200mm Max. door height 2350mm Anti-thrust steel deadlatch Optional outside access device: J-885-SIL



BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A


|-Series Single Door Panic Hardware




UNION J-881TD-SIL (900mm) J-881TD-W-SIL (1200mm)

Technical Attributes

Single point lateral locking touch bar Low projection touch bar Max. door width 900mm/1200mm Max. door height 2350mm Anti-thrust steel deadlatch Integrated dogging device Optional outside access device: J-885-SIL



BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | B | A




J-Series Single Door Panic Hardware

UNION J-882-SIL (900mm) J-882-W-SIL (1200mm)

Technical Attributes

Suitable for non-rebated double doors (will require 2 units) 3 point locking
Max. door width 900mm/1200mm
Max. door height 2350mm
Anti-thrust steel deadlatch
Optional outside access device:
J-885-SIL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A



J-Series Single Door Panic Hardware

UNION J-882TD-SIL (900mm) J-882TD-W-SIL (1200mm)

Technical Attributes

Suitable for non-rebated double doors (will require 2 units) 3 point locking
Low projection touch bar
Max. door width 900mm/1200mm
Max. door height 2350mm
Anti-thrust steel deadlatch
Optional outside access device:
I-885-SIL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | B | A




J-Series Double Door Panic Hardware


UNION J-883-SIL (900mm) J-883-W-SIL (1200mm)

Technical Attributes

Suitable for rebated double doors 3 point locking Max. door width 900mm/1200mm Max. door height 2350mm Anti-thrust steel deadlatch Optional outside access device: I-885-SIL



BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A




J-Series Double Door Panic Hardware


UNION J-883TD-SIL (900mm) J-883-TD-W-SIL (1200mm)

Technical Attributes

Suitable for rebated double doors 3 point locking Low projection touch bar Max. door width 900mm/1200mm Max. door height 2350mm Anti-thrust steel deadlatch Optional outside access device: I-885-SIL



BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | B | A



J-Series Outside Access Handle

UNION J-885-SIL

Technical Attributes


Excludes cylinder

Suitable for timber and metal doors Lever outside access device for fire exit door which need to be accessed from the outside Clutch Release Protection System (CRPS) to protect against abuse

BS EN 1634-1

TESA Exit Devices





TESA Single Door Panic Hardware

TESA 1910908NV

Technical Attributes

Single lateral locking push latch Steel swing latch Max. door width 900mm Max. Door height 2210mm Optional outside access device: MMPS2SCPL MMPP2T5PL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A




TESA Single Door Panic Hardware

TESA 1930908NV

Technical Attributes

Suitable for non-rebated double doors (2 units required) 2 locking points
Max. Door width 900mm
Max. Door height 2210mm
Optional outside access device:
MMPS2SCPL
MMPP2T5PL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A




TESA Double Door Panic Hardware

TESA 1940908NV

Technical Attributes

Suitable for rebated double doors 3 Locking Points Max. door width 900mm Max. door height 2210mm Optional outside access device: MMPS2SCPL MMPP2T5PL

BS EN 1125 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A



TESA Single Door Panic Hardware

TESA TP91008NV

Technical Attributes

Emergency exit device used when little risk of panic situation Suitable for timber and metal doors Optional outside access device: MMPS2SCPL MMPP2T5PL

BS EN 179 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | B | A



TESA Outside Access Devices

TESA MMPP2T5PL (Swing Knob)

Technical Attributes

Suitable for timber and metal doors Knob outside access device for fire exit door which need to be accessed from the outside Excludes cylinder

BS EN 1634-1

Escape Hardware TESA Exit Devices




TESA Outside Access Devices

TESA MMPS2SCPL

Technical Attributes

Suitable for timber and metal doors Lever outside access device for fire exit door which need to be accessed from the outside Excludes cylinder




BS EN 1634-1

Sliding & Folding Door Gear



Sliding Door Gear

Husky 100




Kit	Door Width
27-664060	Husky 100 Kit (H100/15A) - Alu. Track - Max 800mm
27-664061	Husky 100 Kit (H100/18A) - Alu. Track - Max 950mm
27-664062	Husky 100 Kit (H100/20A) - Alu. Track - Max 1050mm
27-664063	Husky 100 Kit (H100/24A) - Alu Track - Max 1250mm
27-665537	Husky 100 Kit (H100/15) - Steel Track - Max 800mm
27-665538	Husky 100 Kit (H100/18) - Steel Track - Max 950mm
27-665539	Husky 100 Kit (H100/20) - Steel Track - Max 1050mm
27-665540	Husky 100 Kit (H100/24) - Steel Track - Max 1250mm
27-669174	Husky 100Kg Soft Stop Kit (Wood Door)
27-664902	F140 FASCIA PACK 2000mm (F140/20) - Incl. Endcaps
27-664903	F140 FASCIA PACK 3000mm (F140/30) - Incl. Endcaps
27-669235	SLIDOCLOSE - Pneumatic Closing System (SC100)

For heavy weight room dividers
For timber, timber framed or composite doors
Not suitable for doors less than 25kg
Easily adjustable door height
End clip stop to hold door in open position
Floor component - Nylon
Guide with channel available as non-standard option
Simultaneous action option
Low headroom function also available

Specificiation:

Maximum door weight: 100kg Minimum door weight: 25kg Maximum door width: 1250mm Maximum door height: 2700mm Door thickness: 20-50mm

Marathon 90



Kit	Door Width
27-789407	Marathon Kit S2 - Opening 400-750mm
27-789558	Marathon Kit S3 - Opening 750-900mm
27-789589	Marathon Kit S4- Opening 900-1050mm
27-789613	Marathon Kit S5 - Opening 1050-1200mm
27-790822	Marathon Kit S6 - Opening 1200-1500mm
27-790853	Marathon Kit S7 - Opening 1500-1800mm
27-790884	Marathon Kit S8 - Opening 1800-2000mm
27-790918	Marathon Fire Door Kit - Fdk1
27-789527	

For heavy-duty and light commercial applications, doors and partitions

For timber, timber framed or composite doors

Easily adjusted door height


Fire door kit available (single doors only)

Self closing kit option for doors up to 60kg (SCK1)

Simultaneous action option

Specification:

Max. door weight: 90kg Max. door width: 1500mm Max door height: 3000mm Door thickness: 32-50mm



Kit	Door Width
27-789400	Marathon Kit 2 - Opening 400-750mm
27-789431	Marathon Kit J3 - Opening 750-900mm
27-789462	Marathon Kit J4 - Opening 900-1050mm
27-789493	Marathon Kit J5 - Opening 1050-1200mm
27-790695	Marathon Kit J6 - Opening 1200-1500mm

For heavy-duty and light commercial applications, doors and partitions


For timber, timber framed or composite doors Easily adjusted door height Self closing kit option for doors up to 60kg (SCK1)

Specification:

Max. door weight: 55kg Max. door width: 1500mm Max. door height: 3000mm Door thickness: 32-50mm

Simultaneous action option

Single Top for Single Track Wardrobe Doors



Kit	Door Width
27-790949 27-790963	Single Top Kit St12 - Max 600mm Single Top Kit St15 - Max 750mm
27-790987	Single Top Kit St18 - Max 900mm

For timber framed composite doors Silent Nylon wheeled ball bearing hangers and aluminium track


Easily adjusted door height Floor component gaide only

Specification:

Max. door weight: 45kg Max. door width: 900mm Max. door height: 2400mm Door thickness: 16-40mm

Sliding Door Gear

Husky 50 for Silent Wood Doors



Kit	Door Width
27-664068 27-664069 27-664070 27-664071 27-665553 27-665554 27-665555	Husky 50 Kit (H50/15A) - Alu. Track - Max 800mm Husky 50 Kit (H50/18A) - Alu. Track - Max 950mm Husky 50 Kit (H50/20A) - Alu. Track - Max 1050mm Husky 50 Kit (H50/15) - Steel Track - Max 800mm Husky 50 Kit (H50/18) - Steel Track - Max 1050mm Husky 50 Kit (H50/20) - Steel Track - Max 1050mm Husky 50 Kit (H50/24) - Steel Track - Max 1250mm
27-665556 27-669170 27-370250 27-664902 27-664903 27-669235	Husky 50kg Soft Stop Kit (Single Damper) Simultaneous Action Kit For Husky Sim100 F140 FASCIA PACK 2000mm (F140/20) - Incl. Endcaps to be used with aluminium tracks only F140 FASCIA PACK 3000mm (F140/30) - Incl. Endcaps to be used with aluminium tracks only SLIDOCLOSE - Pneumatic Closing System (SC100)

For timber, timber framed or composite doors For medium weight doors up to 50kg

Quiet operation - galvanised steel or aluminium track with nylon rollers


Floor component - guide only Simultaneous action option

Soft stop action in single or double kit option

Specification:

Maximum door weight: 50kg Maximum door width: 1250mm Maximum door height: 20-50mm

Double Top



Kit	Door Width	
27-792277	Double Top Kit W12 - 2 Leaves - Max 1200mm	
27-792291	Double Top Kit W15 - 2 Leaves - Max 1500mm	
27-792318	Double Top Kit W18 - 2 Leaves - Max 1800mm	
27-792332	Double Top Kit W24 - 3 Leaves - Max 2400mm	
27-792356	Double Top Kit W30 - 4 Leaves - Max 3000mmm	

For heavy duty applications - wardrobes, cupboards, in hotels, schools and offices

For timber, timber framed or composite doors

Silent - nylon wheeled bearing hangers and aluminium track Easily adjusted door height

Floor component - Nylon

Guide with channel available as a non standard option

Specification:

Maximum door weight: 45kg Maximum door width: 900mm Maximum door height: 2400mm

Door thickness: 16-40mm

SLIDOCLOSE



Kit	Door Width
27-669235	SLIDOCLOSE - Pneumatic Closing System (SC100)

Pneumatic door closer for doors up to 100kg
Easy to install
Can be retrofitted to existing sliding door applications
Comes complete with fascia

Available in a chrome finish No power source required Door speed adjustment settings Suitable for left or righ hand openings


Specification:

Power force start (kgf) 1.5 Power force extended (kgf) 4.1 Maximum door weight 100kg Maximum door width 1270mm

Based on a smooth rolling system with less than 1.0kg table moving force

BS EN1527

Phantom



Kit	Door Width
27-792961	Phantom Kit P9 - Opening 610 - 915mm


For room deviders - for residential, hospital and hotel use For timber, timber framed or composite doors Ultra silent, frictionless, easy operation Floor component - guide only Simultaneous action option

Specification:

Max. door weight: 45kg Max. door width: 610-915mm Max. door height:2400mm Door thickness: 30 - 50mm

Sliding Door Gear

Senator




Kit	Door Width
27-791065	Senator Kit San - Max 900mm

For entrance doors and doors between rooms For timber, timber framed or composite doors Silent - nylon guides and hangers on aluminium track Floor component - guide only

Specification:

Max. door weight: 30kg Max. door width: 900mm Max.door height: 2400mm Door thickness: 20-35mm

Slipper



Kit	Door Width
27-789730	Slipper Kit Ss4 - 2 Leaves - Max 1200mm
27-789761	Slipper Kit Ss5 - 2 Leaves - Max 1500mm
27-789792	Slipper Kit Ss6 - 2 Leaves - Max 1800mm


For fitted furniture of all kinds e.g. kitchen, bathrooms, serving hatches of lightweight wood or chipboard Quiet nylon slides on attractive aluminium track Easily top fixed

Simple to remove doors for cleaning

Specification:

Max. door weight: 9kg Max. door width: 900mm Max. door height: 1800mm Door thickness: 16-30mm

Husky 40



Kit	Door Width
27-665565 27-665566	Husky 40 Folding Kit (Hf40/15) - Leaves - Max 1500mm Husky 40 Folding Kit (Hf40/30) - 4 Leaves* - Max 3000mm


For timber, timber framed or composite doors For light residential folding partitions Neatly stacking at one or both sides Concealed fixing Floor component - pivot only

Specification:

Max. door weight: 40kg Max. door width: 750mm Max. door height: 2700mm Door thickness: 20-44mm

*Extra pivots required if doors will be split (2+2)

- -Bottom Pivot (289B)
- -Top Pivot (289T)



Kit	Door Width
27-665572	Husky 25 Folding Kit (Hf25/12) 2 Leaves - Max 1200mm
27-665573	Husky 25 Folding Kit (Hf25/24) - 4 Leaves* - Max 3000


For timber, timber framed or composite doors For light residential folding partitions Neatly stacking at one or both sides Concealed fixing Floor component - pivot only

Specification:

Max. door weight: 25kg Max. door width: 600mm Max. door height: 2400mm Door thickness: 20-44mm

- *Extra pivots required if doors will be split (2+2)
- -Bottom Pivot (289B) -Top Pivot (289T)

Bifold




Kit	Door Width
27-789132	Bifold Kit B10 - 2 Leaves - Max 1065mm
27-799194	Bifold Kit B15 - 4 Leaves - Max 1525mm
27-799259	Bifold Kit B20 - 4 Leaves - Max 2135mm
27-789262	Bifold Kit B20 - 2 Leaves - Max 2461mm

For timber, timber framed or composite doors
Stable and smooth running
Suitable for jambless openings
Silent and easy to fix - nylon spring-loaded guides with
attractive aluminium top track
Leaves to fold back completely

Specification:

Max. door weight: 14kg Max. door width: 530mm Max door height: 2400mm Door thickness: 25-30mm

Loretto



Kit	Door Width
27-789280	Loretto BTM. Roller Kit D4 - 2 Leaves - Max 1200
27-789314	Loretto BTM. Roller Kit D5 - 2 Leaves - Max 1500mm
27-789345	Loretto BTM. Roller Kit D6 - 2 Leaves - Max 1800mm

For cupboards, bookcases and other good quality cabinet work


For timber framed, glazed or flush doors

Quiet and smooth - nylon guides and rollers, with aluminium rail

Specification:

Max. door weight: 23kg Max. door width: 900mm Max. door height: 1800mm Door thickness: 20-45mm

Sliding Door Gear Cello



 Kit
 Door Width

 27-780000
 Cello 25kg Btm/ Roller Kit C15 - 2 Leaves - Max 1500

 27-780001
 Cello 25kg Btm/ Roller Kit C18 - 2 Leaves - Max 1800mm

 780002
 Cello 25kg Btm/ Roller Kit C24 - 3 Leaves - Max 2400mm

For cupboards and wardrobes

For timber, timber framed or composite doors

Quet and smooth - nylon guides and rollers, with aluminium


rail

easy to install - no routing required

Specification:

Max. door weight: 25 kg Max. door width: 920mm Max door haight: 2400mm Door thickness: 16-40mm

Zenith for Sliding Glass Doors



Kit	Door Width
27-790004	Zenith Btm. Roller Kit Z12 - 2 Leaves - Max 1200mm
27-790035	Zenith Btm. Roller Kit Z15 - 2 Leaves - Max 1500mm
27-790066	Zenith Btm. Roller Kit Z18 - 2 Leaves - Max 1800mm


For showcases, bookcases, display panels, hatches, interior windows and glass doors

A precision made, satin-anodised finish aluminium gear with brush-pile strips

Silent and easy to glide

Specification:

Max. door weight: 25kg Max. door width: 900mm Max. door height: 1800mm Max. glass thickness: 6mm



Kit	Door Width
27-440160 27-440161	Rustic 2M Kit R80-20 - 1000mm (black powder coated) Rustic 3M Kit R80-30 - 1500mm (black poweder coated)
27-440165 27-440135 27-440136 27-440137	Rustic 100 Hanger Kit (black powder coated) Rustic 2M Kit R80-20 - 1000mm (stainless steel) Rustic 3M Kit R80-30 - 1500mm (stainless steel) Rustic 100 Hanger Kit (stainless steel)

Creates traditional look for sliding wooden doors Exposed steel straps fasten down the front of the door to support the rustic finish

The beautifully crafted barn door style hangers run smoothly acress a flat bar track

Robust black powder coat or stainless steel provides a durable finish

Nylon bearing wheels provide a smooth and silent running system

Easy to install

Available in 2m (R80/20) and 3m kits (R80/30)

Tested to 100 000 cycles

Additional kit availabe for 2 door installation

Includes black oval flush pull

Specification (2km Kit R80/20): Max. door weight: 80kg

Min. door width: 500mm Max door width: 1000mm Door thickness: 36-46mm

Specification (3m kit R80/30):

Max. door weight: 80kg Min. door width: 500mm Max. door width: 1500mm Door thickness: 36-46mm

BS EN 1527:2013, ISO9001

Sienna for Sliding Timber Doors



Kit	Door Width
27-440014	Basic Kit 120kg excludes track
27-440100	Sienna Timber Bar Assembly 2.0m (25/2000T)
27-440101	Sienna Timber Bar Assembly 2.5 (25/2500T)
27-440102	Sienna Timber Bar Assembly 3.0m (25/3000T)

Elegant timber door system which creates a minimalistic look For timber doors of between 30-70mm thickness Rollers engineered to run effortlessly along a brushed stainless steel tubular track Stops are positioned on the track to limit the travel of the

Stops are positioned on the track to limit the travel of the door

Specification:

Maximum door panel weight: 120kg

Door thickness: 30-70mm Minimum panel width: 700mm Maximum panel height: 2500mm

Sliding Door Gear

Sienna for Sliding Glass Doors



Kit	Door Width
27-440000	Basic Kit 120kg exluding track
27-440005	Bar 2.0 (requires 4 brackets)
27-440006	Bar 2.5 (requires 5 brackets)
27-440007	Bar 3.0 (requires 6 brackets)
27-440001	Face Fix Brackets for Solid Wall
27-440002	Face Fix Brackets for Glass Wall

Elegant frameless glass door system which creates a minimalistic look

120kg system designed for 8mm, 10mm and 12mm toughened glass

Rollers engineered to run effortlessly along a 25x7.5mm brushed stainless steel tubular track

Designed for use with glass door to glass wall or glass door to solid wall

Stops are positioned on the track to limit the travel of the door

Specification:

Maximum glass panel weight: 120kg

Glass panel thickness: 8mm, 10mm and 12mm

Maximum glass panel width: 1400mm Maximum glass panel height: 2500mm

Pacer




Code	Description
27-668401	Pacer track 2000mm mill finish
27668403	Pacer track 3000mm mill finish
27-668407	Pacer track 6000mm mill finish
27-666401	1B Bracket for face fixing
27-666404	1BX Bracket Joining bracket for face fixing
27-666531	Concealed fixing hanger for wooden, aluminium doors,
	or metal doors
27-666511	Hanger for angle frame metal doors
27-666102	Concealed fixing guide for wooden or aluminium doors
27-666104	Guide for angle frame metals doors
27-727589	Channel 2.0m 94X/2000
27-727668	Channel 3.0m 94X/3000
27-666496	Retaining stop mounted within track

For wooden and metal sliding doors weighing up to 200kg Wooden doors can be either solid or glazed and metal doors can be of angle or box section

Ideal for shop-fronts, offcies and other stylish interiors BS EN 1527:1998

Locksets






Gower Euro Profile Cylinder Lockset (with Cylinder)

UNION
CZ68205222CH
CZ68205222SC
Solid cast zinc handle and zinc backplate
Powder coated lock case
Brass latch and deadbolt
Enhanced durability
Includes 2X28NP Cylinder
Suitable for coastal regions
Suited for external doors
SABS approved
5 Year warranty

Finish

Chrome Satin Chrome




Gower Euro Profile Cylinder Lockset (without Cylinder)

UNION
L-CZ6820522CH
L-CZ6820522SC
Solid cast zinc handle and zinc backplate
Powder coated lock case
Brass latch and deadbolt
Enhanced durability
Suitable for coastal regions
Suited for external doors
SABS approved
5 Year warranty

Finish

Chrome Satin Chrome




Gower 4 Lever Lockset

UNION
CZ6822461CH
CZ6822461SC
Solid cast zinc handle and zinc backplate
Powder coated lock case
Brass latch and deadbolt
Enhanced durability
Suitable for coastal regions
Suited for external doors
SABS approved
5 Year warranty

Finish

Chrome Satin Chrome




Gower 3 Lever Lockset

UNION
CZ6822452CH
CZ6822452SC
Solid cast zinc handle and zinc backplate
Powder coated lock case
Brass latch and deadbolt
Enhanced durability
Suitable for coastal regions
Suited for external doors
SABS approved
5 Year warranty

Finish

Chrome Satin Chrome




Gower 2 Lever Lockset

UNION
CZ6822495CH
CZ6822495SC
Solid cast zinc handle and zinc backplate
Powder coated lock case
Brass latch and deadbolt
Enhanced durability
Suitable for coastal regions
Suited for external doors
SABS approved
5 Year warranty

Finish

Chrome Satin Chrome




Euro Profile Cylinder Lockset (with cylinder)

Yale
CZ694053155CH
Stainless steel backplate with
aluminium handle
Galvanised lock case with zinc
deadbolt and latchbolt
Suited for external doors
SABS approved
3 Year warranty

Finish

Chrome




4 Lever Lockset

Yale
CZ69424615CH
Stainless steel backplate with aluminium handle
Galvanised lock case with zinc deadbolt and latchbolt
Suited for external doors
SABS approved
3 Year warranty

Finish

Chrome




3 Lever Lockset

Yale
CZ69424525CH
Stainless steel backplate with
aluminium handle
Galvanised lock case with zinc
deadbolt and latchbolt
Suited for internal doors
SABS approved
3 Year warranty

Finish

Chrome




2 Lever Lockset

Yale
CZ69424955CH
Steel backplate with aluminium
handle
Galvanised lock case with zinc
deadbolt and latchbolt
Suited for internal doors
SABS approved
3 Year warranty

Finish

Chrome

ESCO Locksets




3 Lever Lockset

ESCO
E3LBX
Steel backplate with iron handle
Galvanised lock case with
aluminium latch and deadbolt
Suitable for internal use
SABS approved
2 Year warranty

Finish

Chrome



2 Lever Lockset


ESCO
E2LBX
Steel backplate with iron handle
Galvanised lock case with
aluminium latch and deadbolt
Suitable for internal use
SABS approved
2 Year warranty


Finish

Chrome

Mortice Locks








2 Lever Dead Lock

UNION 21311-76SS 21311-76PL 2 Lever Lock

Finish

Stainless Steel Polished Brass






4 Lever Dead Lock

UNION 21313-76SS 21313-76PL 4 Lever Lock

Finish

Stainless Steel Polished Brass





Euro Cylinder Dead Lock


UNION L-21315-76SS L-21315-76PL Euro Profile Lock Does not include cylinder

Finish

Stainless Steel Polished Brass

UNION Dead Lock (Commercial)





3 Lever Dead Lock


UNION 2157-78SS 2157-78PL 3 Lever Lock

Finish

Stainless Steel Polished Brass

Keying options: STD, KA, MKD and GMK






Euro Cylinder Dead Lock

UNION L-2109-78SS L-2109-78PL Euro Profile Lock Does not include cylinder

Finish




Euro Cylinder Dead Lock

UNION L-2115-78SS L-2115-78PL Euro Profile Lock Does not include cylinder

Finish

Stainless Steel Polished Brass






Euro Cylinder Roller Dead Lock

UNION L-2115-78SS/R L-2115-78PL/R Euro Profile Lock with adj. roller catch Does not include cylinder Finish

Stainless Steel Polished Brass






Oval Cylinder Dead Lock

UNION L-2141-78SS L-2141-78PL Oval Cylinder Lock Does not include cylinder

Finish

Stainless Steel Polished Brass





Euro Cylinder Dead Lock


TESA 403150HN Euro Cylinder Double throw deadlock Does not include cylinder

Finish

Nickel Plated Steel

UNION Narrow Stile Dead Locks






Euro Cylinder Dead Lock

UNION L-21315-40CH L-21315-40PL Euro Profile Lock Does not include cylinder

Finish





Oval Cylinder Dead Lock

UNION L-2153-40SS L-2153-40PL Oval Profile Lock Does not include cylinder


Finish

Stainless Steel Polished Brass

Sash Locks

UNION Sash Locks (Domestic)







2 Lever Sash Lock

UNION 2295-76SS 2295-76PL 2 Lever Lock

Finish

Stainless Steel Polished Brass






2 Lever Sash Lock

UNION 22311-7615MMCH 2 Lever Lock For cottage pane doors 15mm faceplate for steel doors

Finish

Chrome Plated






3 Lever Sash Lock

UNION 2252-76SS 2252-76PL 3 Lever Lock

Finish

Stainless Steel Polished Brass







3 Lever Sash Lock

UNION 22312-7615MMCH 3 Lever Lock 15mm faceplate for steel doors For cottage pane doors

Finish

Chrome Plated






4 Lever Sash Lock

UNION 2261-76SS 2261-76PL 4 Lever lock

Finish

Stainless Steel Polished Brass






4 Lever Sash Lock

UNION 22313-7615MMCH 4 Lever Lock For cottage pane doors 15mm wide faceplate for steel doors

Finish

Chrome Plated





Euro Cylinder Sash Lock


UNION L-22315-76SS L-22315-76PL Euro Profile Lock

Finish

Stainless Steel Polished Brass

UNION Sash Locks (Commercial)





3 Lever Sash Lock


UNION 2277-78SS 2277-78PL 3 Lever Lock

Finish

Stainless Steel Polished Brass

Keying options: STD, KA, MKD and GMK






5 Lever Sash Lock

UNION 2201-78SC 2201-78PL 5 Lever Lock

Finish






Euro Cylinder Sash Lock

UNION L-2215-78SS/SL L-2215-78BP-SL Euro Profile Lock Lock with silent drawback latch

Finish

Stainless Steel Polished Brass






Euro Cylinder Sash Lock

UNION L-2209-78SS L-2209-78PL Euro Profile Lock 49.5mm centres

Finish

Stainless Steel Polished Brass






Oval Cylinder Sash Lock

UNION L-2241-78SS L-2241-78PL Oval Profile Lock

Finish

Stainless Steel Polished Brass






Euro Cylinder Sash Lock

UNION L-23803-85SS Euro Profile Lock Lock with drawback latch and anti-thrust snib

Finish

Stainless Steel






Euro Cylinder Emergency Sash Lock

UNION L-2349-78SS L-2349-78PL Euro Profile Lock Mortice night latch

Finish






Oval Cylinder Emergency Sash Lock

UNION L-2341-78SS L-2341-78PL Oval Profile Lock Mortice night latch

Finish

Stainless Steel Polished Brass






Euro Cylinder Spring Latch & Deadbolt Lock

UNION Q60X85MM-SS Q60X85MM-PB Q50X85MM-SS Q50X85MM-PB Euro Profile Commercial Lock

Finish

Stainless Steel Polished Brass





Euro Cylinder Roller Latch & Deadbolt Lock


UNION
QR60X85MM-SS
QR60X85MM-PB
QR50X85MM-SS
QR50X85MM-PB
Euro Profile Commercial Lock


Finish

Stainless Steel Polished Brass

Sliding Door Locks

UNION Sliding Door Locks (Domestic)






4 Lever Claw Bolt Lock

UNION 24313-76SS 24313-76PL 4 Lever Lock

Finish

Stainless Steel Polished Brass






Euro Cylinder Claw Bolt Lock

UNION L-24315-76SS L-24315-76PL Euro Profile Lock

Finish





3 Lever Claw Bolt Lock


UNION 2457-78SS 2457-78PL 3 Lever Lock

Finish

Stainless Steel Polished Brass

Keying options STD, KA, MKD and GMK






Oval Cylinder Claw Bolt Lock

UNION L-2441-78SS L-2441-78PL Oval Profile Lock

Finish

Stainless Steel Polished Brass





Euro Cylinder Hook Lock


UNION QH50X85MM-SS Euro Profile Commercial Lock

Finish

Stainless Steel

Latch Locks UNION Latch Locks






Latch Lock

UNION 26310-76SS 26310-76PL Domestic latch lock

Finish

Stainless Steel Polished Brass






Latch Lock

UNION 2657-78SS 2657-78PL Commercial latch lock

Finish






3 Lever Sash Lock

UNION 2277-64SS 2277-64PL 3 Lever Lock Commercial

Finish

Stainless Steel Polished Brass






4 Lever Wing Bolt Sliding Door Lock

UNION 24313-55CH 24313-55PL 4 Lever Domestic Lock

Finish

Chrome Plated Polished Brass






Euro Cylinder Claw Bolt Sliding Door Lock

UNION L-24315-40CH L-24315-40PL Euro Profile Lock Domestic

Finish

Chrome Plated Polished Brass





Euro Cylinder Wing Bolt Sliding Door Lock

UNION L-24315-55CH L-24315-55PL Euro Profile Lock Domestic


Finish

Chrome Plated Polished Brass

UNION Narrow Stile Locks

UNION Narrow Stile Locks for Aluminium Doors






Euro Cylinder Dead Bolt Lock

UNION QD25X85MMSW-SS QD35X85MMSW-SS Euro Profile Commercial Lock Swing Dead Bolt

Finish

Stainless Steel






Euro Cylinder Latch & Dead Bolt Lock UNION Q25X85MMSW-SS Q35X85MMSW-SS Euro Profile Commercial Lock Swing Dead Bolt

Finish

Stainless Steel






Euro Cylinder Roller Latch & Dead Bolt Lock
UNION
QR25X85MMSW-SS
QR35X85MMSW-SS
Euro Profile Commercial Lock
Swing Dead Bolt

Finish

Stainless Steel




Euro Cylinder Hook Lock

UNION QH25X85MM-SS QH35X85MM-SS Euro Profile Commercial Lock Swing Hook Lock

Finish

Stainless Steel





Euro Cylinder Latch & Hook Lock UNION QHL25X85MM-SS


QHL35X85MM-SS Euro Profile Commercial Lock Swing Hook Lock

Finish

Stainless Steel

Bathroom W/C Locks Bathroom W/C Locks






Bathroom Dead Lock

UNION 21314-76SS 21314-76PL W/C 5mm follower Domestic

Finish






Bathroom Dead Lock


UNION 21314-76/8SS 21314-76/8PL W/C 8mm follower Domestic

Finish

Stainless Steel Polished Brass








Bathroom Dead Lock

UNION SS2016SS 8mm follower

Finish

Stainless Steel







Bathroom Sash Lock

UNION 22314-76/5SS 22314-76/5PL W/C 5mm follower Domestic

Finish

Stainless Steel Polished Brass






Bathroom Sash Lock

UNION 22314-76/8SS 22314-76/8PL W/C 8mm follower Domestic

Finish

Stainless Steel Polished Brass






Bathroom Sash Lock

UNION 2226-78SS 2226-78PL W/C 5mm follower Commercial

Finish

Bathroom W/C Locks Bathroom W/C Locks





Bathroom Sliding Door Lock

UNION 24314-76SS 24314-76PL W/C 5mm follower Commercial

8mm options: 24314-76/8SS

Finish

Nightlatches & Rimlocks





Digital Door Lock

Finish


Yale YDC01Y3SN Smart Door Lock For entry utilises: Bullet key card Bullet fob Bullet pin code Satin Chrome



Nightlatch

Finish

UNION 1022G Nightlatch with cylinder dimple key 1022-KB Nightlatch with cylinder - KB502 keyway **Brass Plated**




Nightlatch

Finish

UNION L-1022G Nightlatch without cylinder **Brass Plated**






Rim Lock

Finish

UNION 1445BJ Black powder coated rim lock with 2 keys Black powder coated






Rim Lock

Finish

UNION 1448BJ2 Black powder coated rim lock with 2 keys Black powder coated






Rim Lockset

UNION 1448-5248PX2 Rim lockset complete with plastic knob furniture

Finish

Black powder coated



Rim Lock

UNION 1465BJ2 3 Lever rim lock with 2 keys (left handed) 1465BJ2-RH 3 Lever rim lock with 2 keys (right handed)

Finish

Black powder coated



Rim Lock Furniture

UNION 5248PX Plastic knob furniture

Finish

Brown Plastic



Rim Lock Furniture

UNION 5249PL Pressed brass knob furniture

Finish

Brass Plated

Campus Locks 60mm Centres





Campus Furniture Set

UNION 152x176mm backplate SS6D67L-05CAM60 SS6D67R-05CAM60 200x176mm backplate SS6D87L-05CAM60 SS6D87R-05CAM60

Finish

Stainless Steel



Cylinder Sash Lock


UNION L-2215-78SS/SL Euro profile upright lock with drawback latch

Finish

Stainless Steel

72mm Centres






Campus Furniture Set

UNION 152x176mm backplate SS6D67L-05CAM72 SS6D67R-05CAM72 200x176mm backplate SS6D87L-05CAM72 SS6D87R-05CAM72

Finish

Stainless Steel





Cylinder Sash Lock

UNION L-23803-85SS Euro profile sash lock with drawback latch and anti-thrust snib

Finish

Stainless Steel



Thumb Turn Euro Profile Cylinder

UNION 2X19SC Available as: Keyed alike - 2X19SCKA Master keyed - 2X19SCMKD Cylinder applicable to all campus locks

Finish


Satin Chrome

Glass Solutions




Bottom Door Patch

Bottom Door Patch







Bottom Door Patch


UN-P010SSS Bottom door patch to suit floor springs

Finish

Satin Stainless Steel

Top Door Patches

Top Door Patch




Top Door Patch

UN-P020SS Top patch for 15mm pivot


Finish

Satin Stainless Steel

Top Door Patch for Transom Closer








Top Door Patch for Transom Closer


UN-P022SSS Top patch used with transom closer

Finish

Top Door Patches

Top Door Patch with 15mm Pivot






Over Panel Patch

UN-P030SSS Satin Top panel patch for 15mm pivot Steel

Finish

Satin Stainless

Top Door Patch for Over & Side Panel



Over Panel Patch


UN-P040SSS Top patch for over and side panel with 15mm pivot

Finish

Satin Stainless Steel

Patch for Over Panel

Patch for Over Panel with Side Fin




Over Panel Patch

UN-P041RSSS UN-P041LSSS Patch for over panels and side panels with fin fitting

Finish

Corner Connect Fitting

Corner Connect Fitting



Corner Fitting


UN-P060SSS UN-P061SSS Corner connecting fitting complete with stop UN-P060SSS Corner connect fitting

Finish

Satin Stainless Steel

Over Panel Connector

Over Panel Connector






Over Panel Connector

UN-P070SSS Over panel connector complete with stop

Finish

Satin Stainless Steel

Corner Euro Profile Cylinder Corner Euro Profile Cylinder






Corner Lock

UN-L010SSS Euro profile cylinder lock for corner fitting

Finish

Centre Lock Euro Profile Cylinder Centre Lock Euro Profile Cylinder



Centre Lock


UN-L020SSS Euro profile cylinder lock for centre fitting

Finish

Satin Stainless Steel

Strike Box

Strike Box




Strike Box

UN-S020SSS Double over panel strike box

Finish

Satin Stainless Steel




Strik Box

UN-S050SSS Corner strike box

Finish

Strike Box

Strike Box




Strike Box

UN-S040SSS Corner over panel strike box

Finish

Satin Stainless Steel




Strike Box

UN-S030SSS Single over panel strike box

Finish

Satin Stainless Steel

Top Centre Top Centre



Top Centre

UN-PT24 Used for top door patch recessed into concrete+F9

Rails Rails




Bottom Rail with Lock

UN-RAIL1 and UN-RAIL2 To suit German Spindle Aluminium body Cover 1000mm and 1500mm

Finish

Satin Stainless Steel



Top Rail


UN-RAIL3 and UN-RAIL4 To suit German Spindle Aluminium body Cover 1000mm and 1500mm

Finish

Satin Stainless Steel

Glass Door Shoes

Glass door Shoes



Glass Door Shoe

DCA164-EV1 DCA165-EV1 DCA166-EV1 Available for: DC200, DC300 and DC500/700 Door Closers

Padlocks



Padlock and part number information

Modlock & Laminated Padlock Colours

XX is used in the part numbers. Each modlock colour is inserted into the part number for ordering purposes. Substitute XX with the number that represents the colour of your choice.

Modlock colours:

46 - Black	53 - Brown
47 - Red	56 - White
48 - Blue	58 - Purple
49 - Yellow	54 - Lime Green
50 - Green	57 - Light Blue
52 - Orange	59 - Pink

Laminated Padlock colours:

46 - Black	50 - Green
47 - Red	52 - Orange
48 - Blue	53 - Brown
49 - Yellow	56 - White

Nylon Lockout Padlock

Colours are denoted by a suffix in the part number

BRN - Brown	PUP - Purple
YEL - Yellow	GRN - Green
BLU - Blue	WHT - White

RED - Red SIL - Silver - only available in aluminium BLK - Black PNK - Pink - only available in aluminium

ORG - Orange



Need marked padlocks for easy identification?

Padlocks can be ordered with special markings for identification under the part number 15000000S



Components

Mushroom springs Mushroom Driver Pins Closing Pin 2.5mm Master Pins 2.5mm Key Pins

Padlock Keying Options

ABC - Cascading Master Key System

KD - Keyed to differ KA - Keyed Alike MKD - Master Keyed

GMK - Grand Master Keyed PMU - Partially Made Up

Keyway Profiles

Profiles can be chosen for master key and keyed alike systems. Where Y features in a part number, replace with profile number

0 - Standard profile V01

1 - UNION profile

033 or 035 - Alternative profile

Please note:

Extra keys are available on request.

Master keyed padlocks are supplied with 2 keys per padlock on new systems. Existing systems are supplied without keys. Additional keys can be supplied on provision of permission letter from the registered end user.





30mm Padlock Hardened Steel Shackle

UN333000000000

30mm brass padlock with 15mm hardened steel shackle

Ideal for use on lockers

Not recommended for coastal use

Available as keyed to differ, keyed alike or partially made up





30mm Padlock Stainless Steel Shackle

UN333000000200

30mm brass padlock with 15mm stainless steel shackle

Corrosion resistant

Suitable for coastal environments

Available as keyed to differ, keyed alike or partially made up





30mm Padlock Hardened Steel Long Shackle

UN333002003200

30mm brass padlock with 32mm hardened steel shackle

Not recommended for coastal use

Available as keyed to differ, keyed alike or partially made up

40mm Padlocks





40mm Padlock Hardened Steel Shackle

UN334000000000

40mm brass padlock with 20mm hardened steel shackle

Ideal for use on tool boxes and trailers Not recommended for coastal use

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up

Padlocks 40mm Padlocks





40mm Padlock Stainless Steel Shackle

UN334000000030

40mm brass padlock with 20mm stainless shackle Ideal for use on tool boxes and trailers Suitable for coastal use

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up





40mm Padlock Hardened Steel Long Shackle

UN334002006300

40mm brass padlock with 63mm hardened steel shackle

Ideal for use on electrical panels

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up

50mm Padlocks





50mm Padlock Hardened Steel Shackle

UN335000000000

50mm brass padlock with 28mm hardened steel shackle

Ideal for external gates, sheds and storerooms

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up





50mm Padlock Hardened Steel Shackle

UN335000000030

50mm brass padlock with 035 keyway and 28mm hardened steel shackle

Ideal for external gates, sheds and storerooms

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up





50mm Padlock Hardened Steel Long Shackle

UN335002006300

50mm brass padlock with 63mm hardened steel shackle

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up





50mm Padlock Stainless Steel Shackle

UN335000000200

50mm brass padlock with 28mm stainless steel shackle

Ideal for use with a chain for added security

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up





50mm 3122 Replacement Padlock

UN335000500210

50mm brass padlock with 6mmx28mm stainless steel shackle 3122 series
Can be master keyed with a cylinder profile
Suited for coastal use
6mm shackle diameter

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up





50mm 3122 Replacement Padlock

UN335000000210

50mm brass padlock with 8mmx28mm stainless steel shackle 3122 series Can be master keyed with a cylinder profile Suited for coastal use 8mm shackle diameter

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up





50mm Padlock Stainless Steel Shackle

UN335000000230

50mm brass padlock with 035 keyway and 28mm stainless steel shackle Suitable for coastal use

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up

Padlocks 60mm Padlocks





60mm Padlock Hardened Steel Shackle

UN336000000000

60mm brass padlock with 35mm hardened steel shackle

Ideal for trucks and containers

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up

70mm Padlocks





70mm Padlock Hardened Steel Shackle

UN337000000000

70mm brass padlock with 42mm hardened steel shackle

Ideal for trucks and containers

Available as keyed to differ, keyed alike, master keyed, ABC or partially made up

78mm Insurance Padlocks






78mm Insurance Padlock

UN3845000XX2Y0

78mm insurance grade brass padlock with concealed hardened steel shackle Ideal for roller shutter doors, gate motors and shop fronts

Better security due to limited access to shackle Available as keyed to differ, keyed alike, master keyed or ABC





78mm Insurance Padlock


UN337800000030

78mm insurance grade brass padlock with 035 concealed hardened steel shackle Ideal for roller shutter doors, gate motors and shop fronts

Better security due to limited access to shackle

Available as keyed to differ, keyed alike, master keyed or ABC






78mm Armoured Padlock

UN337800090000

78mm armoured brass padlock with concealed hardened steel shackle Stainless steel armoured jacket for added security Suitable for coastal use

Available as keyed to differ, keyed alike, master keyed or ABC





78mm Armoured Padlock


UN337800090030

78mm armoured brass padlock with 035 keyway concealed hardened steel shackle Stainless steel armoured jacket for added security Suitable for coastal use

Available as keyed to differ, keyed alike, master keyed or ABC

Nylon Padlocks (Modlock)







45mm Nylon Padlock

UN337800000000


45mm nylon padlock with 20mm 316 stainless steel shackle

Ideal for electrical environments (inside & outside) fire-retardant nylon

Available as keyed to differ, keyed alike, master keyed or ABC

Colours available: purple, brown, yellow, blue, red, black, orange, lime green, white





45mm Nylon Padlock

UN3845008XX200

45mm nylon padlock with 28mm long 316 stainless steel shackle Ideal for electrical environments (inside & outside) fire-retardant nylon


Available as keyed to differ, keyed alike, master keyed or ABC

Colours available: purple, brown, yellow, blue, red, black, orange, lime green, white, green

Padlocks

Nylon Padlocks (Modlock)





45mm Nylon Padlock


UN3845002XX2Y0

45mm nylon padlock with 40mm long 316 stainless steel shackle Ideal for electrical environments (inside & outside) fire-retardant nylon

Available as keyed to differ, keyed alike, master keyed or ABC

Colours available: purple, brown, yellow, blue, red, black, orange, lime green, white, green





50mm Nylon Padlock


UN3850000XX2Y0

50mm nylon padlock with 20mm standard 316 stainless steel shackle
Higher security nylon padlock
Ideal for electrical environments (inside & outside)
fire-retardant nylon

Available as keyed to differ, keyed alike, master keyed or ABC

Colours available: brown, yellow, blue, red, black, orange, white, green





50mm Nylon Padlock


UN3850005XX2Y0

50mm nylon padlock with 30mm standard 316 stainless steel shackle Higher security nylon padlock Ideal for electrical environments (inside & outside) fire-retardant nylon

Available as keyed to differ, keyed alike, master keyed or ABC

Colours available: brown, yellow, blue, red, black, orange, white, green





50mm Nylon Padlock


UN3850002XX2Y0

50mm nylon padlock with 48mm 316 standard stainless steel shackle Higher security nylon padlock Ideal for electrical environments (inside & outside) fire-retardant nylon

Available as keyed to differ, keyed alike, master keyed or ABC

Colours available: brown, yellow, blue, red, black, orange, white, green





40mm Laminated Steel Padlock


UN3540008XX2Y0

40mm laminated steel padlock with 28mm 316 stainless steel shackle with waterproof plastic jacket and protective boot Ball locking mechanism Stronger and more secure

Available as keyed to differ, keyed alike, master keyed or ABC

Colours available: black, blue, yellow, green, orange and white, red





38mm Nylon Lockout Padlock

UN4044

38mm nylon lockout padlock with 50mm long 316 stainless steel shackle

Key retaining

Used to lock-out machinery that is undergoing maintenance

6 pins offering better security due to more key differs

Available as keyed to differ, keyed alike, master keyed or ABC

Finish:

White, purple, red, brown, orange, black, yellow, green and blue

Padlocks

Nylon Padlocks (Modlock)





38mm Aluminium Lockout Padlock

UN5055

38mm Aluminium lockout padlock with 32mm long hardened steel shackle

Used to lock-out machinery that is undergoing maintenance

Can be used in high heat environments 6 pins offering better security due to more key differs


Available as keyed to differ, keyed alike, master keyed or ABC

Finish:

Red, brown, black, yellow, blue, pink, purple, green, silver and orange

Padlock Accessories






Lockout Hasp

LX1964

Padlock locking plate with 6 individual locking holes 25mm Used with UN4044 & UN5055





Lockout Hasp


LX1964-38UN

Padlock locking plate with 6 individual locking holes 38mm

Added lip on jaws to prevent forced opening

Red cover






47mm Padlock with 8mm Boron Shackle

MG47-7 MG47I MG47C

47mm padlock with 8mm boron shackle and brass body nickel plated Boron shackle offers higher level of security Available in either patented or non-patented platforms

Available as standard, keyed alike, master keyed and grand master keyed Platforms: Classic, Interactive & 7x7 Patented platforms: Interactive





47mm Padlock with 8mm Boron Shackle


MG47P-7 MG47PI MG47PC

47mm padlock with 8mm protected boron shackle and brass body nickel plated Protected shackle makes it harder to access shackle Boron shackle offers higher level of security Available in either patented or non-patented platforms

Available as standard, keyed alike, master keyed and grand master keyed Platforms: Classic, Interactive & 7x7

Patented platforms: Interactive & 7x





55mm Padlock with Boron Shackle

MG55-7 MG55I MG55C


55mm padlock with 8mm boron shackle and brass body nickel plated Boron shackle offers higher level of security Available in either patented or non-patented platforms

Available as standard, keyed alike, master keyed and grand master keyed

Platforms: Classic, Interactive & 7x7 Patented platforms: Interactive

Padlocks Mul-T-Lock G-Series





55mm Padlock with Boron Shackle


MG55P-7 MG55PI MG55PC

55mm padlock with 8mm protected boron shackle and brass body nickel plated Protected shackle makes it harder to access shackle Boron shackle offers higher level of security Available in either patented or non-patented platforms

Available as standard, keyed alike, master keyed and grand master keyed
Platforms: Classic, Interactive & 7x7
Patented platforms: Interactive

Mul-T-Lock C-Series






50mm Padlock with 8mm Hardened Steel Shackle

MC8 MC8I

50mm padlock with 8mm hardened steel shackle and hardened steel body High security padlock

Available as standard, keyed alike, master keyed and grand master keyed
Platforms: Interactive & Classic
Patented Platforms: Interactive





63mm Padlock with 10mm Hardened Steel Shackle

MC10 MC10I

63mm padlock with 10mm hardened steel shackle and hardened steel body High security padlock

Available as standard, keyed alike, master keyed and grand master keyed
Platforms: Interactive & Classic

Patented Platforms: Interactive





73mm Padlock with 13mm Hardened Steel

MC13 MC13I

73mm padlock with 13mm hardened steel shackle and hardened steel body High security padlock

Available as standard, keyed alike, master keyed and grand master keyed Platforms: Interactive & Classic Patented Platforms: Interactive





92mm Padlock with 16mm Hardened Steel

MC16 MC16I

92mm padlock with 16mm hardened steel shackle and hardened steel body High security padlock

Available as standard, keyed alike, master keyed and grand master keyed
Platforms: Interactive & Classic
Patented Platforms: Interactive






92mm Padlock with 16mm Hardened Steel

MC16 MC16I

92mm padlock with 16mm hardened steel shackle and hardened steel body High security padlock

Available as standard, keyed alike, master keyed and grand master keyed Platforms: Interactive & Classic Patented Platforms: Interactive





52mm Padlock with 13mm Hardened Steel

MC35 MC35I


52mm padlock with 13mm steel shackle and hardened steel body High security padlock Ideal for use on shutter doors

Available as standard, keyed alike, master keyed and grand master keyed
Platforms: Interactive & Classic

Platforms: Interactive & Classic Patented Platforms: Interactive

Padlocks Mul-T-Lock NE-Series





54mm Padlock with 8mm hardened boron shackle


MNE-8GI

54mm padlock with 8mm hardened boron shackle High security padlock for general use key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive





54mm Padlock with 10mm hardened boron shackle

MNE-10LI


*54mm padlock with 10mm hardened boron shackle

High security padlock for general use with protective shutter preventing dust build-up Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive





54mm Padlock with 10mm hardened boron shackle

MNE-10GI


54mm padlock with 10mm hardened boron shackle

High security padlock for general use Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive





54mm Padlock with 10mm protected hardened boron shackle

MNE-10HI

54mm padlock with 10mm protected hardened boron shackle

High security padlock with protected shackle making it difficult to tamper with shackle Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive



64mm Sliding Bolt Padlock with 10mm hardened boron shackle

MSB-10GI


64mm Sliding bolt padlock with 10mm hardened boron shackle

High security padlock for use on shutter doors Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive





66mm Padlock with 12mm hardened boron shackle

MNE-12LI

66mm Padlock with 12mm hardened boron shackle


High security padlock with protective shutter preventing dust build-up

Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive





66mm Padlock with 12mm protected hardened boron shackle

MNE-12HI

66mm Padlock with 12mm protected hardened boron shackle


High security padlock with protected shackle making it difficult to tamper with shackle Protective shutter prevents dust build-up Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive







80mm Sliding Bolt Padlock with 12mm hardened boron shackle

MSB-12GI

80mm Sliding bolt padlock with 12mm hardened boron shackle


High security padlock for use on shutter doors with protective shutter preventing dust build-up Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive

Padlocks Mul-T-Lock NE-Series





66mm Padlock with 14mm hardened boron shackle

MNE-14LI

66mm Padlock with 14mm hardened boron shackle


High security padlock with protective shutter preventing dust build-up

Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive





66mm Padlock with 14mm protected hardened boron shackle

MNE-12HI

66mm Padlock with 14mm protected hardened boron shackle


High security padlock with protected shackle making it difficult to tamper with shackle Protective shutter prevents dust build-up Key retaining

Available as standard, keyed alike, master keyed and grand master keyed

Patented platform: Interactive

Mul-T-Lock Hasp Lock





Hasp Lock

M51232716 Padlock and hasp in one unit Prevents loss of padlock

Key retaining / non-retaining

Dust cover

Drill protection

Welded or bolted


Material:

Body: hardened steel investment casting Bolt: 13 mm, hardened, and non-removable

Patented platform: Interactive

ABLOY Padlocks







PL321

A strong padlock for storage doors, gates and windows and trailers

Body Material: Brass


Shackle Material: Stainless Steel

Available as standard, keyed alike, master keyed and

grand master keyed

Available in Protec2 and Sentry platforms Patented platforms: Protec2 and Sentry







PL330

All purpose padlock of durable construction for storage doors, motorcycles, gates, trailers, power station switches and similar applications.

Body Material: Brass

Shackle Material: Stainless Steel

Available as standard, keyed alike, master keyed and grand master keyed

Available in Protec2, Sentry, and Novel platforms Patented platforms: Protec2, Sentry and Novel








Extra-strong padlocks for applications where high security is required


Ideal for construction equipment, tractor trailers and remote storage areas, trucks, storage bins, roller shutter doors, motorcycles and warehouses. Body Material: Case-hardened steel Shackle Material: Case-hardened boron steel

Available as standard, keyed alike, master keyed and grand master keyed

Available in Protec2, Sentry, and Novel platforms Patented platforms: Protec2, Sentry and Novel








Strong padlock for the doors, windows and gates of storage facilities, trailers, protective bars, storage lockers

Body Material: Brass

Shackle Material: Case-hardened boron steel Available as standard, keyed alike, master keyed and grand master keyed

Available in Protec2 and Sentry platforms Patented platforms: Protec2 and Sentry





PL342

For applications where maximum security is required


Raised shoulders and a top loaded cylinder provide the highest level of security and protection Typical applications include containers, railway wagons, trucks, heavy sliding doors and military uses

Body Material: Case-hardened steel Shackle Material: Case-hardened boron steel Available as standard, keyed alike, master keyed and grand master keved

Available in Protec2 and Sentry platforms Patented platforms: Protec2 and Sentry

Padlocks ABLOY Padlocks






PL350

Extra-strong padlocks for applications where high security is required

Ideal for construction equipment, tractor trailers and remote storage areas, trucks, storage bins, roller shutter doors, motorcycles and warehouses. Body Material: Case-hardened steel Shackle Material: Case-hardened boron steel Available as standard, keyed alike, master keyed and grand master keyed

Available in Protec2, Sentry, and Novel platforms Patented platforms: Protec2, Sentry and Novel





PL362

For applications where maximum security is required

Raised shoulders and a top loaded cylinder provide the highest level of security and protection Typical applications include containers, railway wagons, trucks, heavy sliding doors and military uses

Body Material: Case-hardened steel Shackle Material: Case-hardened boron steel Available as standard, keyed alike, master keyed and grand master keyed


Available in Protec2 and Sentry platforms Patented platforms: Protec2 and Sentry

NOTES

New SMARTair® Knob Cylinder

The new SMARTair® knob cylinder: a door device improved in every way. It is more resistant to attack. It comes in more finishes and colours, upgrading aesthetics and functionality

in equal measure. Suitable for any door, it quickly upgrades your existing mechanical cylinder to an access controlled cylinder. Without any drilling.



Openow™ Compatible with all forms of intelligence

Welcome to the future of access control. Our knob cylinder also offers a new way to open your doors — using the Openow™ mobile app. Site users no longer carry separate credentials, just their smartphone. Security and facility managers boost their efficiency, sending, cancelling and modifying virtual keys when they choose.







Johannesburg - Head Office

176 Progress Road Technikon Roodepoort Tel: +27 11 761 5000 Fax: +27 11 766 3573

Cape Town

Northgate Business Park 10 Gold Street, Northgate Estate Brooklyn Tel: +27 11 531 0770

Durban

91 Escom Road, New Germany IDS Electronics Building Durban Tel: +27 31 001 0711 Fax: +27 31 312 5151

Port Elizabeth

60 5th Avenue Newton Park Port Elizabeth Tel: +27 41 364 1565 Fax: +27 41 364 1431